

TECHNICAL NOTE

D-1443

TIME-DEPENDENT STRUCTURE OF THE UPPER ATMOSPHERE

Isadore Harris and Wolfgang Priester
Goddard Space Flight Center
Greenbelt, Maryland

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
WASHINGTON
July 1962

		-

TIME-DEPENDENT STRUCTURE OF THE UPPER ATMOSPHERE

by
Isadore Harris and Wolfgang Priester
Goddard Space Flight Center

SUMMARY

The physical properties of the upper atmosphere are determined principally by heat conduction, heat sources, and the barometric law. An analysis of the integro-differential equation describing these physical processes has been carried out. It is found that heating of the thermosphere due to absorption of the solar extreme ultraviolet (EUV) radiation alone cannot explain the observed diurnal variation of density and temperature, since it would yield a maximum of these properties at about 17^h local time, instead of 14^h where it is observed. Secondly, if the EUV flux is adjusted to give the observed average temperature, then the amplitude of the diurnal density variation would be much too large compared to the observed amplitude. Thirdly, it would require an extremely high efficiency for the conversion of EUV radiation into heat (i.e., comparing the required flux with Hinteregger's measurements of the EUV flux). Thus, it is necessary to have another heat source in addition to the absorption of EUV radiation. If an additional heat source is used, with a maximum at about 9h local time and a flux of 1 erg/cm² -sec, a time-dependent model of the upper atmosphere is obtained that is in good agreement with the observed densities. There is evidence that this additional heat source derives its energy ultimately from the solar corpuscular radiation.

The results of calculations are presented for a model in the equatorial and temperate zones of the earth for those times when the average solar activity corresponds to a solar radiation flux of 200×10^{-22} W/m²-cps at 10.7 cm wavelength. The physical properties (temperature, density, pressure, scale height, mean molecular weight, and the number densities of N_2 , O_2 , O_3 , O_4 ,

			٠

CONTENTS

Summary	i
INTRODUCTION	1
HEAT CONDUCTION EQUATION FOR A GAS IN EQUILIBRIUM WITH A GRAVITATIONAL FIELD	4
INTERPRETATION OF RESULTS	11
ACKNOWLEDGMENTS	19
References	19
Appendix A Properties of the Upper Atmosphere as	23

TIME-DEPENDENT STRUCTURE OF THE UPPER ATMOSPHERE

by
Isadore Harris and Wolfgang Priester*

Goddard Space Flight Center

INTRODUCTION

The energy balance of the upper atmosphere is determined principally by absorption of solar energy and heat transfer by conduction. These processes are described by the time-dependent equation for heat conduction and by the heat source functions. If these equations are combined with the equation for hydrostatic balance they yield the physical properties of the upper atmosphere as functions of time and altitude.

The solutions of these equations have been studied in detail by a process of numerical integration, and the results have been compared with time-dependent models derived from satellite density data, to obtain some information on the nature of upper atmosphere heat sources.

During the past three years, four main types of phenomena have been found to affect the physical properties of the upper atmosphere; this information was obtained mostly from analysis of the fluctuations in the orbital periods of artificial satellites. Any theoretical model of the upper atmosphere should be able to account for the following phenomena:

the solar activity effect, the diurnal variation, the geomagnetic activity effect, and the semiannual variations.

The solar activity effect is defined as the correlation found between density fluctuations in the altitude range from 200 to 1600 km and the solar flux in the decimeter (3 to 30 cm) wavelength range (References 1-9). This correlation has again been confirmed by Jacchia and Slowey (Reference 10) in their analysis of the orbit of the 12-foot balloon satellite (1961 delta 1).

^{*}National Academy of Sciences-National Research Council Senior Research Associate with the National Aeronautics and Space Administration's Institute for Space Studies; on leave from Bonn University Observatory.

The solar decimeter radiation cannot be the physical cause of the fluctuations but is merely an index of it. This radiation in the wavelength range from 3 to 30 cm is the so-called "slowly varying component" produced, according to Waldmeier and Müller (Reference 11), by thermal emission from condensations in the solar corona. This flux is proportional to $A \int n_e n_i \, ds$, integrated along the ray path through the condensation, where n_e and n_i represent the number densities of electrons and ions respectively and A the projected area of the condensation.

The solar activity effect in the upper atmosphere is believed to be caused to a large extent by the heating due to absorption (photoionization) of solar extreme ultraviolet (EUV) radiation. Hinteregger (Reference 12) has shown from rocket observations that the absorption of this radiation occurs in the altitude range between 150 and 300 km.

The main process producing the emission lines in the extreme ultraviolet is likely to be the emission due to cascades following recombination on excited levels. Consequently, the total intensities of these lines can also be expected to be proportional to the aforementioned integral, if self-absorption is negligible. A close correlation can reasonably be expected between the decimeter flux and the strongest lines in the extreme ultraviolet range of the solar spectrum — He II at 304 A, He I at 584 A, and numerous lines of highly ionized atoms — since these lines should also originate mostly in the coronal condensations.

The proportionality factor between density and the decimeter flux is observed to be a function of height and local time and is larger during the nighttime. This behavior is to be expected from the diurnal variation of the temperature in the atmosphere (References 13 and 14).

The diurnal density variation has an amplitude which increases with altitude. At 210 km it is only a few percent of the mean value according to the orbital analysis (Reference 15) of the Sputnik III rocket and satellite (1958 δ_1 and δ_2). At an altitude of 650 km, however, the amplitude reaches a factor of almost ten, as found by Priester and Martin (Reference 5), Jacchia (Reference 16), Paetzold and Zschörner (Reference 17), King-Hele and Walker (Reference 18). The data showing this effect were obtained mostly from Vanguard I and II (1958 β_2 and 1959 α_1). These data also revealed that in the diurnal variation the density reaches its peak at approximately 14 hocal time, then declines, and at about sunrise the density again begins to increase rapidly to its peak value. This behavior results from the combined action of a time-dependent heat source and thermal conduction. This was pointed out by Nicolet (Reference 19).

The geomagnetic activity effect in the upper air densities was noted by Jacchia (Reference 19) as a correlation between the short-lived density fluctuations and the geomagnetic activity represented by the K_p or A_p indices. This effect was confirmed by density data obtained from seven satellites during the "November 1960 events" (References 20

and 21). It was also confirmed by Jastrow and Bryant (Reference 9) who used the data from Echo I, and was further verified by Paetzold (Reference 22) who used the data from Sputnik II (1958 δ_2). The closest correlation of this kind has been obtained with data from the twelve-foot balloon satellite Explorer IX (1961 δ_1) by Jacchia and Slowey (Reference 10).

This effect strongly suggests the existence of another heat source in addition to the absorption of solar EUV radiation. It seems plausible to attribute this additional heat source to energy that is ultimately derived from the solar corpuscular radiation or from its "steady" component, the solar wind.

The existence of such an additional heat source also is suggested by the fourth effect, a semiannual variation in atmospheric density found by Paetzold and Zschörner (Reference 17) with maxima in March and September and minima in June and July and also in December and January. This behavior is quite similar to the semiannual variation of geomagnetic activity found by Cortie (Reference 23) and discussed in great detail by Bartels (Reference 24).

Paetzold and Zschörner (Reference 25) estimate that a decrease of 0.2 erg/cm²-sec in the overall flux used for heating during the minima (June-July and December-January) is required to explain the observed decrease in density. This suggests that the second heat source, which we shall call a "corpuscular" heat source, normally provides an energy flux that is a few times larger than the aforementioned value of 0.2 erg/cm²-sec. A crude estimate may also be obtained from the absolute value and the variation of the geomagnetic u-measure defined by Bartels (Reference 24) as the "inter-diurnal variability of the horizontal component at the geomagnetic equator." In a recent paper by Priester and Cattani (Reference 26) the semiannual variation of the u-measure was related to a model of the solar corpuscular radiation dependent on heliographic latitude.

In view of this relationship and with roughly 20 percent semiannual variation in the amplitude of the u-measure, we might expect a corpuscular heat source with a total flux in the order of 1 erg/cm²-sec. The measurements from Explorer X by Bridge et al. (Reference 27) revealed a flux of about 5 ergs/cm²-sec for the solar wind outside the earth's magnetosphere; thus the present estimate of 1 erg/cm²-sec for the "corpuscular" heat source seems plausible. Since this heat source is likely to have a diurnal variation, the estimated flux given refers to the diurnal peak value.

These conclusions are supported by the results obtained from the calculations presented herein of the energy balance of the upper atmosphere, in which the time-dependent heat conduction equation was used with the condition of quasi hydrostatic equilibrium. These results showed that a theoretical explanation of the observed atmospheric densities can be obtained only by considering a second heat source which contributes approximately the same amount of heat to the upper atmosphere as the EUV heat source.

In this solution, which represents the observed densities, a peak flux of 0.93 erg/cm²-sec was used for the fraction of the solar EUV radiation converted into heat and a peak flux of 1.03 erg/cm²-sec for the corpuscular heat source.

HEAT CONDUCTION EQUATION FOR A GAS IN EQUILIBRIUM WITH A GRAVITATIONAL FIELD

The temperature distribution of the upper atmosphere is governed mainly by thermal conduction and absorption of solar energy (see Spitzer, Reference 28, and Nicolet, Reference 29). As the temperature undergoes a diurnal variation, the upper atmosphere expands and contracts. This expansion and contraction produces a transfer of heat by mass flow. In the motion of the thermosphere energy is expended or gained as a result of the work done by or against gravity. In this section we shall give a heuristic derivation of the appropriate equation, which will contain an expansion-contraction term allowing for the heat transfer due to the diurnal "breathing" of the thermosphere and the work done by or against gravity.

We shall use Eckart's Equation 9-6 (Reference 30) for the temperature dependence of a gas undergoing a flow in an external gravity field. By simplifying this equation to one dimension and expressing it in different notation, we have

$$\frac{\partial T_1}{\partial t} + \frac{\partial T_0}{\partial z} w + \frac{\gamma - 1}{a_0} \frac{\partial w}{\partial z} = \frac{q}{C_v} . \qquad (1)$$

This is one of the linearized equations of hydrodynamics in which:

 T_1 = the perturbed temperature,

w = the vertical velocity of the gas,

 T_0 = the initial temperature distribution at any initial time,

C = the specific heat at constant volume,

 γ = the ratio of the specific heats,

 a_0 = the coefficient of thermal expansion, which is $1/T_0$ for an ideal gas, and

q = the net gain of heat (in erg/gm-sec) due to heat sources and conduction (will be given in detail subsequently).

The derivation will be given for a gas with a single constituent, but we shall generalize later to include a multiconstituent thermosphere.

The vertical velocity of a gas w will be obtained in a form based upon the considerations used by ionospheric physicists in studying the drift motions of the $F2_{max}$ level of the ionosphere (see Ratcliffe and Weeks, Reference 31). As the atmosphere expands and contracts, we shall assume that a cell of gas reaches an altitude $z + w\Delta t$, at a time $t + \Delta t$,

where the pressure is the same as at the altitude z at the previous time t, i.e., $p(z + w\Delta t, t + \Delta t) = p(z, t)$. Since this motion is very slow (on the order of 10 km/h at 500 km) we shall also assume that the pressure, to the first order, follows the barometric law. Thus

$$p_0 \exp \left[-\int_0^{z+w\Delta t} \frac{gM}{RT(t+\Delta t)} dz' \right] = p_0 \exp \left[-\int_0^z \frac{gM}{RT(t)} dz' \right],$$

where g is the acceleration due to gravity, R the universal gas constant, and p_0 is the pressure at the earth's surface which for our purposes is constant. We expand the above in powers of Δt according to

$$\frac{1}{T(t + \Delta t)} = \frac{1}{T(t)} \left(1 - \frac{1}{T(t)} \frac{\partial T}{\partial t} \Delta t \right)$$

and obtain

$$w = T \int_0^z \frac{1}{T^2} \frac{\partial T}{\partial t} dz'$$
 (2)

or, in the spirit of the linearized Equation 1

$$w = T_0 \int_0^z \frac{1}{T_0^2} \frac{\partial T}{\partial t} dz'.$$

By differentiating the latter with respect to z, we have

$$\frac{\partial w}{\partial z} = \frac{\partial T_0}{\partial z} \int_0^z \frac{1}{T_0^2} \frac{\partial T}{\partial t} dz' - \frac{1}{T_0} \frac{\partial T}{\partial t} ,$$

which we substitute into Equation 1:

$$\frac{\partial T_1}{\partial t} + \gamma \frac{\partial T_0}{\partial t} T_0 \int_0^z \frac{1}{T_0^2} \frac{\partial T_1}{\partial t} dz' + (\gamma - 1) \frac{\partial T_1}{\partial t} = \frac{q}{C_v}$$

or

$$\frac{\partial T_1}{\partial t} + \frac{\partial T_0}{\partial z} T_0 \int_0^z \frac{1}{T_0^2} \frac{\partial T_1}{\partial t} dz' = \frac{q}{C_p} , \qquad (3)$$

where $C_{\rm p}$ is the specific heat at constant pressure.

Equation 3 is our basic equation; we shall integrate it numerically, taking for T_0 , $\partial T_0/\partial z$, and the non-linear terms in q, their values at $t-\Delta t$, where Δt is our integration interval. In this fashion new initial solutions are determined which will be used as the unperturbed functions T_0 in each step of the integration process. Thus the numerically determined perturbed solutions will not differ greatly from the unperturbed solutions at any time. With this understanding for the treatment of the non-linear terms, we drop the subscripts 1 and 0.

The second term on the left side of Equation 3, being proportional to the gradient of the temperature, represents a mode of "convective" transport of heat owing to the diurnal expansion and contraction — a free expansion of a non-isothermal gas in a gravitational field. In its present form this term also partially includes the effects of gravity. The main effect of gravity in the heat balance is contained in the right side of Equation 3 where C_n appears instead of C_v .

It remains to be shown that the assumptions leading to the expression for w are consistent with Eckart's Equation 9-5 for the variation of the perturbed pressure, which in the present one-dimensional notation is

$$\frac{\partial \mathbf{p_1}}{\partial t} + \frac{\partial \mathbf{p_0}}{\partial z} \mathbf{w} + \rho_0 \gamma \frac{\mathbf{RT_0}}{\mathbf{M}} \frac{\partial \mathbf{w}}{\partial z} = (\gamma - 1) \rho_0 \mathbf{q}, \qquad (4)$$

 $\mathbf{p_0}$ being the unperturbed pressure and $\boldsymbol{\rho_0}$ the unperturbed density.

From hydrostatic equilibrium, we have $dp_0/dz = -\rho_0 g$ and substituting in Equation 4 the expression for w we obtain

$$\frac{\partial p_1}{\partial t} = \rho_0 gT \int_0^x \frac{1}{T_0^2} \frac{\partial T}{\partial t} dz';$$

or from the perfect gas law $p = \rho RT/M$,

$$\frac{\partial \rho_1}{\partial t} = -\frac{\rho_0}{T} \frac{\partial T_1}{\partial t} + \frac{g\rho_0 M}{R} \int_0^z \frac{1}{T^2} \frac{\partial T}{\partial t} dz'. \qquad (5)$$

From the conservation of mass,

$$\frac{\partial}{\partial t} \int_0^\infty \rho \, dz = \int_0^\infty \frac{\partial \rho}{\partial t} \, dz = 0 . \qquad (6a)$$

Thus by integrating Equation 5 over z, we obtain

$$\int_{0}^{\infty} \frac{\rho_{0}}{T} \frac{\partial T}{\partial t} dz = \int_{0}^{\infty} dz \frac{g \rho_{0} M}{R} \int_{0}^{z} dz' \frac{1}{T^{2}(z')} \frac{\partial T(z')}{\partial t} . \tag{6b}$$

The double integral on the right side of this equation can be transformed in the following manner: it is an integral over an area in the (z, z') plane bounded by the z-axis and the z = z' line; and the order of the integration can be changed by first integrating with respect to z from z = z' to $z = \infty$, and then over z' from 0 to $z' = \infty$. Thus Equation 6b becomes

$$\int_0^{\infty} \frac{\rho_0}{T} \frac{\partial T_1}{\partial t} dz = \int_0^{\infty} \frac{1}{T_0^2(z')} \frac{\partial T(z')}{\partial t} \left[\int_{z'}^{\infty} \frac{gM}{R} \rho_0(z) dz dz' \right] dz'$$

If the foregoing is to be true for all possible variations of $\partial T/\partial t$, we must have

$$\rho_0 = \frac{1}{T_0} \int_z^{\infty} \frac{gM}{R} \rho_0(z') dz'$$

which is another form of the barometric law for the case of a non-isothermal atmosphere. By differentiating the above with respect to z to obtain

$$\frac{\partial \rho_0}{\partial z} = -\frac{1}{T} \frac{gM}{R} \rho_0 - \frac{1}{T_0^2} \frac{\partial T_0}{\partial z} \int_z^{\infty} \frac{gM}{R} \rho(z') dz'$$

and by using Equation 6a, we have

$$\frac{\partial \rho_0}{\partial z} = -\frac{1}{T_0} \frac{gM}{R} \rho_0 - \frac{\rho_0}{T_0} \frac{\partial T_0}{\partial z} .$$

Integrating, we have

$$\frac{\rho_0}{\rho_{00}} = \frac{T_{00}}{T_0} \exp \left[- \int_0^x \frac{gM}{RT_0} dz' \right] , \qquad (7)$$

where ρ_{00} , T_{00} are the values of ρ_{0} and T_{0} , respectively, at z = 0.

Thus, we see that the assumption of hydrostatic equilibrium (in the approximation of the linearized equations) for deriving w is consistent with the equation for the variation of

pressure with time. We can integrate the time-dependent equation (Equation 3), assuming that Equation 7 holds at any instant of time.

In order to generalize the above expression for a multi-constituent thermosphere, we shall now give the expression for q:

$$q\rho = Q_{cond} + Q_{euv} + Q_{ox} + Q'$$
.

The term

$$Q_{cond} = \frac{\partial}{\partial z} \left(K(T) \frac{\partial T}{\partial z} \right) \tag{8}$$

is the net gain of heat by conduction, where

$$K(T) = \frac{\sum_{i} A_{i} n_{i}(z)}{\sum_{i} n_{i}(z)} T^{1/2}(z)$$
 (9)

is the coefficient of heat conduction, A_i is a constant depending upon the constituent i, and n_i is the number density of atoms or molecules of the ith constituent. From Chapman and Cowling (Reference 32) (1960) (see also Nicolet, (Reference 29)) we have the following values (in erg/cm-sec- ${}^{\circ}K^{3/2}$):

$$A(H) = 2.1 \times 10^{3};$$

 $A(He) = 9.0 \times 10^{2};$
 $A(0) = 3.6 \times 10^{2};$
 $A(0_{2}, N_{2}) = 1.8 \times 10^{2}.$

The heat source due to the absorption of the solar EUV-radiation is given by

$$Q_{euv} = \sum_{i} \epsilon_{i} n_{i}(z) \int_{0}^{\infty} d\lambda F_{\lambda} \sigma_{i}(\lambda) e^{-\tau_{i}(\lambda,z,t)} , \qquad (10)$$

where

$$\tau_{i}(\lambda, z, t) = \int_{z}^{\infty} \sigma_{i}(\lambda) \frac{n_{i}(z)}{\cos \theta} dz$$
;

 $\sigma_i(\lambda)$ is the cross-section for absorption by the i^{th} constituent of radiation of wavelength λ in the region $d\lambda$; F_{λ} is the incident flux of wavelength λ in the region $d\lambda$ at the top of the

atmosphere; and θ is the zenith angle of the sun, ϵ_i is an efficiency factor for the conversion to thermospheric heat of energy in the extreme ultraviolet absorbed by the i^{th} constituent.

The heat loss due to the cooling by atomic oxygen radiating in the infrared is given by (Reference 33)

$$Q_{nx} = -n_0 f(T) ,$$

where

$$f(T) = E_1 A_{12} \left(\frac{W_1 \exp\left(-\frac{E_1}{kT}\right)}{W_2 + W_1 \exp\left(-\frac{E_1}{kT}\right) + W_0 \exp\left(-\frac{E_0}{kT}\right)} \right);$$

 n_0 is the number density of atomic oxygen; E_1 the energy difference between the $3P_1$ and $3P_2$ levels of atomic oxygen; E_0 the energy difference between the $3P_0$ and $3P_2$ levels of atomic oxygen; W_0 , W_1 , W_2 the statistical weights of the various levels; and A_{12} the Einstein coefficient for the transition $3P_1$ - $3P_2$.

The observations of the geomagnetic activity effect and of the semiannual effect strongly indicate the existence of another heat source, the energy of which is very likely provided ultimately by the solar corpuscular radiation and/or its "steady" component, the solar wind, for which we reserve a quantity Q' in our basic formula. Detailed considerations about this source are given later.

We need the expression for the total heat capacity at constant pressure, which we take as

$$\rho C_{p} = \sum_{i} n_{i}(z)kB_{i},$$

where k is the Boltzmann constant and B_i is a constant depending upon the constituent:

$$B_{i} \begin{cases} = & 3.5 \text{ for diatomic molecules;} \\ = & 2.5 \text{ for monatomic molecules.} \end{cases}$$

Equation 3 may be rewritten as

$$\frac{\partial}{\partial z} \left(K(T) \frac{\partial T}{\partial z} \right) - \rho C_{p} \frac{\partial T}{\partial z} T \int_{z_{0}}^{z} \frac{1}{T^{2}} \frac{\partial T}{\partial z} dz' + Q_{euv} + Q_{ox} + Q' = \rho C_{p} \frac{\partial T}{\partial t}$$
(11)

which we shall integrate numerically. This equation is linearized by evaluating the non-linear factors from the temperature and density values at the previous time step in the integration procedure. All quantities in Equation 11 depend on altitude z and time t. After the temperature profile is determined, the number densities n_i are calculated by means of the barometric relation

$$n_{i}(z,t) = n_{i}(z_{0}) \frac{T(z_{0})}{T(z,t)} \exp \left[- \int_{z_{0}}^{z} \frac{m_{i}g(z')}{kT(z',t)} dz' \right]$$
 (12)

The numerical procedure used to integrate Equation 11 was the implicit method (see Diaz et al., Reference 34) for solving parabolic equations. This method avoids the problem of instability which can arise from application of the explicit method (see Lowan, Reference 35). The boundary conditions are a given initial temperature distribution, the temperature and densities of the constituents at the lower boundary held constant in time, and a zero gradient of the temperature at the upper boundary. The numerical integration was performed on an IBM 7090 computer.

Various integration intervals in time and space were tested, $\Delta t = 0.25$ hours and $\Delta z = 1$ km were found to be satisfactory. The temperature gradient was zero at the upper boundary, which was taken to be 1000 km. An upper boundary at this altitude assures that the gradient in the temperature goes smoothly to zero. Several initial temperature profiles were used to discover how rapidly the results converge to a final steady temperature profile of diurnal variation. This procedure necessitated integrating over a period of four or five days in real time to achieve convergence, regardless of the initial temperature profile used.

A small quantity equal to 10^{-3} added to $\cos \theta$ to avoid the divergence when $\cos \theta$ goes to zero corresponds to an error of 2/3 minute in time.

During the computations it was found that the "convective" term corresponding to heat transport caused by the diurnal variation of the temperature is small. It decreases the mean diurnal temperature of the exosphere by less than 5 percent.

The total pressure was computed by summing up the partial pressures due to each constituent, which were calculated from the perfect gas law

$$p_i(z,t) = n_i(z,t) kT(z,t)$$
 (13)

The total density was calculated by means of

$$\rho(z,t) = \sum_{i} n_{i}(z,t) m_{i}, \qquad (14)$$

where m_i is the mass in grams of the i^{th} type of molecule. Then the mean molecular weight was calculated from

$$M(z,t) = \frac{\sum_{i} n_{i}(z,t)M_{i}}{\sum_{i} n_{i}(z,t)}$$
 (15)

Finally, the scale height was computed by using

$$H(z,t) = \frac{RT(z,t)}{M(z,t)g(z)}$$
 (16)

The densities at heights greater than 1,000 km were computed by the following method. In the isothermal region

$$n_{i}(z,t) = n_{i}(z_{m},t) \exp \left[-\frac{m_{i}}{kT_{m}(t)} \int_{z_{m}}^{z} g(z') dz'\right],$$
 (17)

where T_m is the temperature in the isothermal region which begins at the altitude z_m , which was taken equal to the upper boundary of the integration (1,000 km). By integrating Equation 17 we have for the number densities at heights above z_m ,

$$n_{i}(z,t) = n_{i}(z_{m},t) \exp \left[-\frac{m_{i}g_{m}R_{m}}{kT_{m}(t)} \frac{z-z_{m}}{R_{m}-z_{m}+z} \right]$$
 (18)

where the acceleration of gravity is

$$g(z) = g_m \left(\frac{R_m}{R_m - z_m + z}\right)^2 , \qquad (19)$$

 \mathbf{g}_{m} being the acceleration of gravity at the distance \mathbf{R}_{m} from the center of the earth, at height \mathbf{z}_{m} .

INTERPRETATION OF RESULTS

In the attempts to obtain a theoretical time-dependent model of the upper atmosphere by solving the heat conduction equation for the atmosphere in quasi hydrostatic equilibrium (Equations 11 through 16) — a model which should represent the observed densities satisfactorily, the absorption of solar EUV radiation combined with the heat loss Q_{ox} due to

infrared reradiation by oxygen atoms was the only heat source used at first. The loss due to reradiation has only a small influence on the temperature distribution, as has been previously noted by Hunt and Van Zandt (Reference 36). (The source Q' in Equation 11 was taken as zero in these first attempts.) The calculations yield a diurnal maximum temperature and density at 17^h local time, not at 14^h as observed from satellite drag data. The losses due to conduction and Q_{ox} are not sufficient to balance the heat input due to Q_{euv} and thereby yield a maximum temperature at 14^h . Furthermore, the ratio of daytime maximum temperature or density to nighttime minimum temperature or density respectively is much larger than the observed ratio: the calculations employing the EUV absorption as the only heat source yield a temperature ratio of 2.6, while the observed value is about 1.5.

These results are qualitatively independent of boundary conditions. For testing, two different sets of number densities were used which differed considerably in the important ratio ${\rm O/O_2}$ at the lower boundary. Diffusive equilibrium was assumed to hold for all altitudes above 120 km. The numerical values for the boundary conditions at 120 km are given in Table 1. A temperature of 355°K was chosen in both cases; no attempt was made to ac-

Table 1
Boundary Values at 120 km Altitude $(T = 355^{\circ}K)$

Constituent		r Density les/cm³)
	Set 1*	Set 2**
N ₂	5.80 × 10 ¹¹	5.95×10^{11}
O ₂	1.20×10^{11}	3.13×10^{10}
0	7.60×10^{10}	2.57×10^{11}
He	2.50×10^7	2.50×10^{7} *
H	$4.36 \times 10^{4} **$	4.36×10^4

^{*}Values are from Nicolet (Reference 37)

count for a diurnal variation of this temperature, since no considerable variation was expected at this altitude. However, further investigation is desirable.

Mean values for the photoionization cross sections were used: 15, 15, and 12×10^{-18} cm² for N₂, O₂, and O respectively. These averages are valid for the wavelength range from about 60 to 900 A.

The incident flux was chosen to yield a model which is in agreement with the average observed densities and temperatures, specifically around 600 km. As an illustration, consider the maximum and minimum values of temperature and density at 600 km calculated for two different fluxes of the EUV radiation: In the first example the flux was 1.8 erg/cm²-sec

and the first set of boundary values (Table 1) was used. A maximum temperature of $1959^{\circ} K$ was obtained at 17^{h} local time, and a minimum of $849^{\circ} K$ at 6^{h} . The corresponding densities are 1.59×10^{-15} and $3.44\times10^{-17}~{\rm gm/cm^{3}}$. In the second example the flux was $2.2~{\rm erg/cm^{2}}$ -sec and the second set of boundary values was used. The maximum and minimum temperatures and densities obtained at $600~{\rm km}$ are $2026^{\circ} K$ at 17^{h} local time, $910^{\circ} K$ at 6^{h} , and $3.81\times10^{-15}~{\rm and}~1.47\times10^{-16}~{\rm gm/cm^{3}}$ respectively.

^{**}Values are from Jastrow and Kyle (Reference 38)

The peak fluxes are generally considerably higher than the flux of 1.1 erg/cm²-sec required by D. C. Hunt and T. E. van Zandt (1961), who compared the observed data at diurnal maximum with a time-independent solution. This discrepancy occurs because the time-independent solution can be applied only to define diurnal average values if the time-independent flux is considered as a diurnal average. A comparison with the observed diurnal maximum values therefore yields unacceptable conclusions.

The diurnal variation of the temperature calculated with only the EUV heat source is given in Figure 1 for an altitude of 600 km (dashed line), along with the temperature distribution (solid line) which well represents the observed data.

It is concluded that no agreement can be obtained between the observations and a theory based on a EUV heat source alone. Furthermore, an extremely high efficiency (70 to 90 percent) would be required for the conversion of the EUV flux into thermospheric heat if this theory is to compare with Hinteregger's rocket measurements — a total flux of 2.5 erg/cm^2 -sec in the range from 44 to 1,000 A (Reference 12).

Therefore the existence of a second heat source with the following properties is strongly suggested: a maximum in the mid-morning and a minimum in the early or mid-afternoon, a small amount of heating during the night, and an average magnitude comparable to the heat provided by the EUV flux.

A heat source with these properties is required to represent the density observed at those times when a large diurnal bulge is found. For the comparison the Bonn Observatory model of 1961 (Reference 39) was used; it is in very good agreement with the density data obtained by other groups. This model is reduced to years of high solar activity, represented by a 10.7 cm solar radiation flux of $S = 200 \times 10^{-22}$ w/m²-cps or by the corresponding flux $S = 170 \times 10^{-22}$ w/m²-cps of the 20 cm solar radiation.

The time variation of this new heat source which we have called the "corpuscular" heat source, might be correlated with some other geomagnetic phenomena which would serve as indicators of corpuscular activity. The intensities of the micropulsations observed by




Figure 1—Diurnal variation of the exospheric temperature calculated with an EUV heat source alone ($Q_{\rm euv}$) and combined with the additional "corpuscular" heat source ($Q_{\rm euv}$ + Q').




Figure 2—Diurnal variation of the fluxes of the EUV heat source (Q_{euv}) and of the "corpuscular" heat source (Q')

Campbell (Reference 40) in California show the main maximum at about 9^h local time, and thereby have the principal property required. A physical connection of these pulsations with the second heat source proposed here is plausible, but direct observations of micropulsations in the ionospheric F-layer would be desirable. The geomagnetic field strength at the equator also has approximately the time-varying properties required.

The chosen diurnal variation of the flux of the corpuscular heat source which is given in Figure 2, together with the fraction of the solar EUV flux converted into heat in the thermosphere (having a peak value of 0.93 erg/cm²-sec). This implies an efficiency factor of 37 per-

cent. The peak value of the flux of the corpuscular heat source that yields a good agreement with the observed densities is $1.03~\rm erg/cm^2$ -sec. This value is in good agreement with the estimates obtained from the semiannual variation (see the Introduction). It also agrees with the magnitude of the heat source proposed by Dessler (Reference 41) — a source which is due to the dissipation of hydromagnetic waves generated by the solar corpuscular radiation. The energy dissipation takes place in the F region of the ionosphere. For the altitude dependence of our corpuscular head source Q' an analytic approximation to the dissipation curve given by Dessler is used. This altitude dependence is also similar in shape to the heat input due to absorption of solar EUV radiation.

The expression used for Q'is

$$Q' = \frac{F}{S_1 - S_2} \left[\exp \left(-\frac{z - z_0}{S_1} \right) - \exp \left(-\frac{z - z_0}{S_2} \right) \right] f(t) ,$$

where

$$F = \int_{z_0}^{\infty} Q'(z, t_{max}) dz$$

is the flux of this heat source at the time of its peak value. The values chosen for s_1 , s_2 , and z_0 are 60, 40, and 120 km respectively which yield a maximum for Q' at 170 km. The diurnal variation f(t) is normalized to a peak value equal to unity and is represented by the following Fourier coefficients:

$$a_0 = +0.427,$$
 $a_1 = -0.263,$ $a_2 = +0.063,$ $a_3 = -0.015,$ $a_4 = +0.024,$ $a_5 = -0.006,$ $a_6 = -0.004,$ $a_1 = +0.369,$ $a_2 = -0.156,$ $a_3 = +0.010,$ $a_4 = +0.208,$ $a_5 = -0.007.$

By using this corpuscular source in addition to the EUV heat source good agreement is obtained between observed and calculated densities. The better general agreement is obtained with the first set of boundary conditions in Table 1. The solid line in Figure 1 shows the calculated diurnal variation of the exospheric temperature. In Figures 3 and 4 the calculated diurnal variations of densities are compared with the densities of the Bonn Observatory model (Reference 39). In the altitude range from 400 to 700 km, where the Bonn model is based on the most reliable density determinations, we have an almost perfect agreement. For altitudes below 400 km the agreement is also satisfactory. In the range above an altitude of 1,000 km the Bonn Observatory model is based on densities derived from the satellite Echo I by Römer (References 6 and 7) using a method which




Figure 3—Diurnal variation of density for selected altitudes from 160 to 600 km. The solid curves give the values calculated with Table 1. The circles are densities taken from the Bonn University Observatory observational model of 1961.




Figure 4—Diurnal variation of density for selected altitudes from 700 to 2,000 km. The solid curves give the values calculated with Table 1. The circles are densities taken from the Bonn University Observatory observational model of 1961.

takes into account the diurnal bulge by considering how the orbit traverses the bulge. An auxiliary model was needed for his calculations. The one he used early in 1961 was based on an extrapolation of the altitude variation of the diurnal amplitude; this variation increased systematically with height. In an atmosphere containing a helium layer (where the mean molecular weight decreases with altitude and time) the amplitude of the diurnal density variations begins to decrease again above 1,000 km (Figure 4). Therefore, the maximum densities in the Bonn model are too great for altitudes above 1,000 km by an estimated amount indicated by the arrows in Figure 4. Those reduced densities are then in better agreement with our calculated densities. The densities calculated by Bryant (Reference 9) using a general density scale height of 260 km are all placed well between our maximum and minimum density curves in the altitude range from 1075 to 1450 km.

The temperature, scale height and mean molecular weight are given as functions of altitude for four selected local times of the day in Figures 5, 6 and 7 respectively. It may be noticed that the 10^h and the 22^h temperature curves in Figure 5 cross at about 170 km. This is related to the fact that the daytime densities in the altitude range from 130 to 190 km are lower than the nighttime densities, in agreement with the observational model by Martin et al. (Reference 39). The mass difference between the nighttime and daytime densities below 190 km is sufficient to provide the mass for the diurnal bulge above that height, since our model conserves the total mass (see Equation 6).

In Figure 8 the densities of the observational model at an altitude of 600 km are compared with the densities calculated for both sets of boundary conditions which differ considerably in the ratio $\rm O/O_2$ at the lower boundary (120 km). In general, both sets




Figure 5—Temperature as a function of altitude from 120 km to 600 km for four selected local times.

afford a satisfactory agreement in the range from 200 to 600 km; the first set yields a better fit with the observed data at 600 km (Figure 8), but the discrepancy is not large enough to eliminate the second set. The observed densities may need some systematic corrections, since the atmospheric bulge was only approximately considered in the reduction of the observational data (Reference 39).

It is interesting to compare the exospheric maximum and minimum temperatures for these two sets of calculations. From the first set of boundary conditions the results are 1770° K for the diurnal maximum and 1160° K for the diurnal minimum. The corresponding temperatures for the second set are 1515° and 975° K respectively. These values demonstrate the sensitivity of the exospheric temperature to the boundary conditions and, especially, to the ratio $0/0_2$. In the first set this ratio is 0.63; in the second set, 8.2.




Figure 6—Pressure scale heights as a function of altitude from 120 km to 1,300 km for four selected local times.




Figure 7—The mean molecular weight as a function of altitude from 120 km to 1,300 km for four selected local times.




Figure 8—Comparison of the calculated densities using the two sets of boundary conditions given in Table 1 with the observed data of the Bonn 1961 Model at an altitude of 600 km.

The physical properties of the upper atmosphere based on the first set of boundary conditions (Table 1) are presented in Appendix A as functions of altitude from 120 to 2,050 km for selected hours in local time. This model applies to the equatorial and temperate zones of the earth and is valid for those years when the solar activity can be represented by an average flux of 200×10^{-22} w/m²-cps for the 10.7 cm radiation (or a flux of 170×10^{-22} w/m²-cps for the 20 cm radiation).

It should be emphasized again that to obtain good agreement with the observational model a heat source in addition to the solar EUV flux is required. It is probable that this heat source derives its energy ultimately from the solar corpuscular radiation.

In the present calculations good agreement was obtained with the observational models with a diurnal average flux of 0.44 erg/cm²-sec and a peak value of 1.03 erg/cm²-sec at 9^h local time, combined with an EUV heat source having an average flux of 0.30 erg/cm²-sec and a peak value of 0.93 at 12^h local time.

Of the four effects mentioned in the introduction, this calculated model is for the diurnal variation alone. The three other effects could be represented by changes in the total fluxes of the two heat sources, both of which are expected to vary considerably during the 11-year solar cycle. The analysis of the density determinations from satellite drag measurements during an entire solar cycle could reveal the necessary information about the flux variations of the two heat sources. But we should also be prepared for the possibility that the diurnal variation of the corpuscular heat source may change in shape and in position of the maximum during the colar cycle. Therefore, direct measurements of the solar EUV radiation and of the solar wind intensity outside the magnetosphere are urgently desired for at least one solar cycle.

ACKNOWLEDGMENTS

The authors are very much obliged to Dr. R. Jastrow for his stimulation and permanent interest and would like to acknowledge their indebtedness to Mr. Lee Kyle and Dr. R. Jastrow for the development of the earlier phase of the program from which this procedure was derived. Further, they wish to express their appreciation to Mr. E. Monasterski for preparing the extensive machine program and constructing the procedure for numerical integration of the conduction equations.

REFERENCES

- 1. Priester, W., "Sonnenaktivität und Abbremsung der Erdsatelliten," Mitteilung der Universitäts-Sternwarte Bonn No. 24, 1959; Also Naturwissenschaften 46(6):197-198, March 1959.
- 2. Jacchia, L. G., "Atmospheric Fluctuations of Solar Orgin Revealed by Satellites," Harvard College Observ. Announcement Card No. 1423, January 16, 1959.
- 3. Jacchia, L. G., "Solar Effects on the Acceleration of Artificial Satellites," Smithsonian Inst. Astrophys. Observ., Res. Space Sci. Spec. Rept. No. 29, September 1959.
- 4. Dessler, A. J., "Ionospheric Heating by Hydromagnetic Waves," J. Geophys. Res. 64(4):397-401, April 1959.
- 5. Priester, W. and Martin, H. A., "Solare und Tageszeitliche Effekte in der Hochatmosphäre aus Beobachtungen Künstlicher Erdsatelliten," Forschungsberichte des Landes Nordrhein-Westfalen No. 547, 1960 (Mitteilung der Universitäts-Sternwarte Bonn No. 29, 1960); Translation: "Solar and Diurnal Effects in the Upper Atmosphere from Observations of Artificial Earth Satellites," Great Britain, Royal Aircraft Establishment Library Translation No. 901, May 1960.
- 6. Römer, M., "Modell der Exosphäre im Höhenbereich 1000-1700 Km Berechnet aus den Bahnänderungen des Satelliten Echo I," Forschungsberichte des Landes Nordrhein-Westfalen No. 997, 1961 (Mitteilung der Universitats-Sternwarte Bonn No. 37, 1961); Translation: "Model of the Exosphere at Heights Between 1000-1700 Km Calculated from the Orbital Perturbations of the Satellite Echo I," Great Britain, Royal Aircraft Establishment Library Translation No. 954, July 1961.
- 7. Römer, M., "Terrestrial Exosphere at Heights of 1000-1700 km," *Nature*, 191(4785): 238-240, July 15, 1961.

- 8. Zadunaisky, P. E., Shapiro, I. I., and Jones, H. M., "Experimental and Theoretical Results on the Orbit of Echo 1," Smithsonian Inst. Astrophys. Observ., Res. in Space Sci. Spec. Rept. No. 61, March 20, 1961.
- 9. Bryant, R., "A Comparison of Theory and Observation of the Echo I Satellite," J. Geo-phys. Res. 64(69):3066-3069, September 1961.
- 10. Jacchia, L. G. and Slowey, J., "Preliminary Analysis of the Atmospheric Drag of the Twelve-Foot Balloon Satellite (1961 8 1)," Smithsonian Inst. Astrophys. Observ., Res. in Space Sci. Spec. Rept. No. 84, February 9, 1962.
- 11. Waldmeier, M., and Müller, H., "Die Sonnenstrahlung im Gebiet von $\lambda = 10$ cm," Zeitschrift für Astrophysik 27(1):58-72, April 5, 1950.
- 12. Hinteregger, H. E., "Preliminary Data on Solar Extreme Ultraviolet Radiation in the Upper Atmosphere," J. Geophys. Res. 66(8): 2367-2380, August 1961.
- 13. Priester, W., "Solar Activity Effect and Diurnal Variation in the Upper Atmosphere," J. Geophys. Res. 66(12):4143-4148, December 1961.
- 14. Jacchia, L. G., "A Working Model for the Upper Atmosphere," Nature, 192(4808):1147-1148, December 23, 1961.
- 15. Priester, W., Martin, H. A., and Kramp, K., "Diurnal and Seasonal Density Variations in the Upper Atmosphere," *Nature* 188(4746)202-204, October 15, 1960.
- 16. Jacchia, L. G., "A Variable Atmospheric-Density Model from Satellite Accelerations," Smithsonian Inst., Astrophys. Observ., Res. in Space Sci. Spec. Rept. No. 39, March 30, 1960.
- 17. Paetzold, H. K. and Zschörner, H., "The Structure of the Upper Atmosphere and its Variations after Satellite Observations," Space Research II: Proc. 2nd Internat. Space Sci. Sympos., Florence, April 1961, ed. by H. C. van de Hulst, C. de Jager, and A. F. Moore, Amsterdam: North-Holland Pub. Co., 1961, pp. 958-973.
- 18. King-Hele, D. G., and Walker, D. M. C., "Upper-Atmosphere Density During the Years 1957 to 1961, Determined from Satellite Orbits," Space Research II: Proc. 2nd Internat. Space Sci. Sympos., Florence, April 1961, ed. by H. C. van de Hulst, C. de Jager, and A. F. Moore, Amsterdam: North-Holland Pub. Co., 1961, pp. 918-957.
- 19. Jacchia, L. G., "Corpuscular Radiation and the Acceleration of Artificial Satellites," Nature, 183(4676):1662-1663, June 13, 1959.

- Jacchia, L. G., "Satellite Drag During the Events of November 1960," Space Research II: Proc. 2nd Internat. Space Sci. Sympos., Florence, April 1961, ed. by
 H. C. van de Hulst, C. de Jager, and A. F. Moore, Amsterdam: North-Holland Pub. Co., 1961, pp. 747-750.
- 21. Groves, G. V., "Correlation of Upper Atmosphere Air Density with Geomagnetic Activity, November 1960," Space Research II: Proc. 2nd Internat. Space Sci. Sympos., Florence, April 1961, ed. by H. C. van de Hulst, C. de Jager, and A. F. Moore, Amsterdam: North-Holland Pub. Co., 1961, pp. 751-753.
- 22. Paetzold, H. K., and Zschörner, H., "An Annual and a Semiannual Variation of the Upper Air Density," *Geofisica Pura e Applicata* 48:85-92, 1961.
- 23. Cortie, A. L., "Sun-spots and Terrestrial Magnetic Phenomena, 1898-1911: The Cause of the Annual Variation in Magnetic Disturbances," *Monthly Not. Roy. Astronom. Soc.* 73(1):52-60, November 8, 1912.
- 24. Bartels, J., "Terrestrial-Magnetic Activity and its Relation to Solar Phenomena," Terrest. Mag. and Atmos. Elec., 37(1):1-52, March 1932.
- 25. Paetzold, H. K. and Zschörner, H., "The Structure of the Upper Atmosphere and its Variations after Satellite Observations," Space Research II: Proc. 2nd Internat. Space Sci. Sympos., Florence, April 1961, ed. by H. C. van de Hulst, C. de Jager, and A. F. Moore, Amsterdam: North-Holland Pub. Co., 1961, pp. 958-973.
- 26. Priester, W., and Cattani, D., "On the Semiannual Variation of Geomagnetic Activity and its Relation to the Solar Corpuscular Radiation," J. Atmos. Sci., 19(2):121-126, March 1962
- 27. Bridge, H. S., Dilworth, C., et al., "Direct Observations of the Interplanetary Plasma," Mass. Inst. Tech., Lab. Nuclear Sci. and Dept. Phys., Prelim. Rept. 1961; Also Proc. Internat. Conf. Cosmic Rays and the Earth Storm Kyoto, September 1961 (J. Phys. Soc. Japan 17, Suppl. A, In press).
- 28. Spitzer, L., Jr., "The Terrestrial Atmosphere Above 300 Km," in: *The Atmospheres of the Earth and Planets*, ed. by G. P. Kuiper, Rev. Ed., Chicago: University of Chicago Press, 1952, pp. 211-247.
- 29. Nicolet, M., "Structure of the Thermosphere," Planet. Space Sci., 5(1):1-32, January 1961.
- 30. Eckart, C. H., "Hydrodynamics of Oceans and Atmospheres," New York: Pergamon Press, 1960.

- 31. Ratcliffe, J. A. and Weekes, K., "The Ionosphere," in: *Physics of the Upper Atmosphere*, ed. by J. A. Ratcliffe, New York: Academic Press, 1960, pp. 377-470.
- 32. Chapman, S. and Cowling, T. G., "The Mathematical Theory of Non-Uniform Gases," 2nd Ed., Cambridge: University Press, 1952.
- 33. Bates, D. R., "The Temperature of the Upper Atmosphere," *Proc. Phys. Soc. London*, 64B(9):805-821, September 1, 1951.
- 34. Diaz, G. B., Clippinger, R. F., et al., "Partial Differential Equations," in *Handbook of Automation, Computation, and Control*, ed. by E. M. Grabbe, S. Ramo, and D. E. Wooldridge, New York: John Wiley and Sons, 1958, Vol. 1, Chapter 14, pp. 64-90.
- 35. Lowan, A. N., "On the Cooling of the Upper Atmosphere after Sunset," J. Geophys. Res. 60(4):421-429, December 1955.
- 36. Hunt, D. C. and Van Zandt, T. E., "Photoionization Heating in the F Region of the Atmosphere," J. Geophys. Res. 66(6):1673-1682, June 1961.
- 37. Nicolet, M., "Density of the Heterosphere Related to Temperature," Smithsonian Inst., Astrophys. Observ., Res. in Space Sci., Spec. Rept. No. 75, September 19, 1961.
- 38. Jastrow, R., and Kyle, H., "The Earth Atmosphere," *Handbook of Astronautical Engineering*, ed. by H. H. Koelle, New York: McGraw-Hill, 1961, Chapter 2, pp. 2-13.
- 39. Martin, H. A., Neveling, W., et al., "Model of the Upper Atmosphere from 130 Through 1600 Km Derived from Satellite Orbits," *Mitteilung der Universitäts-Sternwarte Bonn* No. 35, 1961; Also *Space Research II: Proc. 2nd Internat. Space Sci. Sympos., Florence, April 1961*, ed. by H. C. van de Hulst, C. de Jager, and A. F. Moore, Amsterdam: North-Holland Pub. Co., 1961, pp. 902-917.
- 40. Campbell, W. H., "Studies of Magnetic Field Micropulsations with Periods of 5 to 30 Seconds," J. Geophys. Res. 64(11):1819-1826, November 1959.

Appendix A

Properties of the Upper Atmosphere as Functions of Local Time

The properties of the upper atmosphere are tabulated as a function of local time (for every hour of the day) and as a function of altitude (from 120 km to 2050 km). The quantities listed are: temperature (°K); density (gm/cm³); pressure (dynes/cm²); scale height (km); mean molecular weight, and number densities (cm⁻³) for N₂, O₂, O, He, H. At the beginning of each page the local time (in hours); the cosine of the zenith angle θ of the sun during the times of equinoxes on the equator; and the temperature gradient at 120 km in °K/km (labeled INT GRAD) are given.

The model used applies to the earth's equatorial and temperate zones when the average solar activity is represented by a solar radiation flux of 200×10^{-22} w/m²-cps at a wavelength of 10.7 cm.

	N(H) /CM3	4.356G 04 2.929E 04 2.288E 04 1.952E 04	1.562E 04 1.456E 04 1.377E 04 1.315E 04 1.227E 04	1.166E 04 1.121E 04 1.085E 04 1.055E 04	Sodod mm wam	9.114E 03 8.951E 03 8.794E 03 8.641E 03	8.348E 03 8.207E 03 8.069E 03 7.935E 03 7.805E 03	7.677E 03 7.552E 03 7.430E 03 7.511E 03 7.195E 03
;	N(HE) /CM3	2.5006 07 1.553E 07 1.143E 07 9.199E 06 7.806E 06	6.855E 06 6.162E 06 5.631E 06 5.207E 06 4.563E 06	4.084E 06 3.704E 06 3.387E 06 3.115E 06 2.876E 06	2.663E 06 2.470E 06 2.295E 06 2.135E 06 1.988E 06	1.853E 06 1.728E 06 1.613E 06 1.506E 06	1.315E 06 1.229E 06 1.150E 06 1.076E 06	9.440E 05 8.846E 05 8.292E 05 7.776E 05
	N(C) /CM3	7.600E 10 3.445E 10 2.007E 10 1.330E 10 9.527E 09	7.171E 09 5.583E 09 4.453E 09 3.614E 09 2.469E 09	1.255E 09 1.255E 09 9.160E 08 6.751E 08	3.739E 08 2.801E 08 2.106E 08 1.588E 08 1.201E 08	9.096E 07 6.906E 07 5.254E 07 4.004E 07	2.339E 07 1.792E 07 1.375E 07 1.057E 07 8.137C 06	6.274E 06 4.846E 06 3.748E 06 2.903E 06
	N(02) /CM5	1.200E 11 3.576E 10 1.526E 10 7.818E 09	2.739c 09 1.762E 09 1.172E 09 8.000c 08 3.925c 08	2.018E 08 1.070E 08 5.786E 07 3.177E 07	9.875E 06 5.568E 06 3.159E 06 1.801E 06	5.944E 05 3.427E 05 1.987E 05 1.156E 05	3.954E 04 2.324E 04 1.370E 04 8.107E 03	2.864E 05 1.710E 03 1.024E 03 6.152E 02 3.707E 02
	1.7313E 01 N(N2) /CM3	5.800E 11 1.919E 11 8.846E 10 4.833E 10 2.922E 10	1.272E 10 1.272E 10 8.852E 09 6.307E 09 3.361E 09	1.870E 09 1.069E 09 6.234E 08 3.683E 08 2.198E 08	1.322E 08 8.002E 07 4.869E 07 2.976E 07 1.827E 07	1.125E 07 6.958E 06 4.316E 06 2.686E 06 1.677E 06	1.050E 06 6.590E 05 4.150E 05 2.620E 05 1.659E 05	1.053E 05 6.706E 04 4.281E 04 2.739E 04
	INT GRAD= MEAN MOL WT	27.46 26.98 26.56 26.16 25.78	25.40 24.64 24.64 24.26 23.49	22.73 21.98 21.25 20.56 19.91	19.32 18.79 18.32 17.90	17.19 16.90 16.63 16.38	15.92 15.69 15.46 15.21	14.64 14.32 13.97 13.58
	0000E-01, SCALE HT KM	11.4 16.8 21.5 25.5 28.9	31.9 34.4 36.6 38.6 42.1	45.2 48.0 50.6 53.1	57.9 60.1 62.1 64.1	69.3 70.9 72.4 73.9	75.4 77.0 78.7 80.4 82.4	84.5 86.9 89.7 92.8
	OS(TH)= 10.0 PRESSURE CYNE/CM2	3.802E-02 1.860E-02 1.103E-02 7.209E-03 4.994E-03	3.594E-03 2.658E-03 2.006E-03 1.538E-03 9.370E-04	5.926E-04 3.858E-04 2.571E-04 1.749E-04	8.507E-05 6.060E-05 4.368E-05 3.182E-05 2.339E-05	1.734E-05 1.295E-05 9.735E-06 7.364E-06 5.602E-06	4.286E-06 3.297E-06 2.549E-06 1.983E-06	1.220E-06 9.660E-07 7.701E-07 6.184E-07 5.005E-07
	= -0. , C DENSITY GM/CM3	3.5366-11 1.1746-11 5.4576-12 3.0176-12 1.8496-12	1.213E-12 8.334E-13 5.924E-13 4.319E-13 2.428E-13	1.440E-13 8.881E-14 5.645E-14 3.679E-14 2.451E-14	1.663E-14 1.148E-14 8.050E-15 5.718E-15 4.11E-15	2.987E-15 2.190E-15 1.620E-15 1.206E-15 9.043E-16	6.818E-16 5.167E-16 3.935E-16 3.010E-16 2.312E-16	1.783E-16 1.380E-16 1.073E-16 8.374E-17 6.563E-17
	FOURS) TEMP K	355 514 646. 752 837	905 960 1003 1039	1125 1148 1164 1175	1189 1193 1195 1198	1201 1201 1202 1203 1203	1204 1204 1205 1205 1205	1205 1206 1206 1206 1206
	TIME (IN ALT KM	120 130 140 150	170 180 190 200 220	240 280 300 320	340 340 380 400 420	7500 7500 2500 2500 2500	540 580 580 600 620	640 660 680 700 720

7.081E 03 6.969E 03 6.861E 03 6.754E 03	6.548E 03 6.448E 04 6.350E 03 6.255E 03	6.069E 03 5.979E 03 5.892E 03 5.805E 03 5.597E 03	5.2116 03 5.2116 03 5.0326 03 4.861E 03	4.542E 03 4.393E 03 4.251E 03 4.116E 03	3.862E 03 3.743E 03 3.630E 03 3.521E 03	3.221E 03 3.221E 03 3.129E 03 5.040E 03 2.955E 03
6.847E 05 6.428E 05 6.037E 05 5.672E 05	5.012E 05 4.714E 05 4.436E 05 4.175E 05	3.702E 05 3.488E 05 3.287E 05 3.099E 05	2.3196 05 2.0126 05 1.7496 05 1.5236 05 1.3296 05	1.161E 05 1.016E 05 8.914E 04 7.830E 04 6.889E 04	6.071E 04 5.358E 04 4.737E 04 4.194E 04 3.718E 04	3.3026 04 2.9366 04 2.6146 04 2.3316 04 2.0826 04
1.750E 06 1.361E 06 1.061E 06 8.277E 05 6.468E 05	5.061E 05 3.965E 05 3.111E 05 2.445E 05 1.923E 05	1.515E 05 1.195E 05 9.439E 04 7.465E 04	2.353E 04 1.337E 04 7.649E 03 4.409E 03	1.497E 03 8.813E 02 5.224E 02 3.117E 02 1.872E 02	1.132E 02 6.884E 01 4.213E 01 2.594E 01	1.001E 01 6.273E 00 3.953E 00 2.505E 00 1.596E 00
2.240E 02 1.357E 02 8.248E 01 5.027E 01	1.883E 01 1.157E 01 7.130E 00 4.406E 00 2.729E 00	1.695E 00 1.056E 00 6.593E-01 4.127E-01	4.120E-02 1.332E-02 4.371E-03 1.455E-03	1.684E-04 5.849E-05 2.059E-05 7.346E-06 2.655E-06	9.720E-07 3.603E-07 1.352E-07 5.136E-08	7.676E-09 3.019E-09 1.201E-09 4.829E-10 1.963E-10
1.131E 04 7.292E 03 4.715E 03 3.056E 03	1.293E 03 8.443E 02 5.525E 02 3.624E 02 2.383E 02	1.571E 02 1.037E 02 6.868E 01 4.557E 01	6.058E 00 2.254E 00 8.493E-01 3.242E-01	4,905E-02 1,943E-02 7,788E-03 3,158E-03 1,295E-03	5.373E-04 2.253E-04 9.551E-05 4.092E-05 1.771E-05	7.745E-06 3.421E-06 1.526E-06 6.872E-07 3.124E-07
12.69 12.20 11.68 11.13	10.02 9.46 8.92 8.40 7.90	7.44 7.02 6.63 6.28 5.56	7. 00 2. 00	#.06 3.95 3.92 3.89	3.87 3.84 3.82 3.80 3.78	3.75 3.73 3.70 3.68
100.4 105.1 110.4 116.4	130.8 139.3 148.6 158.7	181.1 193.1 205.6 218.2 249.6	278.9 304.5 326.0 343.6 358.1	370.2 380.7 389.9 398.5 406.6	414.4 422.2 429.9 437.8	454.1 462.5 471.3 480.4
4.083E-07 3.360E-07 2.791E-07 2.339E-07	1.690E-07 1.458E-07 1.268E-07 1.113E-07 9.856E-08	8.793E-08 7.901E-08 7.146E-08 6.502E-08	4.345E-08 3.661E-08 3.124E-08 2.691E-08 2.334E-08	2.034E-08 1.781E-08 1.564E-08 1.378E-08	1.077E-08 9.559E-09 8.500E-09 7.575E-09 6.765E-09	6.053E-09 5.427E-09 4.876E-09 4.390E-09
5.167E-17 4.087E-17 3.249E-17 2.596E-17	1.688E-17 1.375E-17 1.128E-17 9.319E-18 7.763E-18	6.521E-18 5.524E-18 4.720E-18 4.068E-18 2.910E-18	2.185E-18 1.708E-18 1.380E-18 1.143E-18 9.634E-19	8.230E-19 7.098E-19 6.164E-19 5.382E-19 4.718E-19	4.150E-19 3.260E-19 3.236E-19 2.867E-19 2.545E-19	2.264E-19 2.017E-19 1.800E-19 1.609E-19 1.440E-19
1206 1206 1206 1206 1207	1207 1207 1207 1207 1207	1207 1207 1207 1207	1207 1207 1207 1207 1207	1207 1207 1207 1207 1207	1207 1207 1207 1207 1207	1207 1207 1207 1207
740 760 780 800 820	88 ¢ ¢ 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	940 960 980 1000 1050	1100 1150 1200 1250 1300	1350 1400 1450 1500	1600 1650 1700 1750 1800	1850 1900 1950 2000 2050

N(H) /CMS	4.356E 04 2.934E 04 2.300E 04 1.949E 04	1.583E 04 1.477E 04 1.398E 04 1.337E 04	1.186E 04 1.140E 04 1.102C 04 1.072E 04 1.045E 04	1.021E 04 9.989E 03 9.786E 03 9.594E 03 9.412E 03	9.237E 03 9.069L 03 8.906E 03 8.749E 03 8.596E 03	8.447E 03 8.302C 03 8.160E 03 8.022E 03 7.887E 03	7.756E 03 7.628E 03 7.502E 03 7.380E 03
N(HE) /CM3	2.500E 07 1.556E 07 1.149E 07 9.273E 06 7.886E 06	6.936E 06 6.24 1E 06 5.705E 06 5.276E 06 4.621E 06	4.152E 06 3.742E 06 3.417E 06 3.138E 06 2.893E 06	2.674E 06 2.478E 06 2.299E 06 2.136E 06 1.986E 06	1.849E 06 1.722E 06 1.605E 06 1.496E 06	1.303E 06 1.217E 06 1.137E 06 1.063E U6 9.940E 05	9.299E 05 8.703E 05 8.149E 05 7.643E 05
N(0) /CM3	7.600E 10 3.450E 10 2.015E 10 1.338E 10 9.586E 09	7.212E 09 5.608E 09 4.465E 09 3.616E 09 2.458E 09	1.725E 09 1.235E 09 8.964E 08 6.569E 08	3.598E 08 2.681E 08 2.005E 08 1.50%E 08	8.523E 07 6.43BE 07 4.873E 07 3.695E 07 2.807E 07	2.136E 07 1.628E 07 1.243E 07 9.511E 06 7.287E 06	5.591E 06 4.247E 06 3.308E 06 2.550E 06 1.969E 06
N(02) /CM3	1.200E 11 3.581E 10 1.530E 10 7.837E 09 4.471E 09	2.732E 09 1.750E 09 1.159E 09 7.869E 08 3.819E 08	1.941E 08 1.017E 08 5.437E 07 2.952E 07 1.621E 07	8.975E 06 5.007E 06 2.810E 06 1.585E 06 8.986E 05	5.116E 05 2.92kE 05 1.678E 05 9.66kE 04 5.585E 04	3.239E 04 1.885E 04 1.101E 04 6.446E 03	2.233E 03 1.321E 03 7.833E 02 4.660E 02 2.781E 02
1.7284E 01 N(N2) /CM3	5.800E 11 1.921E 11 8.872E 10 4.849E 10 2.928E 10	1.884E 10 1.267E 10 8.784E 09 6.231E 09	1.811E 09 1.025E 09 5.918E 08 3.462E 08 2.046E 08	1.219E 08 7.307E 07 4.405E 07 2.668E 07 1.623E 07	9.906E 06 6.069E 06 3.731E 06 2.301E 06 1.424E 06	8.835E 05 5.499E 05 3.433E 05 2.149E 05	8.4926 04 5.3606 04 3.3936 04 2.1536 04 1.3706 04
INT GRAD= MEAN MOL WT	27.46 26.98 26.56 26.16 25.17	25.38 25.00 24.61 24.22 23.44	22.66 21.89 21.15 20.45 19.80	19.21 18.68 18.21 17.79	17.10 16.81 16.54 16.30	15.83 15.59 15.35 15.08 14.80	14.48 14.13 13.75 13.33
93E-01, SCALE HT KM	11.4 16.8 21.4 25.3 28.6	31.4 33.9 36.1 38.0 41.4	44.7.3 47.3 52.4 52.8	57.1 59.3 61.3 63.3	66.8 68.4 69.9 71.4 72.9	74.5 76.1 77.8 79.6 81.6	83.9 86.4 89.4 92.7 96.6
OS(TH)= 9.65 PRESSURE CYNE/CM2	3.8026-02 1.8596-02 1.1006-02 7.1716-03 4.9506-03	3.548E-03 2.613E-03 1.963E-03 1.499E-03 9.060E-04	5.688E-04 3.678E-04 2.437E-04 1.648E-04	7.941E-05 5.632E-05 4.043E-05 2.933E-05 2.147E-05	1.586E-05 1.179E-05 8.833E-06 6.656E-06 5.045E-06	3.846E-06 2.949E-06 2.274E-06 1.763E-06 1.376E-06	1.0806-06 8.5406-07 6.8026-07 5.4606-07
= 1.000, C DENSITY GM/CM3	3.536E-11 1.175E-11 5.474E-12 3.027E-12 1.854E-12	1.213E-12 8.312E-13 5.888E-13 4.277E-13	1.4046-13 8.5966-14 5.4276-14 3.5166-14 2.3296-14	1.573E-14 1.081E-14 7.546E-15 5.339E-15 3.823E-15	2.767E-15 2.022E-15 1.489E-15 1.105E-15 8.252E-16	6.197E-16 4.679E-16 3.549E-16 2.704E-16 2.069E-16	1.590E-16 1.227E-16 9.506E-17 7.396E-17 5.781E-17
HOURS) TEMP	355 513 642 745 828	893 945 987 1021 1070	1104 1127 1142 1153	1166 1170 1173 1175	1178 1179 1180 1181	1182 1182 1183 1183	1183 1183 1183 1184
TIME (IN ALT KM	120	170 180 190 200 220	240 280 300 320	340 340 380 400 420	1440 460 480 500 520	5 40 5 80 6 20 6 20	640 660 680 700 720

7.143E 03 7.028E 03 6.917E 03 6.807E 03	6.596E 03 6.493E 03 6.393E 03 6.295E 03 6.199E 03	6.105E 03 6.013E 03 5.923E 03 5.334E 03 5.022E 03	5.419E 03 5.227E 03 5.043E 03 4.869E U3	4.544E 03 4.392E 03 4.248E 03 4.110E 03	3.852E 03 3.731E 05 3.616E 03 3.505E 03 3.400E 03	3.298E 03 3.201E 03 3.108E 03 3.019E 03 2.953E 03
6.704E 05 6.287E U5 5.897E 05 5.534E 05 5.196E 05	4.879E 05 4.584E 05 4.308E 05 3.809E 05	3.583E 05 3.372E 05 3.175E 05 2.990E 05 2.577E 05	2.225E 05 1.925E 05 1.669E 05 1.450E 05	1.100E 05 9.602E U4 8.400E 04 7.360E 04 6.460E 04	5.679E 04 5.001E 04 4.411E 04 3.896E 04 3.447E 04	3.054E 04 2.710E U4 2.408E 04 2.142E 04 1.909E 04
1.522E 06 1.179E 06 9.142E 05 7.100E 05 5.522E 05	4.301E 05 3.355E 05 2.620E 05 2.049E 05	1.259E 05 9.885E 04 7.773E 04 6.120E 04 3.386E 04	1.888E 04 1.061E 04 6.008E 03 3.428E 03 1.970E 03	1.140E 03 6.647E 02 3.901E 02 2.305E 02 1.371E 02	8.212E 01 4.949E 01 3.001E 01 1.831E 01	6.940E 00 4.311E 00 2.693E 00 1.692E 00
1.665E 02 9.993E 01 6.017E 01 3.633E 01 2.200E 01	1.336E 01 8.134E 00 4.967E 00 3.041E 00 1.867E 00	1.150E 00 7.096E-01 4.391E-01 2.725E-01 8.359E-02	2.605E-02 8.244E-03 2.649E-03 8.641E-04 2.860E-04	9.601E-05 3.269E-05 1.129E-05 3.949E-06 1.400E-06	5.030E-07 1.830E-07 6.742E-08 2.515E-08 9.493E-09	3.626E-09 1.401E-09 5.479E-10 2.166E-10 8.657E-11
8.740E 03 5.591E 03 3.585E 03 2.305E 03	9.596E 02 6.215E 02 4.035E 02 2.626E 02 1.713E 02	1.120E 02 7.342E 01 4.823E 01 3.176E 01	4.064E 00 1.484E 00 5.491E-01 2.059E-01 7.817E-02	3.006E-02 1.170E-02 4.610E-03 1.838E-03 7.414E-04	3.025E-04 1.248E-04 5.205E-05 2.194E-05 9.350E-06	4.026E-06 1.751E-06 7.692E-07 3.413E-07
12.38 11.86 11.31 10.75	9.61 9.05 8.51 7.99 7.51	7.07 6.67 6.31 5.99 5.34	#	3.97 3.97 3.93 3.90 3.87	3.85 3.83 3.80 3.78	3.73 3.71 3.68 3.65 5.62
101.0 106.0 111.8 118.3	143.9 143.0 152.9 163.6	187.0 199.4 212.0 224.6 255.4	283.2 306.9 326.5 342.4 355.5	366.6 376.2 384.9 393.0 400.8	408.4 416.1 423.8 431.7	448.0 456.6 465.5 474.7 484.3
3.609E-07 2.974E-07 2.475E-07 2.080E-07	1.513E-07 1.309E-07 1.144E-07 1.008E-07 8.954E-08	8.017E-08 7.228E-08 6.558E-08 5.984E-08	4.035E-08 3.406E-08 2.909E-08 2.506E-08	1.891E-08 1.652E-08 1.449E-08 1.274E-08	9.928E-09 8.794E-09 7.807E-09 6.945E-09	5.533E-09 4.954E-09 4.444E-09 3.996E-09
4.540E-17 3.583E-17 2.844E-17 2.270E-17	1.476E-17 1.203E-17 9.877E-18 8.180E-18 6.832E-18	5.757E-18 4.896E-18 4.200E-18 3.636E-18 2.632E-18	1.998E-18 1.577E-18 1.283E-18 1.068E-18 9.029E-19	7.7256-19 6.664E-19 5.786E-19 5.047E-19	3.880E-19 3.416E-19 3.015E-19 2.666E-19 2.362E-19	2.097E-19 1.865E-19 1.661E-19 1.482E-19
1184 1184 1184 1184	1184 1184 1184 1185	1185 1185 1185 1185	1185 1185 1185 1185	1185 1185 1185 1185	1185 1185 1185 1185	1185 1185 1185 1185
740 760 780 800 820	8 ¢ 0 8 ¢ 0 8 8 0 9 0 0 9 2 0	940 960 980 1000 1050	1100 1150 1200 1250	1350 1400 1450 1500 1550	1600 1650 1700 1800	1850 1900 1950 2000 2050

N(H) /CM3	4.356E 04 2.941E 04 2.312E 04 1.965E 04 1.749E 04	1.602E 04 1.496E 04 1.417E 04 1.355E 04 1.265E 04	1.202E 04 1.154E 04 1.115E 04 1.084E 04 1.056E 04	1.031E 04 1.009E 04 9.681E 03 9.684E 03	9.319E 03 9.147E 03 8.481E 03 8.820E 03 8.664E 03	8.512E 03 8.364E 03 8.219E 03 8.078E 03 7.941E 03	7.807E 03 7.676E 03 7.548E 03 7.424E 03 7.424E 03
N(HE) /CM3	2.500E 07 1.559E 07 1.155E 07 9.345E 06 7.961E 06	7.009E 06 6.309E 06 5.767E 06 5.332E 06 4.665E 06	4.165E 06 3.767E 06 3.45E 06 3.150E 06 2.901E 06	2.679E U6 2.479E 06 2.298E 06 2.133E 06 1.981E 06	1.842E 06 1.714E 06 1.596E 06 1.487E 06	1.293E 06 1.206E 06 1.126E 06 1.052E 06 9.826E U5	9.185E 05 8.589E 05 8.035E 05 7.519E 05
N(0) /CM3	7.600E 10 3.456E 10 2.023E 10 1.345E 10 9.636E 09	7.243E 09 5.625E 09 4.469E 09 3.612E 09 2.443E 09	1.215E 09 1.215E 09 8.781E 08 6.407E 08	3.480E 08 2.583E 08 1.924E 08 1.438E 08	8.087E 07 6.087E 07 4.590E 07 3.468E 07 2.625E 07	1.991E 07 1.512E 07 1.151E 07 8.772E 06 6.697E 06	5.121E 06 3.922E 06 5.009E 06 2.312E 06 1.779E 06
N(02) /CM5	1.2006 11 3.586E 10 1.533E 10 7.851E 09 4.469E 09	2.722E 09 1.737E 09 1.145E 09 7.737E 08	1.871E 08 9.711E 07 5.147E 07 2.770E 07 1.508E 07	8.287E 06 4.587E 06 2.555E 06 1.430E 06 8.048E 05	4.548E 05 2.581E 05 1.470E 05 8.407E 04	2.778E 04 1.605E 04 9.308E 03 5.415E 03	1.850E 03 1.087E 03 6.402E 02 3.783E 02 2.243E 02
1.7225E 01 N(N2) /CM3	5.800E 11 1.924E 11 8.896E 10 4.862E 10 2.931E 10	1.881E 10 1.260E 10 8.706E 09 6.150E 09 3.218E 09	1.757E 09 9.868E 08 5.650E 08 3.280E 08	1.138E 08 6.779E 07 4.059E 07 2.442E 07	8.951E 06 5.449E 06 3.329E 06 2.040E 06 1.254E 06	7.737E 05 4.786E 05 2.969E 05 1.847E 05	7.213E 04 4.526E 04 2.848E 04 1.797E 04
INT GRAD= MEAN MOL WT	27.46 26.98 26.56 26.15 25.76	25.37 24.98 24.58 24.19 23.39	22.60 21.82 21.07 20.37 19.71	19.12 18.60 18.13 17.71	17.03 16.74 16.48 16.23	15.76 15.51 15.26 14.98	14.35 13.99 13.58 13.14
SCALE HT KM	11.4 16.8 21.3 25.1 28.3	31.1 33.5 35.6 37.5 40.9	2.45 2.45 2.45 2.45 2.45 2.45	56.6 58.8 60.8 62.7	66.2 67.8 69.3 70.8	73.9 75.5 77.2 79.1 81.2	83.6 86.2 84.3 92.9 96.9
8.66 SURE /CM2	3.802E-02 1.858E-02 1.097E-02 7.132E-03 4.905E-03	3.503E-03 2.570E-03 1.924E-03 1.463E-03 8.789E-04	5.486E-04 3.530E-04 2.329E-04 1.569E-04	7.510E-05 5.311E-05 3.801E-05 2.750E-05 2.008E-05	1.479E-05 1.097E-05 8.196E-06 6.161E-06	3.543E-06 2.710E-06 2.086E-06 1.615E-06	9.866E-07 7.794E-07 6.206E-07 4.982E-07
= 2.000, COS(TH)= DENSITY PRES GM/CM3 DYNE	3,536E-11 1,177E-11 5,489E-12 3,035E-12	1,2126-12 8,2806-13 5,8466-13 4,2326-13 2,3446-13	1.371E-13 8.340E-14 5.239E-14 3.379E-14 2.229E-14	1.501E-14 1.028E-14 7.156E-15 5.050E-15 3.607E-15	2.604E-15 1.898E-15 1.394E-15 1.032E-15 7.685E-16	5.757E-16 4.335E-16 3.280E-16 2.492E-16 1.902E-16	1.458E-16 1.122E-16 8.678E-17 6.739E-17 5.258E-17
HOURS) TEMP K	355 512 639 739 819	9882 932 973 1006 1055	1088 1111 1126 1138 1145	1151 1155 1158 1160	1163 1164 1165 1166	1166 1167 1167 1167	1168 1168 1168 1168
TIME (IN ALT KM	120 130 140 150	170 180 190 200 220	240 260 360 320	340 380 400 420	7 F F F F F F F F F F F F F F F F F F F	540 580 580 600 620	640 660 680 700 720

7.182E 03 7.066E 03 6.752E 03 6.841E 03 6.732E 03	6.625E 03 6.521E 03 6.419E 03 6.319E 03 6.222E 03	6.126E 03 6.032E 03 5.941E 03 5.851E 03 5.635E 03	5.430E 03 5.234E 03 5.048E 03 4.871E 03 4.703E 03	4.542E 03 4.389E 03 4.242E 05 4.103E 03	3.842E 03 3.720E 04 3.604E 03 3.492E 03	3.283E 03 3.186E 03 3.092E 03 3.002E 03 2.915E 03
6.593E 05 6.178E 05 5.790E 05 5.430E 05 5.093E 05	4.779E 05 4.486E 05 4.213E 05 3.957E 05	3.496E 05 3.287E 05 3.092E 05 2.910E 05 2.503E 05	2.157E 05 1.863E 05 1.612E 05 1.398E 05 1.214E 05	1.056E 05 9.209E 04 8.042E 04 7.034E 04 6.164E 04	5.410E 04 4.756E 04 4.188E 04 3.693E 04	2.886E 04 2.556E 04 2.268E 04 2.015E 04 1.793E 04
1.371E 06 1.058L 06 8.179E 05 6.332E 05	3.811E 05 2.963E 05 2.307E 05 1.798E 05 1.404E 05	1.098E 05 8.592E 04 6.735E 04 5.287E 04 2.902E 04	1.606E 04 8.960E 03 5.036E 03 2.852E 03 1.628E 03	9.354E 02 5.415E 02 3.156E 02 1.853E 02 1.095E 02	6.511E 01 3.898E 01 2.349E 01 1.424E 01 8.685E 00	5.330E 00 3.290E 00 2.043E 00 1.276E 00 8.010E-01
1.333£ 02 7.952£ 01 4.756£ 01 2.853£ 01 1.716£ 01	1.036E 01 6.266E 00 3.802E 00 2.313E 00 1.411E 00	8.633E-01 5.296E-01 3.257E-01 2.009E-01 6.068E-02	1.863E-02 5.808E-03 1.839E-03 5.912E-04 1.929E-04	6.385E-05 2.144E-05 7.299E-06 2.520E-06 8.815E-07	3.125E-07 1.122E-07 4.081E-08 1.503E-08 5.602E-09	2.113E-09 8.068E-10 3.116E-10 1.217E-10 4.807E-11
7.209E 03 4.584E 03 2.923E 03 1.868E 03	7.691E 02 4.953E 02 3.198E 02 2.070E 02 1.343E 02	8.731E 01 5.691E 01 3.718E 01 2.435E 01 8.536E 00	3.034E 00 1.094E 00 3.995E-01 1.479E-01 5.546E-02	2.106E-02 8.099E-03 3.153E-03 1.242E-03 4.952E-04	1.997E-04 8.144E-05 3.358E-05 1.400E-05 5.901E-06	2.513E-06 1.081E-06 4.700E-07 2.065E-07 9.148E-08
12.15 11.60 11.04 10.46 9.88	9.30 8.74 8.21 7.71	6.82 6.14 6.09 5.79 5.19	4.77 4.29 4.16 4.07	4.00 3.96 3.92 3.89	3.84 3.81 3.79 3.77	3.72 3.69 3.66 3.63
101.6 107.0 113.1 120.1	136.5 146.1 156.4 167.5	191.5 204.0 216.6 229.2 259.3	285.9 308.3 326.5 341.3	363.9 373.0 381.3 589.2 396.8	404.4 412.0 419.7 427.6 435.7	444.0 452.7 461.7 471.1
3.298E-07 2.722E-07 2.270E-07 1.912E-07	1.398E-07 1.213E-07 1.063E-07 9.393E-08 8.369E-08	7.513E-08 6.790E-08 6.174E-08 5.644E-08	3.236E-08 3.236E-08 2.765E-08 2.380E-08 2.061E-08	1.793E-08 1.566E-08 1.371E-08 1.204E-08	9.362E-09 8.282E-09 7.344E-09 6.526E-09	5.1886-09 4.6406-09 4.1596-09 3.7376-09
4.1236-17 3.2506-17 2.5778-17 2.0576-17	1.3386-17 1.091E-17 8.975E-18 7.447E-18 6.235E-18	5.269E-18 4.494E-18 3.869E-18 3.361E-18 2.454E-18	1.878E-18 1.492E-18 1.219E-18 1.018E-18	7.381E-19 6.369E-19 5.527E-19 4.817E-19	3.695E-19 3.249E-19 2.864E-19 2.529E-19 2.238E-19	1.984E-19 1.762E-19 1.567E-19 1.396E-19 1.246E-19
1169 1169 1169 1169	1169 1169 1169	1169 1169 1169	1169 1169 1169 1169	1169 1169 1169 1169	1169 1169 1169 1169 1169	1169 1169 1169 1169
740 760 780 800 820	840 860 880 900	940 960 980 1000	1100 1150 1200 1250 1300	1350 1400 1450 1500	1600 1650 1700 1800	1850 1900 1950 2000 2050

N(H) /CM3	:11	ዓ ተ 8E ዐተ	111	111	:н				70E 04	278E 04					.062E 04	ļ	ш	¥	31E 03	Ē	<u> </u>	E .	37E	196 03	36E	37.E					967E 03		699E 05			
z		2.948	•	5-	1.7	٥-۱	1	-	-3	1.2	1.2	-	=	0.1	0.1	<	?	਼	5 6	۲.	Ų.	*1	-	0.6	φ,	•	•	•	•	•	7.9	•	7.6	•	•	•
N(HE) /CM3	.500E	1.563E 07	- 16 1E	.412E	.028E	.071E	.365E	.817E	5.375E 06	•695E	. 185E	3622.	.442E	• 153€	2.900E 06	1	010E U	475E 0	2.292E 06	.126E 0	.974E 0	834E 0	<u>ا</u>	1.588E 06	0	377E 0	0	. 197E O	0	.043E 0	.739	0 3660	504	.952E 0	.438E 0	.960E 0
		10				60	60	60	60	60	60	60	90	08	08				08			07	07	07	20	07	20	07	07	90	90	90	90	90	90	90
N(0) /CM3	•	3.463E	٥,	~	9	~	9	-₹	3.602E	₹.	689	197	8.618E	.268	.594			2.507E		1.389E	1.038E	.779	.842	4.396E	.315	.50t	1.895E	1.437E	1.091E	•	6.324E	4.826E	3.689	2.825E	2.166E	1.664E
N(02) /CM3	200E 1	3.5926 10	536E 1	859E 0	463E 0	.710E	.722E	. 131E	7.607E 08	•625E	311E 0	330E 0	4.914E 07	530E 0	424E 0	1.10	340.	.288E	2.377E 06	.325₺	• 423E	.177E 0	.361E 0	1.339E 05	.626E 0	•358E 0	.500E	.439E	8.308E 03	.813E	.798E	.632E 0	9.546E 02	.602E 0	.298E 0	.948E 0
1.7139E 01 N(N2) /CM3	800	171	3616	871E	931E	.876E	.253E	.622E	6.068E 09	.152E			5.431E 08	14.		2020		597E	3.815E 07	286E	376E	.316E	-044E	3.070E 06	.875E	. 149E	.059E	.351E	2.690E 05	•668E	.037E	.468E	4-045E 04	.536E	•595E	•005€
INT GRAD= MEAN MOL WT	7 - 4	26.98	6.5	6.1	5.7	5.	0.	5.4	24.16	3,3	2.5	1.7	21.00	0.3	9.6		ָ •	Ç	18.07	Ŷ	~;	Ċ.	9	16.43	٦.	٥.	~	₹,	15.20	¢.	۰,		13.89	•	•	•
0711E-01, SCALE HT KM	1.1	16.7	21.2	24.9	28.1	30.7	33.1	35.2	37.1	9"01	43.6	46.4	49.1	51.7	54.1	4 7 7		58.5	9.09	62.5	64.2			69.0			73.5	75.2	6.97	78.9	81.0	83.5	86.2	89.4	93.1	97.3
IS(TH)= 7. PRESSURE DYNE/CM2	3.802E-02	1.856E-02	0-346	9.1E-0	51E-0	3.460E-03	30E-	386-	1.432E-03	-369	5.322E-04	3.4136-04	2.246E-04	1.5105-04	1.0346-04	0 12 1	1 1	34E-0	3.634E-05	25E-0	15E-0	38E-0	+3E-0	7.782E-06	+2E-0	12E-0	3.352E-06	61E-0	5	238-0	36E-0		7.343E-07	47E-	36E-	-990
= 3.000, CO DENSITY GM/CM3	3.536E-11					1.210E-12					1.340E-13		5.081E-14						6.871E-15			2.490E-15		1.330E-15			5.468E-16					1.376E-16	1.058E-16	8.167E-17	6.336E-17	4.939E-17
HOURS)	355	511	635	733	=	872	922	962	π 66	1043	1077	1100	1116	1128	1136	1142	7111	0	6#1	1152	1153	1155	1156	1156	1157	1158	1158	1158	1159	1159	1159	1159	1160	1160	0911	1160
TIME (IN ALT KM	120	130	0 † [150	091	170	180	190	200	220	240	260	280	300	320	340	2 7 6	000	085	004	1.20	0 11 11	1460	08 1	200	520	540	260	580	900	620	049	099	680	100	720

7.200E 03 7.083E 03	168E 0	355E U	745E 0						6.231E 03					5.639E 05	(>	0	0	0	4.700E 03	5.385	4 2 4 4 F	2376	1960 1960	3.462E 03	ያ3ሎ6 በ	712F 0	0.305	183F 0	3.576E 03	•273E	175F	080F	900P	2.903E 03
6.516E 05 6.102E 05									3.659E 05	4 3 RF	232	7000	78.58	2.456E 05		>	0	9	С	1.185E 05	30F	100	 	39E	5.986E U4					3.1536 04					1.725E 04
1.280E 06 9.858E 05					2 721.0									2.634E 04						1.446E 03	277F	7772F		.620E	9.535E 01					7-426E 00					6.729E-01
1.154E 02 6.853E 01					5 200E 00					7-1975-01	1 300F -01	2.604E-01	1.657F-01	4.961E-02	1 5105-03	- 310E-02	4.668E-03	1.466E-03	4.672E-04	1.512E-04	4-964E-05	1.654E-05	5.5865-06	1.913E-06	6.642E-07	2.337E-07	8.328E-08	3.006F-08	1.099E-08	4.067E-09	1.524E-09	5.775E-10	2.215E-10	8.592E-11	3.37 IE-11
6.355E 03 4.028E 03	260E 0	631E 0	042E 0		1 282E 02			-	-					7.163E 00	2 527E 00	700	040E	278E	1.205E-01	485E	1.691E-02	6.458E-03	2.497E-03	9.769E-04	3.8686-04	1.550E-04	6.278E-05	2.572E-05	1.066E-05	4-463E-06	1.889E-06	8.076E-07	3.489E-07	1.523E-07	6.710E-08
11.99	10.86	10.27	69.6	_	8.55	•	? '	٠.	•	29.9	6.30	5.97	5.68	5.10	17.71	 	† † †	4.26	4.13	4.05	3.99	3.95	3.91	3.88	3.86	3.83	3.81	5.78	3.76	3.74	3.71	3.68	3.65	3.62	3.59
102.2	114.2	† · 7	129.4	138.4	148.2		0.00	1.01	182.1	194.5	207.0	219.7	232.2	261.7	287.6		20%	\$26.5	340.7	352.4	362.3	371.2	379.4	387.1	394.7	402.2	1.604	417.4	425.3	433.5	441.9	450.6	459.7	469.1	479.0
3.114E-07 2.574E-07	2.149E-07	1.815E-07	1.545E-07	-331F-	1.1575-07	1410		- 74756-	•029E-	-219E-	.534E-	-950E-	5.445E-08	-447E-	٦,	J L 7 N	-130E-	•680E-	2.307E-08	•997E−	-736E-	•515E-	1.326E-08	-164E-	.024E-	33E-	36E-	77E-	6.285E-09	74E-	4-999E-09	6 JE-	3.997E-09	89E-	30E-
3.870E-17 3.050E-17	2.4.18E-17	1-400E-17	1.55 IE-17	1.256F-17	1.026F-17	01-3644	4 0000	1.020E-18	5.888E-18	4.986E-18	4.262E-18	3.677E-18	3.202E-18	2.351E-18	1-808E-18	0.1.7.1.1.0	01-3744°I	1.182E-18	9.881E-19	8.379E-19	7.1776-19	6.192E-19	5.372E-19	4.680E-19	4.090E-19	3.5856-19	3.151E-19	2.775E-19	2.448E-19	2.165E-19	1.918E-19	1.702E-19	1.5136-19	1.347E-19	1.201E-19
1160	09[]	0 ;	<u> </u>	1161	1161	1141			9	1161	1161	1161	1161	1161	1161	1711		0	191	191	1161	1161	1161	1161	1161	1161	1161	1161	1161	1161	1161	1911	1161	1161	1161
740	082		079	940	860	ARO		200	420	046	096	980	1000	1050	1100	1150		1000	1250	1300	1350	1400	1450	1500	1550	1600	1650	1700	1750	1800	1850	0041	1950	2000	2050

N(H) /CM3	4.356E 04					.632E	.525E	1.443E 04	.379E	.284E	1.216E 04		1.124E 04			1.036E 04		9.911E 03			.339E 0	.165E 0	8.997E 03	.835E 0	.677E 0	8.524E 03	.575E	-229E	088E	• 94 9E	三 日 十 1	35E		7.306E 03
NCHE) /CM3	2.5006 07	36 CE	16 /E	+72E	083E	-119E	3404e	5.847E 06	.397E	.705E			3.432E 06			.663E	.462E	2.280E 06	• 115E	.963E	.825E	€697E	1.579E 06	-471E	-370E	1.278E 06	Ų.	<u>ا</u> پ	w u	LL +	0.58E 0	46/E 0	0 440	6.932E 05
N(0) /CM3	7.600E 10	E .	.038E	.356E	.705E	.276E	• 630E	4.455E 09	•585E	•406E	-667E	• 180E	8.484E 08	.164E	.513E	.325	-462E	1.829£ 08	•364E	.020E	543E	742E	4.323E 07	261E	+64E	1.866E 07					.760E	-640E	./88E	1.643E 06
N(02) /CM3	1.200E 11					2.694E 09							4.755E 07			7.512E 06		2.295E 06			03.9E	284E	1.297E 05	389€	226E	2.426E 04					300E	308E	400	3.221E UZ 1.903E 02
1.7032E 01 N(N2) /CM3	5.800E 11	. 931E 1	.939E	.876E 1	.928E 1	3698	244E	8.534E 09	988E	093E	307∂	292E (5.279E 08	045E	176E			3.698E 07		717	373E	300 é	2.984E 06	824E	1 18E	6.875E 05	•241E	.624E	ш (•013E	321E	955E	129t	9.851E 03
INT GRAD= MEAN MOL WT	27.46	26.98	26.55	26.14	25.74	25.34	24.94	24.53	24.13	23.31	22.50	21.72	20.96	20.26	19-61	19.03	18.50	18.04	17.64	17.28	16.96	16.68	16.42	16.17	15.93	15.70	₹.	Ξ.	06-71	r,	-2	φ.	* (12.50
3000E-01. SCALE HT KM	. .	16.7	21.1	24.7	27.8	30.5	32.9	35.0	36-9	ħ=0ħ	43.5	46.4	49.1	51.7	54.2	56.5	58.7	60.7	62-6	4.49	0.99	67.6	69.5	7.07	72.2	73.7	75.3	77.1	79.1	81.2	×.	ġ,	• •	9.26
S(TH)= 5.(PRESSURE CYNE/CM2	3.802E-02	5E-0	71E-0	31E-0	20E-0	L.	-396	1.858E-03	07E-	87E-	-207E-	.337E-	2.196E-04	-477E-	.012E-	Ш	33E-	3.564E-05	77E-	31E-	34E-	26E-	7.659E-06	3.E-	+8E-	3.3055-06	27E-	-311 -311	-1 to	72E-	-195E-	-268E-	- (4 III	3.7746-07
: 4.000, CO DENSITY GM/CM3	3.536E-11	1.1816-11	5.516E-12	3.046E-12	1.856E-12	1.206E-12		5.747E-13			1.3146-13	7.944E-14	4.966E-14	3.192E-14	2.1016-14	1-4125-14	9.667E-15	6.723E-15	4.741E-115	3.385E-15	2.442E-15	1.779E-15	1.306E-15	9.659E-16	7.188E-16	5.380E-16	4.048E-16	3.060E-16	2.324E-16	1.772E-16	1.357E-16	1.0446-16	8-065E-17	4.882E-17
HOURS) TEMP K	355	509	632	728	80 #	865	† 6	454	487	10.38	1073	1097	1115	1127	1136	1142	1147	1150	1153	1155	1156	1157	1158	1159	1159	1160	1160	0911	1161	1911	1161	1161	191	1162
TIME (IN ALT KM	120	~	⇉	150	9	170	180	190	200	220	240	260	280	300	320	340	360	380	00 4	420	011	1460	1480	200	520	540	260	580	009	620	049	099	089	720

7.186E 03 7.068E 03 6.954E 03 6.842L 03 6.732E 03	6.625E 03 6.520L 03 6.418E 03 6.317L 05 6.219L 05	6.1236 03 6.0296 03 5.047E 03 5.047E 03 5.047E 03	5.425E 03 5.227E 03 5.040E 03 4.662E 05	4.532E 03 4.578E 03 4.231E 03 4.091E 03 3.957E 03	3.830E 03 3.708E 03 3.591E 03 5.479E 03	3.270E 03 3.172C 03 3.078C 03 2.987E 03 2.901E 03
6.490E 05 6.078E 05 5.695E 05 5.338E 05 5.005E 05	4.695E 05 4.405E 05 4.135E 05 3.883E 05	3.428E 05 3.222E 05 3.030E 05 2.850E 05 2.449E 05	2.109E 05 1.820E 05 1.574E 05 1.363E 05	1.029E 05 8.959E 04 7.817E 04 6.833E 04 5.982E 04	5.24.6E 04 4.60%L 04 4.055E 04 3.57.8E 04 3.154E 04	2.788E 04 2.468E 04 2.188E 04 1.943E 04
1,265E 06 9,745E 05 7,521E 05 5,813E 05 4,500U 05	3.488E 05 2.708E 05 2.105E 05 1.639E 05 1.278E 05	9.973E 04 7.7746 04 6.103E 04 4.763E 04 2.617E 04	1.4435 04 8.0216 03 4.494E 03 2.556E 03 1.442E 03	8.2656 02 4.7686 02 2.7706 02 1.6216 02	5.662E 01 3.379E 01 2.030E 01 1.227E 01 7.462E 00	4.566E 00 2.811E 00 1.740E 00 1.084E 00 6.785E-01
1,128E 02 6,707E 01 4,000E 01 2,392E 01 1,435E 01	8.630E 00 5.206E 00 3.149E 00 1.910E 00	7.089E-01 4.336E-01 2.659E-01 1.635E-01	1.495E-02 4.630E-03 1.456E-03 4.649L-04 1.507E-04	4.955E-05 1.655E-05 5.593E-06 1.918E-06 6.670L-07	2,350E-07 8,387E-08 3,032E-08 1,110E-08 4,113E-09	1.543E-09 5.857E-10 2.249E-10 8.736E-11 3.432E-11
6.232E 03 5.952E 03 2.513E 03 1.602E 03	6.561E 02 4.214E 02 2.714E 02 1.752E 02	7.353E 01 4.781E 01 3.116E 01 2.035E 01 7.090E 00	2.505E 00 8.974E-01 3.259E-01 1.199E-01	1.688E-02 6.455E-03 2.499E-03 9.791E-04 3.882E-04	1.557E-04 6.316E-05 2.591E-05 1.075E-05 4.506E-06	1.909E-06 8.174E-07 3.536E-07 1.545E-07 6.815E-08
11.97 11.41 10.84 10.25 9.67	9.09 8.54 8.01 7.52 7.07	6.65 6.29 5.96 5.67	4.70 4.44 4.26 4.13	3.99 3.95 3.88 3.86	3.83 3.81 3.78 3.76 3.74	3.71 3.68 3.65 3.62 3.59
102.5 108.2 114.6 121.8	138.9 148.7 159.4 170.7	195.0 207.6 220.3 232.8 262.3	288.1 309.6 327.0 341.2 352.9	362.8 371.7 379.9 387.6 395.2	402.7 410.3 418.0 425.9	442.4 451.2 460.3 469.7 479.6
3.090E-07 2.555E-07 2.135E-07 1.802E-07 1.537E-07	1.324E-07 1.152E-07 1.012E-07 8.963E-08	7.1996-08 6.5186-08 5.9366-08 5.4346-08 4.4406-08	3.703E-08 3.133E-08 2.678E-08 2.306E-08	1.736E-08 1.515E-08 1.326E-08 1.164E-08	9.04.1E-09 7.994E-09 7.085E-09 6.293E-09 5.602E-09	4.998E-09 4.469E-09 4.005E-09 3.596E-09
3.828E-17 3.018E-17 2.394E-17 1.912E-17 1.537E-17	1.2466-17 1.0186-17 8.3866-18 6.9726-18 5.8516-18	4.956E-18 4.238E-18 3.659E-18 3.187E-18 2.342E-18	1.802E-18 1.438E-18 1.179E-18 9.862E-19 8.365E-19	7.166E-19 6.184E-19 5.366E-19 4.676E-19 4.088E-19	3.5846-19 3.1506-19 2.7746-19 2.4486-19 2.1656-19	1.918E-19 1.702E-19 1.514E-19 1.348E-19 1.202E-19
1162 1162 1162 1162	1162		1163 1163 1163 1163	1163 1163 1163 1163	1163 1163 1163 1163	1163 1163 1163 1163
740 760 780 800 820	8 40 8 40 9 9 0 9 2 0	940 980 1000 1050	1100 1150 1200 1250	1350 1400 1450 1500	1600 1650 1700 1750	1850 1900 1950 2000 2050

									_								_						_	_		_		_					_	_	_							
			ć	5,3	5 6	5 8	3	•	3	đ	Sã	5 8	3		_	_	_		ā		Š	6	0 0	2 6	0.5	S	3	3 3	3 3	3 6	03.5	3	3 3	2 5	0.5	3	03	03	3	0.5	03	63
	E Z	/CM3	7.4.7	1000	7077	1000	1.789E	i	- 639E	1,20F	1 7 7 7	707	.279E		.208E	154E	1121	3770	υ α 133 •	1	3000	1000	777	0 0	- 278H	37.70	-	1	† a	200	369€.	5	2 5	± ;	1556	0	5	729	-601E	476	353	234€
			=	Ė	10	ý 5	, -	•	_	-	-	-	-		_	_	_	_	-	•	-	c	> 0		Š	ř	5	Ċ	. a	oi∝	ာ်	3	o a	Ö	4 0	_	~	7	-	<u>٠</u>	`	,
	_		7				9	,	90	90	2 6	2 6	9		90	90	90	3	2 6	,	Š	2	9 4	3	9 4	2	ć	2 4	2 6	2 5	90	40	3 6	9 6	0 4	0 1	S	50	90	05	90	0.5
	(HE)	/CM3	100	7.F	72.2	121	19E		4 SE	166	184	200	82E		54E	38E	396	190	0	,	444	7 7 2	יי ממ	1 1	0000	i O	36) / C	7 2	1 L	367E	7,40		ш ц - с	10.00	1 0	19E	90E	390	6.3E	57E	- 986E
	Z	`	7,	1	-	0	8.119E		7	4.0			4.68		 	3.7	5.3	,	α,	•	•	,	•	•	• • •		-			1 4	-		•	•		- 6	6.7	0	8.5	6.	7.	6-9
			2	2 9	2	2 2	6		3	60	0	000	3		6	60	90	98	980)	90	ğ	9 0	2 2	0 a	3	20	5 6	5 5	. 2	20	20			5 6	3 3	90	90	90	90	90	90
	9	/CM3	700	785	1	20.5	.715E		~	_	~	١.	82E		184	919	98E	17	189F	1	2	3	3 3	1	U 4	5	a,	3 2	- 4	4	54E	364	70 E	300	4356		0.5E	62E	8886	90e	03E	77E
-	Z	`	7.6		2.0	-	2.6		٠	9.5			2.3		•	=	8.3	9	17 17	•	۲,	4	. «	`	10	•	7	• °	7	۲.	2.5	-	-	-	- a		0.0	۰.	3.8	٠,	~	٧,
	_		=	2	2	60	60		3	60	60	E C	0.8		8	07	07	0.7	07		90	90	200	9) r	,	50	1 1	50	70	10	40	100	† N	3 6	ָר רָ ס כ	60	03	03	02	02	02
	703	/CM3	00E	03E	=	156E	438E		177E	9069	~	80F	88€		344	27E	10E	31E	378E		88E	135	ا ک ا	1000	1200F	,	L/	١.		-	611E	70F	- L	2 2 2	28 PE) (UZE	826E	78 E	85E	93E	60 €
•	•	•					7		٠	•	•	7	5.488		-	8	7 . 4	2,5	-		7.5	77	2	-	7	•	•		•		9.7			•			•	-8	•	6.3	3.7	2.5
0			=	=	10	0	10		0	0	60	60	60	9	Š	80	90	90	90		98	20	20	2.0	70	;	90	90	90	90	90	20	90	2 5	3 6	1 4	ņ	10	†0	† 0	đ	† 0
6910E	[N]	CM M	00	7	5	77E	21		9	≉	7	5	₩8E	. 1	1 1	7. 1.	27E	29E	.777E		53 E	86E	77E	A L	384F	!	3.3	8	55	₩6±	<u>₹</u>	6	8	6	14.0		3	2	90E	88	2	ň
9.	Z	`				4.8			æ.	1.2	8.4	6.5	3.0		•	·	5.2	3.0	1.7		•	•	•		7		-7	7	Ξ.	1.9	~		٠.) O	6	, -	-	7.13	₹,	Φ,	`	٦.
RAC=	z	<u>⊢</u>	۰	8	5	#	м	,	~	~	2	_	0	c	•	_	9	_	~		'n	~	~	_	. –			_	•	_	ത	•			œ	. ~	^	5	~	_		.
NT GR	A L	¥0L	~	•	•0	26.1	ы		٠				23.3		•	•	ċ	ċ	19.6		٥.	5	0	4	17.3			•		16.21		7	5		10	, <	•	3	٠,	٠,	7	٠,
- - -	щ	₹	7	9	0	9.	۲.		#	ھ	o,	6.	'n	0	o .		~	~1	٥,			+	S	ري.	M		0	Ŋ	_	9.	_	~	m	0	0		•	. #	_	21	٠,	œ
82E-01	420	Ħ	=	16.	21,	24.	27.	,	Š.	32.	₹.	36.	0,	2.2	j	0	•	N	#		57.	20	61.	63	65		99	68	70.	71.	73.	74.	76.	78.	79	ď	5	8	87.	0.	, ,	6
2.58	Ϋ́ :	Z.		o	$\overline{}$	0.3	0	į	Ş	03	03	03	₹	á	.	3 (†	ъ О	đ		0	0	0	0	90		05	05	90	90	90	90	90	90	90	9	9	20	20	٠. م	> r	<u>,</u>
 	200	NE/C	02E-	53E-	88E-	1156-(86E-		<u>.</u>	716-	39E-	92E-(08E-	7 1 5	J (205	- J / E	84E-	122E-(54E-	78E-	48E-	-36 to	4 1E-		<u>.</u>	4	L	34E-	il.	ւև		l.	04E-	.!		52E-	١.	١,	L.	L.
.S(TH) = 2.	K	ò	3.80	1.8	0.1	7.0	* • 4	•	ŋ.	₹.	æ	.3	~	-	•	0	-	₹	۰,		7.1	0	3.6	2-6	6		→	0.	9.0	0.9	2	3.4	2-6	2.0	1.6	1,2	-	6	no o	•	•	9
ຽຸ			=	_	12	12	75	5	7 :	~	2	13	-2	~	2 -	:	≠ .		<u>≠</u>		<u> </u>	2	2	15	15		15	15	15	16	91	16	16	16	16	16		9 :	0 !	<u>- :</u>	- 1	<u>-</u>
5.000,	100	Σ Σ	3.536E-11	83E-	25E-	47E-	52E-	į	1000	3 IE-	93E-	-306	36E-	946	1 L	1	- L -	7.1E-	-396		146-	22E-	-30¢	39E-	47E-		98E-	-39Z	16E-	-39€	59E−	12E-	38E-	16E-	31E-	-491	,	12E-	126	777	100	7
11	3 (٥	3.5	-	5.5	3.0	-8	-	7.	8	5.0	7	2.236E-13	Č			>	2.	2.096E-14		† •	6	6.7	9.4	3-447E-15		2.4	.8	 	6.6	7.469E-16	5.612E-16	4.2	3.2	2.4		:	1.442E-1	- :	0		7.0
HOURS)	<u> </u>		355	909	53	754	00	17	5:	=	53	987	- -	20		5 6		<u>_</u>	131		29	₹	68	7	1173		174	75	92	11	82	178	78	62	62	62		1180	9 6	6 6	2 6	20
Y Z	- '	-	1	'	~		~	J		ا -و	-بي	<i>J</i> -	~	1			- ;	_			=	=	=	=	Ξ		Ξ	Ξ	Ξ	Ξ		=	Ξ	Ξ	Ξ	=	•	=:				Ξ
TIME (1		ķ.	120	130	07	150	160	170	2 0	200	06.	200	220	240	0 4 0		0 0	00	320		340	200	380	00	120		011	091	08+	200	220	540	260	580	200	520		019				2
֡֟֞֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֟֓֓֓֓֓֓֓֓֓֓֓֓֡֓֓֓֓֟֓֓֓֟		_										•	•	•		•		•	.,		,	.,		-	~		~	~	~	-,	•	41	•,	٠,	~	٠,	•	~	. 4	. r	- 1	-

7.117E 03 7.002E 03 6.591E 05 6.781E 05	6.570E 03 6.467E 03 6.367E 03 6.269E 03	6.079E 03 5.988E 03 5.897E 03 5.397E 03	5.395E 03 5.202E 03 5.019E 03 4.845E 03	4.5216 05 4.3706 05 4.2256 05 4.0886 05 3.9566 05	5.831E 03 3.710E 03 3.595E 03 3.485E 03 5.380E 04	3.279E 03 3.182E 03 5.089E 03 5.000E 03
6.547E 05 6.138E 05 5.757E 05 5.402E 05 5.070E 05	4.761E 05 4.472E 05 4.202E 05 3.949E 05	3.493E 05 3.287E 05 3.094E 05 2.913E 05 2.509E 05	2.166E 05 1.873E 05 1.623E 05 1.409E 05	1.068E 05 9.323E 04 8.152E 04 7.141E 04 6.265E 04	5.506E 04 4.846E 04 4.273E 04 3.773E 04	2.955E 04 2.621E 04 2.328E 04 2.071E 04 1.845E 04
1.373E 06 1.062E 06 8.234E 05 6.390E 05 4.966E 05	3.865E 05 3.012E 05 2.351E 05 1.837E 05	1.127E 05 8.843E 04 6.949E 04 5.467E 04 3.019E 04	1.681E 04 9.429E 03 5.330E 03 3.036E 03	1.007E 03 5.858E 02 3.435E 02 2.026E 02 1.203E 02	7.193E 01 4.328E 01 2.621E 01 1.597E 01	6.035E 00 3.743E 00 2.335E 00 1.465E 00 9.240E-01
1.351E 02 8.096E 01 4.867E 01 2.934E 01	1.076E 01 6.541E 00 3.988E 00 2.438E 00	9.190E-01 5.665E-01 3.501E-01 2.169E-01 6.630E-02	2.059E-02 6.495E-03 2.080E-03 6.761E-04 2.230E-04	7.464E-05 2.533E-05 8.718E-06 3.041E-06 1.075E-06	3.849E-07 1.396E-07 5.129E-08 1.907E-08	2.735E-09 1.054E-09 4.109E-10 1.620E-10 6.457E-11
7.281E 03 4.651E 03 2.979E 03 1.912E 03	7.942E 02 5.137E 02 3.331E 02 2.165E 02 1.410E 02	9.211E 01 6.030E 01 3.956E 01 2.602E 01 9.214E 00	3.309E 00 1.205E 00 4.445E-01 1.661E-01 6.291E-02	2.412E-02 9.363E-03 3.679E-03 1.463E-03 5.884E-04	2.394E-04 9.850E-05 4.098E-05 1.723E-05 7.325E-06	3.146E-06 1.365E-06 5.981E-07 2.647E-07
12.17 11.63 11.07 10.50 9.93	9.36 8.80 8.27 7.77	6.88 6.49 6.15 5.84 5.23	4.80 4.31 4.17	4.01 3.96 3.92 3.89	3.84 3.82 3.80 3.77 3.75	3.73 3.70 3.67 3.64
102.4 107.8 113.9 120.8	137.1 146.5 156.8 167.9	191.7 204.2 216.8 229.5 259.8	286.8 309.6 328.3 343.5	366.7 376.1 384.6 392.6 400.3	407.9 415.5 423.2 431.1	447.6 456.2 465.2 474.5
3.3276-07 2.7506-07 2.2966-07 1.9356-07	1.418E-07 1.231E-07 1.079E-07 9.537E-08 8.499E-08	7.630E-08 6.897E-08 6.271E-08 5.734E-08	3.8926-08 3.2926-08 2.8156-08 2.4266-08 2.1036-08	1.8316-08 1.6006-08 1.4036-08 1.2346-08	9.610E-09 8.511E-09 7.555E-09 6.720E-09	5.352E-09 4.791E-09 4.298E-09 3.864E-09
4.125E-17 3.259E-17 2.590E-17 2.071E-17 1.667E-17	1.351E-17 1.103E-17 9.087E-18 7.546E-18 6.323E-18	5.345E-18 4.561E-18 3.926E-18 3.411E-18 2.489E-18	1.903E-18 1.511E-18 1.235E-18 1.030E-18	7.4786-19 6.4576-19 5.6086-19 4.8926-19	3.7616-19 3.3116-19 2.9216-19 2.5836-19 2.2886-19	2.030E-19 1.805E-19 1.607E-19 1.434E-19
1180 1180 1181 1181	11811	1181 1181 1181 1181	1181 1181 1181 1181	1381 1181 1181 1181	1811 1811 1811 1811	1181 1181 1181 1181
740 760 780 800	840 860 880 900	940 960 980 1000	1100 1150 1200 1250	1350 1400 1450 1500	1600 1650 1700 1750	1850 1900 1950 2000 2050

N(H) /CM3	4.356E 04	2.971E 04					111	1.4366 04	111	a			1.086E 04					9.522E 03			3484	8.822E 05	567E	517E	371E				7.827E 05		375€.	.453E	.554E	7.105E 05	
N(HE) /CM3		1.574E 07				13.5E	39 IE	5.810E 06	34 OE	919E	3980	3019	3.331E 66	047E	80 SE	587E	398E	2-226E 06	070€	927E		1.676E 06	•565E		.366E	1.278E 66			1.048E 06		204E 0	530E 0	0000 0000 0000 0000	7.150E 05	
N(0) /CM3		3.485E 10			_	243E	580E	4.397E 09	526€	356E			8.379€ 08		1.1	3.378L 08		1.903E 08			.256E	6.282E 07	-770E	3099.	.801E	148E	250E	3692	9.781E 06	249E	-835E	•517E	.503E	2.115E 06	
N(02) /CM3		3.608E 10			_			1.092E 09			1.732E 08		4.806E 07			092E	567E	2.596E 06	485E	539E	934€	2.863E 05	568E	750E	721E	3.368E 04			7.010E 03		5016 0	50 1E 0	0515 0	3.300E 02	
1.6783E 01 N(N2) /CM3	104	1.937E 11			111			8.366E 09				-	5.304E 08			.130E	.721E	4.097E 07	.511E	.546E	_	5.937E 06	_	_	_	9.111E 05								1.586E 04	
INT GRAD≠ MEAN MOL WT	27.46	26.98	26.55	26.13	25.73	25.32	24.92	24.52	24.11	23.31	22.51	21.75	21.02	20.33	19.71	19.14	18.62	18.17	17.77	17.41	17.09	16.81	16.55	16.31	16.08	15.86	15.63	15.39	15.14	14.87	14.57	14.24	88 SI	13.06	
76E-06, SCALE HT KM	7.	16.6	20.9	24.5	27.6	30.4	32.9	35.1	37.3	 	9.44	47.8	50.8	53.6	56.2	58.6	6.09	63.1	65.1	6.99	68.7	70.3	71.9	73.4	74.9				81.6		85.8	88.2		97.9	
)≠ 1.11 ESSURE NE/CM2	3C2E-0	1.851E-02	385E-0	987E-0	762E-0	.374E-0	-4.60E-0	1.8336-03	3916-0		5.235E-04	3.396E-04	2.263E-04	1.5436-04	1.072E-04	.564E-0	•414E-0	921E-	*870E-0	.120E-0	-578E-	1.183E-05	.932E-	.783E-	.179E-	3.977E-06	070E-	382E-	1.859E-06	459E-	-	-152E-	-321E-	4.790E-07	
= 6.000, COS(TH DENSITY PR GM/CM3 DY	3.536E-11	1.185E-11	5.530E-12	3.044E-12	1.8468-12	1.1936-12	8.067E-13	5.640E-15	4.049E-13	2.216E-13	1.287E-13	7.847E-14	4.9536-14	3.2196-14	2.1456-14	1-4598-14	1.011E-14	7-119E-15	5.081E-15	3.670E-15	2-6796-15	1.9736-15	1.465E-15	1.096E-15	8.247E-16	6.241E-16	4.746E-16	3.626E-16	2. 783E-16	2.144E-16	1.659E-16	1.288E-16	1.004E-16	6.179E-17	
(IN HOURS)= T TEMP	355	507	627	721	798	861	†1 6	958	966	1056	1100	1132	1155	1172	181	1193	1199	1204	1207	1209	1211	1213	1213	1214	1215	1215	1216	1216	12.16	1217	1217	1217	1217	1217	
TIME (II ALT KM	120	130	140	150	160	170	180	190	200	220	240	260	280	300	320	340	360	380	004	420	044	1460	1480	200	520	240	260	580	009	950	049	099	0.00	720	

6.992E 03 6.883E 03 6.776E 03 6.672E 03	6.470E 03 6.373E 03 6.277E 03 6.183E 05	6.002E 03 5.914E 03 5.828E 03 5.743E 03 5.539E 03	5.345E 03 5.160E 03 4.984E 03 4.817E 03 4.656E 03	4.504E 03 4.358E 03 4.218E 03 4.085E 03	3.435E 03 3.719E 03 3.607E 03 3.500E 03	3.298E 03 3.204E 03 3.113E 03 3.026E 03 2.942E 03
6.696E 05 6.290E 05 5.911E 05 5.557E 05 5.226E 05	4.916E 05 4.627E 05 4.356E 05 4.102E 05 3.864E 05	3.641E 05 3.433E 05 3.237E 05 5.053E 05 2.643E 05	2.291E 05 1.990E 05 1.732E 05 1.511E 05	1.0125 05 1.0126 05 8.8856 04 7.8146 04 6.884E 04	6.073E 04 5.367E 04 4.750E 04 4.210E 04 3.737E 04	3.322E 04 2.957E 04 2.656E 04 2.355E 04 2.104E 04
1.647E 06 1.285E 06 1.003E 06 7.846E 05 6.145E 05	4.819E 05 3.785E 05 2.976E 05 2.344E 05 1.848E 05	1.459E 05 1.154E 05 9.131E 04 7.237E 04	2.307E 04 1.317E 04 7.576E 03 4.390E 03 2.562E 03	1.505E 03 8.908E 02 5.306E 02 3.181E 02 1.920E 02	1.166E 02 7.126E 01 4.381E 01 2.710E 01 1.686E 01	1.055E 01 6.641E 00 4.203E 00 2.674E 00 1.711E 00
2.003£ 02 1.220£ 02 7.448£ 01 4.560£ 01 2.800£ 01	1.724E 01 1.064E 01 6.588E 00 4.089E 00 2.545E 00	1.588E 00 9.932E-01 6.229E-01 3.916E-01	3.995E-02 1.305E-02 4.328L-03 1.456E-03 4.969E-04	1.719E-04 6.031E-05 2.144E-05 7.724E-06 2.818E-06	1.041E-06 3.897E-07 1.476E-07 5.657E-08 2.194E-08	8.607E-09 3.415E-09 1.370E-09 5.557E-10 2.278E-10
1.024E 04 6.634E 03 4.307E 03 2.803E 03 1.828E 03	1.196E 03 7.837E 02 5.149E 02 3.391E 02 2.239E 02	1.481E 02 9.821E 01 6.527C 01 4.348E 01 1.589E 01	5.890E 00 2.211E 00 8.411E-01 3.240E-01 1.264E-01	4.989E-02 1.994E-02 8.060E-03 3.296E-03 1.363E-03	5.701E-04 2.410E-04 1.030E-04 4.448E-05 1.940E-05	8.551E-06 3.806E-06 1.711E-06 7.762E-07 3.555E-07
12.59 12.10 11.58 11.04	9.93 9.38 8.33 7.84	7.39 6.97 6.59 6.25 5.55	5.04 4.68 4.26 4.14	4.06 3.96 3.89	3.84 3.84 3.82 3.80	3.76 3.73 3.71 3.68 3.66
102.1 106.9 112.4 118.5 125.5	133.3 141.9 151.3 161.5	184.1 196.2 208.7 221.3 252.7	282.0 307.6 329.1 346.7 361.3	373.5 384.1 393.4 402.1 410.2	418.1 425.9 433.7 441.7	458.0 466.5 475.3 484.3
3.922E-07 3.239E-07 2.698E-07 2.269E-07 1.925E-07	1.649E-07 1.426E-07 1.244E-07 1.095E-07 9.710E-08	8.679E-08 7.812E-08 7.077E-08 6.448E-08 5.221E-08	4.330E-08 3.655E-08 3.124E-08 2.694E-08 2.340E-08	2.0426-08 1.7906-08 1.5746-08 1.3886-08	1.088E-08 9.660E-09 8.600E-09 7.671E-09	6.142E-09 5.512E-09 4.957E-09 4.466E-09
4.878E-17 3.870E-17 3.085E-17 2.473E-17	1.617E-17 1.321E-17 1.086E-17 9.001E-18 7.518E-18	6.3316-18 5.3766-18 4.6046-18 3.9776-18 2.8586-18	2.153E-18 1.689E-18 1.367E-18 1.134E-18 9.573E-19	8.1886-19 7.0706-19 6.1476-19 5.3736-19 4.715E-19	4.152E-19 3.666E-19 3.245E-19 2.878E-19 2.558E-19	2.277E-19 2.031E-19 1.814E-19 1.623E-19 1.455E-19
12.18 12.18 12.18 12.18	1218 1218 1218 1218	1218 1218 1218 1218	1218 1218 1218 1218 1218	1218 1218 1218 1218	12 18 12 18 12 18 12 18 12 18	1218 1218 1218 1218
740 760 780 800	840 860 880 900	940 960 980 1000 1050	1100 1150 1200 1250	1350 1400 1450 1500	1600 1650 1700 1750	1850 1900 1950 2000 2050

N(H) /CM3	4.356E 04 2.977E 04 2.361E 04 2.013E 04 1.787E 04	1.627E 04 1.506E 04 1.411E 04 1.333E 04 1.215E 04	1.131E 04 1.068E 04 1.021E 04 9.833E 03	9.278E 03 9.060E 03 8.867E 03 8.693E 03	8.381E 03 8.238E 03 8.102E 03 7.971E 03 7.645E 03	7.722E 03 7.603E 03 7.486E 03 7.375E 03	7.154E 03 7.048E 03 6.945E 03 6.843E 03
N(HE) /CM3	2.500E 07 1.577E 07 1.178E 07 9.545E 06 8.106E 06	7.087E 06 6.318E 06 5.712E 06 5.220E 06 4.467E 06	3.918E 06 3.501E 06 3.170E 06 2.899E 06 2.670E 06	2.472E 06 2.298E 06 2.142E 06 2.001E 06 1.872E 06	1.754E 06 1.645E 06 1.543E 06 1.450E 06 1.362E 06	1.281E 06 1.205E 06 1.134E 06 1.068E 06	9.475E 05 8.931E 05 8.421E 05 7.944E 05 7.496E 05
N(0) /CM3	7.600E 10 3.490E 10 2.050E 10 1.359E 10 9.666E 09	7.192E 09 5.521E 09 4.336E 09 3.468E 09 2.310E 09	1.604E 09 1.147E 09 8.391E 08 6.235E 08	3.557E 08 2.717E 08 2.086E 08 1.608E 08	9.649E 07 7.503E 07 5.84TE 07 4.566E 07 3.572E 07	2.196E 07 1.727E 07 1.359E 07	8.460E 06 6.689E 06 5.296E 06 4.199E 06 3.335E 06
N(02) /CM3	1.200E 11 5.612E 10 1.541E 10 7.823E 09 4.395E 09	2.638E 09 1.660E 09 1.081E 09 7.240E 08 3.457E 08	1.759E 08 9.361E 07 5.151E 07 2.904E 07	9.702E 06 5.707E 06 3.385E 06 2.021E 06 1.214E 06	7.327E 05 4.442E 05 2.703E 05 1.651E 05	6.221E 04 3.837E 04 2.374E 04 1.473E 04 9.164E 03	5.719E 03 3.578E 03 2.245E 03 1.413E 03 8.912E 02
1.6659E 01 N(N2) /CM3	5.800E 11 1.940E 11 8.962E 10 4.861E 10 2.896E 10	1.834E 10 1.213E 10 8.276E 09 5.792E 09 3.005E 09	1.652E 09 9.463E 08 5.589E 08 3.375E 08	1.288E 08 8.088E 07 5.116E 07 3.256E 07 2.083E 07	1.338E 07 8.630E 06 5.586E 06 3.627E 06 2.362E 06	1.543E 06 1.010E 06 6.635E 05 4.368E 05 2.883E 05	1.908E 05 1.265E 05 8.412E 04 5.606E 04 3.745E 04
INT GRAD= MEAN MOL WT	27.46 26.98 26.54 26.13 25.72	25.32 24.92 24.52 24.13	22.59 21.87 21.18 20.53 19.94	19.39 18.89 18.44 18.04	17.37 17.08 16.83 16.59	16.16 15.95 15.74 15.53	15.08 14.83 14.55 14.26 13.93
82E-01, SCALE HT KM	11.4 16.6 20.9 24.5	333 333 335 426 426 6	46.7 50.5 53.9 57.0	62.6 65.1 67.5 69.6 71.6	73.5 75.3 77.0 78.6 80.2	81.8 83.3 84.9 86.6 88.4	90.3 92.5 94.6 97.2
OS(TH)= -2.58 PRESSURE DYNE/CM2	3.802E-02 1.850E-02 1.083E-02 6.968E-03 4.751E-03	3.371E-03 2.464E-03 1.844E-03 1.407E-03	5.4826-04 3.6326-04 2.4756-04 1.7266-04	8.846E-05 6.468E-05 4.784E-05 3.573E-05 2.692E-05	2.044E-05 1.562E-05 1.201E-05 9.291E-06 7.223E-06	5.642E-06 4.428E-06 3.491E-06 2.765E-06 2.200E-06	1.759E-06 1.413E-06 1.140E-06 9.257E-07 7.557E-07
SI 7.000, CO DENSITY GM/CM3	3.536E-11 1.187E-11 5.531E-12 3.037E-12 1.837E-12	1.184E-12 7.989E-13 5.576E-13 4.000E-13 2.196E-13	1.2886-13 7.9526-14 5.1076-14 3.3846-14 2.3016-14	1.598E-14 1.131E-14 8.121E-15 5.912E-15 4.354E-15	3.239E-15 2.432E-15 1.840E-15 1.402E-15	8.280E-16 6.413E-16 4.990E-16 3.898E-16	2.406E-16 1.900E-16 1.505E-16 1.197E-16 9.547E-17
H H	355 506 625 721 800	925 925 976 1021 1097	1156 1201 1235 1260 1278	1291 1300 1307 1312 1315	1318 1320 1321 1323 1323	1324 1325 1325 1325 1326	1326 1326 1326 1326 1326
TIME (IN	120 130 140 150	170 180 190 200 220	240 280 300 320	340 340 380 400	##0 ##0 200 500	540 580 580 600	640 660 680 700 720

6.647E 03 6.52E 03 6.459E 03 6.368E 03 6.278E 03	6.191E 03 6.105E 03 6.021E 03 5.938E 03 5.857E 03	5.778E 03 5.70E 03 5.624E 03 5.549E 03 5.368E 03	5.195E 03 5.030E 03 4.872E 03 4.721E 03 4.577E 03	4.439E 03 4.307E 03 4.180E 03 4.059E 03 3.942E 03	3.831E 03 3.724E 03 3.621E 03 3.522E 03 3.427E 03	3,335E 03 3,248E 03 3,165E 03 5,082E 03 5,004E 03
7.075E 05 6.681E 05 6.311E 05 5.963E 05 5.636E 05	5.329E 05 5.040E 05 4.768E 05 4.513E 05 4.272E 05	4.045E 05 3.832E 05 3.631E 05 3.442E 05	2.644E 05 2.324E 05 2.046E 05 1.804E 05	1.410E 05 1.249E 05 1.108E 05 9.852E 04 8.769E 04	7.817E 04 6.978E 04 6.238E 04 5.584E 04 5.006E 04	4.493E 04 4.058E 04 3.634E 04 3.275E 04 2.954E 04
2.650E 06 2.109E 06 1.681E 06 1.342E 06	8.577E 05 6.871E 05 5.511E 05 4.426E 05 3.559E 05	2.865E 05 2.309E 05 1.863E 05 1.505E 05 8.875E 04	5.270E 04 3.151E 04 1.897E 04 1.149E 04 7.011E 03	4.304E 03 2.659E 03 1.653E 03 1.034E 03 6.502E 02	4.114E 02 2.618E 02 1.675E 02 1.078E 02 6.974E 01	4.535E 01 2.965E 01 1.948E 01 1.287E 01 8.540E 00
5.637E 02 3.575E 02 2.273E 02 1.449E 02 9.262E 01	5.935E 01 3.812E 01 2.454E 01 1.584E 01	6.649E 00 4.323E 00 2.817E 00 1.840E 00 6.409E-01	2.2646-01 8.1106-02 2.9456-02 1.0836-02 4.0396-03	1.525E-03 5.830E-04 2.256E-04 8.839E-05 3.504E-05	1.405E-05 5.700E-06 2.338E-06 9.697E-07 4.065E-07	1.722E-07 7.372E-08 3.188E-08 1.393E-08 6.144E-09
2.508E 04 1.683E 04 1.132E 04 7.632E 03 5.157E 03	3.492E 03 2.370E 03 1.612E 03 1.099E 03 7.504E 02	5.136E 02 3.523E 02 2.421E 02 1.667E 02 6.622E 01	2.662E 01 1.083E 01 4.461E 00 1.859E 00 7.832E-01	3,338E-01 1,438E-01 6,263E-02 2,757E-02 1,226E-02	5.508E-03 2.499E-03 1.145E-03 5.299E-04 2.475E-04	1.167E-04 5.549E-05 2.664E-05 1.290E-05 6.298E-06
13.58 13.20 12.79 12.36	11.42 10.93 10.43 9.93 9.43	8.95 8.48 8.03 7.61	70°50°50°50°50°50°50°50°50°50°50°50°50°50	4.28 4.17 4.09 7.98	3.94 3.91 3.89 3.87	3.83 3.81 3.77 3.77
103.2 106.7 110.8 115.3	126.2 132.6 139.7 147.6 156.2	165.6 175.7 186.6 198.0 228.6	260.5 291.8 320.6 346.0 367.8	386.2 401.7 415.0 426.7 437.1	446.7 455.7 464.3 472.8	489.6 498.1 506.7 515.5 524.4
6.206E-07 5.128E-07 4.267E-07 3.575E-07	2.565E-07 2.197E-07 1.897E-07 1.650E-07	1.277E-07 1.136E-07 1.017E-07 9.167E-08 7.247E-08	5.905E-08 4.926E-08 4.184E-08 3.602E-08	2.742E-08 2.4 16E-08 2.137E-08 1.898E-08 1.690E-08	1.510E-08 1.351E-08 1.212E-08 1.089E-08 9.810E-09	8.850E-09 7.240E-09 6.565E-09 5.963E-09
7.642E-17 6.138E-17 4.948E-17 4.004E-17 3.254E-17	2.655E-17 2.177E-17 1.793E-17 1.485E-17	1.036E-17 8.728E-18 7.403E-18 6.320E-18 4.386E-18	3.178E-18 2.399E-18 1.879E-18 1.519E-18	1.064E-18 9.123E-19 7.914E-19 6.924E-19 6.097E-19	5.395E-19 4.793E-19 4.272E-19 3.818E-19 3.420E-19	3.069E-19 2.760E-19 2.48E-19 2.242E-19 2.026E-19
1327 1327 1327 1327	1327 1327 1327 1327	1327 1327 1327 1327	1327 1327 1327 1327	1327 1327 1327 1327	1327 1327 1327 1327	1327 1327 1327 1327
740 760 780 800 820	840 860 960 920	940 960 980 1000 1050	1100 1150 1250 1250	1350 1400 1450 1500	1600 1650 1700 1750	1850 1900 1950 2000 2050

		₫	₹	ð	ð	† 0			ð	_			_	င်					63					0			03								200	
E S	S = 3 >	#-356E	2.982E	2. \$62E	2.007E	1.770E	1.597E	1.464E	1.359E	1.275E	1.150E	1.064E	1.603E	9.573E	9.223E	8.943E	.711	•5 1t	8.540E	. 184	040.	.906	.780	7.659E	.543	.431	7.523E	.216	5 :	*	٠.	ω	۲.	٠ •	0.545E	•
N(HE)			1.580E 07						5.518E 06					3.028E 06			2.389E 06		2.087E 06			1.732E 06	<u>٠</u>	1.537E 06	o ·	0	1.293E 06					0	0	O	8.292E 05)
N(0)			3.495E 10			-	.084E	360 to	4.235E 09	.385E	.268E	_		8.609E 08	_		-850E	3466*	2.3416 08	.837E	•447E	.142E		7.172E 07		.536E	5.616E 07	-88/E	-309L		• 4 82E	-190E	_	. 702E	6.208E 06	30.0
N(02)			3.615E 10						1.072E 09			350E	319E	5.813E 07	399E	024E	222E	453E	4.583E 06	837E	766E	1.105E 06		4.372E 05			1.117E 05								3.319E 03	
1.6540E 01 N(NZ)			1.9415 11						8.172E 09					6.160E 08			1.563E 08	_	6.611E 07		-	111		8.434E 06		117	2.552E 06	_			-				8 070F ON	
INT GRAD= MEAN		27.46	26.98	26.54	26.13	25.73	25.33	24.94	24.56	24.18	23.44	22.73	22.05	21.41	20.80	20.22	~	?	18.77	٤,	٠.	17.68	17.38	17.12	16.87	16.65	16.44	16.25	16.06	15.87	15.68	₹.	. 2	•	2 8 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	•
SCALE	E E	7. _	16.5	20.8	24.6	28.0	31.2	34.2	37.1	39.9	45.0	49.5	53.5	57.2	60.5	63.5	66.3	68.9	71.3	73.6	75.8	77.8	79-7	81.5	83.2	8 †* 0	86.5	88.	89.7	91.3	92.9	7.46	96.5	5.86	000	70-
S(TH)= -5.00 PRESSURE	DINETURE)2E-0	1.848E-02	31E-0	50E-0	36E-0	. 1E	-37F	1.886E-03	55E-	<u>=</u>	-3/1	54E-	2.811E-04	-31	19E-	1.065E-04	196	5.954E-05	18	57E-	2.664E-05	2.066E-05	1.612E-05	1.265E-05	9.968E-06	7.893E-06	6-277E-06	5.012E-06	4-018E-06	3.233E-06	2.613E-06	2.119E-06	1.726E-06	1.412E-U0	2001
= 8.000, CO: DENSITY		3.536E-11	1.188E-11	5.527E-12	3.025E-12	1.822E-12			5.496E-13			1.319E-13	8.324E-14	5.465E-14	3.700E-14	2.567E-14	1.817E-14	1.308E-14	9.557E-15	7.069E-15	5.287E-15	3.992E-15					1.095E-15	8-60 IE-16	6.785E-16	5.374E-16	4.272E-16	3.408E-16	.727E-1	- 190E-1	1.703E-10	
HOURS)	۷.	355	505	625	723	808	883	952	1014	1069	1162	1233	1286	1324	1353	1373	1388	1398	90 † 1	1412	1416	14 19	1421	1423	1424	1425	1425	1426	14.26	1427	1427	1427	1428	1428	8241	1
TIME (IN	E Z	120	130	0 1 C	150	160	170	180	190	200	220	240	260	280	300	320	340	360	380	004	420	044	1460	7.80	200	520	240	260	580	900	620	049	099	089	720) -

6.370E 03 6.285E 03 6.202E 03 6.121E 03 6.041E 03	5.963E 03 5.886E 03 5.810E 03 5.736E 03 5.664E 03	5.592E 03 5.522E 03 5.454E 03 5.386E 03 5.223E 03	5.067E 03 4.917E 03 4.773E 03 4.636E 03 4.504E 03	4.257E 03 4.257E 03 4.140E 03 4.028E 03 3.921E 03	3.818E 03 3.718E 03 3.623E 03 5.531E 03 5.442E 03	3.357e 03 3.275e 03 3.196e 03 3.119e 03 3.046e 03
7.447E 05 7.060E 05 6.696E 05 6.352E 05 6.028E 05	5.723E US 5.434E US 5.161E US 4.904E US 4.660E US	4.430E 05 4.213E 05 4.007E 05 3.813E 05	2.985E 05 2.647E 05 2.352E 05 2.093E 05 1.865E 05	1.664E 05 1.487E 05 1.331E 05 1.193E 05 1.071E 05	9.623E 04 8.660E 04 7.804E 04 7.041E 04 6.361E 04	5.754E 04 5.211E 04 4.724E 04 4.289E 04 3.897E 04
4.048E 06 3.275E 06 2.653E 06 2.151E 06 1.747E 06	1.420E 06 1.156E 06 9.416E 05 7.680E 05 6.272E 05	5.128E 05 4.197E 05 5.439E 05 2.820E 05 1.727E 05	1.064E 05 6.599E 04 4.118E 04 2.586E 04 1.634E 04	1.039E 04 6.639E 03 4.269E 03 2.760E 03 1.795E 03	1.173E 03 7.709E 02 5.092E 02 3.381E 02 2.256E 02	1.513E 02 1.019E 02 6.902E 01 4.695E 01 3.208E 01
1.414E 03 9.264E 02 6.083E 02 4.004E 02 2.642E 02	1.7476 02 1.158E 02 7.695E 01 5.124E 01 3.420E 01	2.288E 01 1.533E 01 1.030E 01 6.937E 00 2.604E 00	9.907E-01 3.818E-01 1.490E-01 5.885E-02 2.353E-02	9.523E-03 3.899E-03 1.614E-03 6.760E-04 2.862E-04	1.225E-04 5.298E-05 2.315E-05 1.022E-05 4.559E-06	2.053E-06 9.33TE-07 4.286E-07 1.986E-07 9.286E-08
5.560E 04 3.839E 04 2.656E 04 1.842E 04	8.908E 03 6.215E 03 4.344E 03 3.043E 03 2.135E 03	1.502E 03 1.058E 03 7.468E 02 5.281E 02 2.240E 02	9.607E 01 4.168E 01 1.828E 01 8.106E 00 3.633E 00	1.64SE 00 7.52SE-01 3.477E-01 1.622E-01 7.643E-02	3.635E-02 1.745E-02 8.451E-03 4.131E-03 2.037E-03	1.013E-03 5.079E-04 2.569E-04 1.310E-04 6.730E-05
14.31 14.02 13.70 13.36	12.61 12.21 11.78 11.34	10.44 9.98 9.52 9.08 8.03	7.11 6.34 5.73 5.26 4.91	7 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	4.05 4.00 3.97 3.94 3.94	3.87 3.83 3.83 3.83
105.4 108.3 111.4 114.8	123.0 127.8 133.2 139.1	152.9 160.8 169.4 178.7 204.8	234.4 266.2 298.5 329.5 358.1	383.5 405.7 424.8 441.3 455.6	468.3 479.8 490.3 500.2	518.9 527.9 536.9 545.8 554.9
9.572E-07 7.938E-07 6.616E-07 5.543E-07	3.958E-07 3.374E-07 2.895E-07 2.499E-07 2.171E-07	1.899E-07 1.671E-07 1.481E-07 1.320E-07	8.087E-08 6.620E-08 5.545E-08 4.728E-08	3.5736-08 3.1486-08 2.7916-08 2.4876-08	1.996E-08 1.796E-08 1.620E-08 1.465E-08	1.2046-08 1.0946-08 9.9616-09 9.0826-09 8.2936-09
1.153E-16 9.368E-17 7.632E-17 6.236E-17 5.111E-17	4.203E-17 3.467E-17 2.871E-17 2.386E-17 1.991E-17	1.668E-17 1.404E-17 1.187E-17 1.008E-17 6.864E-18	4.837E-18 3.534E-18 2.675E-18 2.094E-18	1.395E-18 1.177E-18 1.010E-18 8.771E-19 7.695E-19	6.804E-19 6.052E-19 5.409E-19 4.852E-19 4.367E-19	3.940E-19 3.562E-19 3.228E-19 2.929E-19 2.663E-19
1428 1428 1429 1429	1429 1429 1429 1429	14.29 14.29 14.29 14.29	1429 1429 1429 1429	14.29 14.29 14.29 14.29	1429 1429 1429 1429	1429 1429 1429 1429
740 760 780 800 820	840 860 880 900	940 960 980 1000 1050	1100 1150 1200 1250	1350 1400 1450 1500 1550	1600 1650 1700 1750	1850 1900 1950 2000 2050

N(H) /CM3	4.356E 04 2.985E 04 2.359E 04 1.989E 04	1.551E 04 1.410E 04 1.301E 04 1.216E 04 1.092E 04	1.009E 04 9.501E 03 9.072E 03 8.743E 03	8.269E 03 8.087E 03 7.928E 03 7.785E 03	7.533E 03 7.418E 03 7.309E 03 7.204E 03	7.005E 03 6.910E 03 6.817E 03 6.726E 03 6.638E 03	6.551E 03 6.466E 03 6.383E 03 6.302E 03
N(HE) /CM3	2.500E 07 1.582E 07 1.176E 07 9.431E 06 7.881E 06	6.771E 06 5.942E 06 5.306E 06 4.807E 06 4.079E 06	3.577E 06 3.207E 06 2.921E 06 2.689E 06 2.495E 06	2.327E 06 2.180E 06 2.048E 06 1.928E 06 1.818E 06	1.716E 06 1.62E 06 1.534E 06 1.452E 06 1.375E 06	1.303E 06 1.235E 06 1.171E 06 1.111E 06 1.055E 06	1.001E 06 9.509E 05 9.033E 05 8.584E 05 8.160E 05
N(0) /CM3	7.600E 10 3.498E 10 2.045E 10 1.343E 10	6.939E 09 5.288E 09 4.145E 09 3.323E 09 2.251E 09	1.603E 09 1.182E 09 8.916E 08 6.842E 08 5.314E 08	4.164E 08 3.285E 08 2.604E 08 2.073E 08	1.325E 08 1.064E 08 8.553E 07 6.890E 07	4.492E 07 4.635E 07 2.946E 07 2.391E 07	1.580E 07 1.287E 07 1.050E 07 8.571E 06 7.007E 06
N(02) /CM3	1.200E 11 3.617E 10 1.536E 10 7.731E 09 4.310E 09	2.579E 09 1.629E 09 1.073E 09 7.318E 08 3.673E 08	1.984E 08 1.126E 08 6.617E 07 3.985E 07 2.443E 07	1.518E 07 9.529E 06 6.029E 06 3.839E 06 2.457E 06	1.580E 06 1.020E 06 6.609E 05 4.296E 05 2.801E 05	1.832E 05 1.201E 05 7.896E 04 5.205E 04 3.440E 04	2.2796 04 1.5136 04 1.0076 04 6.7236 03 4.4966 03
1.6432E 01 N(N2) /CM3	5.800E 11 1.942E 11 8.933E 10 4.804E 10 2.837E 10	1.787E 10 1.183E 10 8.139E 09 5.777E 09: 3.124E 09	1.808E 09 1.095E 09 6.849E 08 4.381E 08 2.849E 08	1.246E 08 1.246E 08 8.340E 07 5.614E 07	2.579E 07 1.758E 07 1.202E 07 8.240E 06 5.665E 06	3.905E 06 2.698E 06 1.869E 06 1.297E 06 9.026E 05	6.294E 05 4.398E 05 3.080E 05 2.161E 05 1.519E 05
INT GRAD≡ MEAN MOL WT	27.46 26.98 26.54 26.13 25.73	25.35 24.97 24.61 24.25 23.56	22.89 22.25 21.64 21.05 20.50	19.99 19.51 19.07 18.67	17.97 17.66 17.39 17.14 16.91	16.70 16.50 16.32 16.14 15.96	15.79 15.61 15.23 15.23
SCALE HT KM	11.4 16.5 20.9 24.8 28.5	32.1 35.5 38.8 41.8	52.1 56.3 60.0 63.4	69.4 72.1 74.6 77.0 79.3	81.4 83.4 85.3 87.1 88.9	90.6 92.2 93.9 95.5	98.8 100.5 102.3 104.2
COS(TH) = -7.07 PRESSURE DYNE/CM2	3.802E-02 1.847E-02 1.081E-02 6.970E-03 4.788E-03	3.442E-03 2.560E-03 1.955E-03 1.525E-03 9.737E-04	6.512E-04 4.502E-04 3.193E-04 2.309E-04 1.698E-04	1.265E-04 9.535E-05 7.260E-05 5.577E-05 4.317E-05	3.366E-05 2.640E-05 2.083E-05 1.652E-05	1.053E-05 8.461E-06 6.824E-06 5.525E-06 4.489E-06	3.660E-06 2.994E-06 2.458E-06 2.025E-06 1.675E-06
# 9.000, C DENSITY GM/CM3	3.5366-11 1.1886-11 5.5146-12 3.0026-12 1.7996-12	1.153E-12 7.773E-13 5.457E-13 3.959E-13 2.247E-13	1.373E-13 8.835E-14 5.910E-14 4.071E-14 2.870E-14	2.062E-14 1.505E-14 1.114E-14 8.34.1E-15 6.312E-15	4,820E-15 3,712E-15 2,879E-15 2,248E-15 1,766E-15	1.395E-15 1.107E-15 8.826E-16 7.064E-16 5.675E-16	4.575E-16 3.700E-16 3.001E-16 2.441E-16
N HOURS)	355 504 626 730 824	910 989 1060 1124 1228	1306 1364 1406 1437	1475 1486 1495 1501	1509 1511 1513 1515 1516	1516 1517 1518 1518 1518	1519 1519 1519 1520
TIME (II ALT KM	120 130 140 150	170 180 190 200 220	240 260 280 300 320	340 360 380 400	## ## ## ## ## ## ## ## ## ## ## ## ##	540 560 580 600	640 660 700 720

6.143E 03 6.067E 03 5.991E 03 5.917E 03 5.844E 03	5.773E 03 5.703E 03 5.634E 03 5.567E 03 5.501E 03	5.436E 03 5.372E 03 5.309E 03 5.247E 03 5.097E 03	4.954E 03 4.816E 03 4.684E 03 4.557E 03	4.206E 03 4.206E 03 4.098E 03 3.995E 03	3.797E 03 3.704E 05 3.614E 05 3.528E 05 3.445E 05	3.365E 03 3.287E 03 3.212E 03 3.140E 03
7.759E 05 7.380E 05 7.021E 05 6.682E 05	6.057E 05 5.770E 05 5.497E 05 5.239E 05	4.762E 05 4.542E 05 4.333E 05 4.135E 05 3.683E 05	3.285E 05 2.935E 05 2.626E 05 2.333E 05 2.111E 05	1.897E 05 1.707E 05 1.538E 05 1.388E 05 1.254E 05	1.134E 05 1.027E 05 9.311E 04 8.453E 04 7.684E 04	6.992E 04 6.370E 04 5.810E 04 5.305E 04 4.849E 04
5.735E 06 4.699E 06 3.855E 06 3.166E 06 2.603E 06	2.142E 06 1.765E 06 1.456E 06 1.202E 06 9.938E 05	8.224E 05 6.813E 05 5.649E 05 4.689E 05 2.957E 05	1.876E 05 1.197E 05 7.687E 04 4.964E 04 3.224E 04	2.106E 04 1.383E 04 9.132E 03 6.061E 03	2.712E 03 1.828E 03 1.238E 03 8.424E 02 5.759E 02	3.956E 02 2.730E 02 1.892E 02 1.317E 02 9.209E 01
3.015E 03 2.026L 03 1.364E 03 9.208E 02 6.229E 02	4.224E 02 2.870E 02 1.954E 02 1.333E 02 9.118E 01	6.248E 01 4.291E 01 2.952E 01 2.036E 01 8.107E 00	3.269E 00 1.334E 00 5.508E-01 2.301E-01 9.722E-02	4.154E-02 1.794E-02 7.835E-03 3.457E-03 1.541E-03	6.9426-04 3.1586-04 1.4516-04 6.7276-05 3.1496-05	1.488E-05 7.095E-06 3.413E-06 1.656E-06 8.107E-07
1.071E 05 7.558E 04 5.346E 04 3.789E 04 2.691E 04	1.915E 04 1.365E 04 9.750E 03 6.977E 03 5.002E 03	3.592E 03 2.585E 03 1.863E 03 1.345E 03 6.007E 02	2.712E 02 1.237E 02 5.701E 01 2.655E 01 1.248E 01	5.929E 00 2.843E 00 1.376E 00 6.721E-01 3.313E-01	1.648E-01 8.266E-02 4.183E-02 2.134E-02 1.098E-02	5.694E-03 2.977E-03 1.568E-03 8.326E-04 4.454E-04
14.81 14.58 14.33 14.06	13.46 13.13 12.78 12.41	11.63 11.22 10.80 10.37 9.32	8.33 7.43 6.67 6.04 5.53	5.14 4.61 4.43 4.30	# 12 # 12 # 06 3.98	3.95 3.93 3.90 3.88
108.4 110.8 113.3 116.2	122.7 126.5 130.7 135.3	146.0 152.2 159.0 166.4	212.9 241.7 273.0 305.6 337.8	368.4 396.5 421.7 443.9	480.4 495.5 509.0 521.3 532.6	543.3 553.5 563.3 573.0 582.5
1.390E-06 1.158E-06 9.685E-07 8.136E-07	5.818E-07 4.955E-07 4.241E-07 3.648E-07	2.744E-07 2.399E-07 2.110E-07 1.866E-07	1.094E-07 8.775E-08 7.223E-08 6.075E-08 5.200E-08	4.513E-08 3.960E-08 3.505E-08 3.123E-08 2.797E-08	2.516E-08 2.271E-08 2.056E-08 1.865E-08	1.546E-08 1.411E-08 1.290E-08 1.182E-08
1.629E-16 1.336E-16 1.098E-16 9.049E-17 7.477E-17	6.195E-17 5.147E-17 4.287E-17 3.582E-17	2.524E-17 2.129E-17 1.802E-17 1.531E-17	7.205E-18 5.159E-18 3.809E-18 2.901E-18	1.835E-18 1.515E-18 1.277E-18 1.095E-18 9.514E-19	8.359E-19 7.407E-19 6.610E-19 5.930E-19	4.8326-19 4.3836-19 3.9856-19 3.6316-19
1520 1520 1520 1520	1520 1520 1520 1520	1520 1521 1521 1521 1521	1521 1521 1521 1521 1521	1521 1521 1521 1521 1521	1521 1521 1521 1521 1521	1521 1521 1521 1521 1521
740 760 780 800 820	840 860 980 920	940 960 980 1000	1100 1150 1200 1250	1350 1400 1450 1500	1600 1650 1700 1750 1800	1850 1900 1950 2000 2050

N(H) /CM3	4.356E 04 2.986E 04 2.547E 04 1.959E 04	1.501E 04 1.358E 04 1.249E 04 1.165E 04	9.647E 03 9.091E 03 8.684E 03 8.374E 03	7.928E 03 7.758E 03 7.609E 03 7.476E 03	7.242E 03 7.136E 03 7.035E 03 6.938E 03 6.845E 05	6.755E 03 6.667E 03 6.581E 03 6.498E 03 6.416E 03	6.336E 03 6.258E 03 6.182E 03 6.107E 03
N(HE) /CM3	2.500E 07 1.582E 07 1.170E 07 9.297E 06 7.699E 06	6.571E 06 5.744E 06 5.120E 06 4.635E 06 3.938E 06	3.461E 06 3.111E 06 2.841E 06 2.623E 06 2.440E 06	2.282E 06 2.143E 06 2.019E 06 1.905E 06	1.705E 06 1.616E 06 1.532E 06 1.454E 06 1.381E 06	1.312E 06 1.246E 06 1.185E 06 1.127E 06 1.072E 06	1.021E 06 9.718E 05 9.255E 05 8.817E 05
N(0) /CM3	7.600E 10 3.498E 10 2.036E 10 1.327E 10 9.266E 09	6.803E 09 5.190E 09 4.082E 09 3.288E 09 2.253E 09	1.624E 09 1.211E 09 9.245E 08 7.176E 08	4.466E 08 3.562E 08 2.855E 08 2.297E 08	1.500E 08 1.217E 08 9.889E 07 8.050E 07 6.564E 07	5.360E 07 4.383E 07 3.589E 07 2.942E 07 2.415E 07	1.985E 07 1.633E 07 1.346E 07 1.110E 07 9.163E 06
N(02) /CM3	1.200E 11 3.616E 10 1.529E 10 7.660E 09	2.563E 09 1.631E 09 1.086E 09 7.492E 08 3.855E 08	2.1346 08 1.2416 08 7.4696 07 4.6036 07 2.887E 07	1.834E 07 1.177E 07 7.610E 06 4.952E 06 3.239E 06	2.128E 06 1.403E 06 9.286E 05 6.165E 05 4.105E 05	2.741E 05 1.835E 05 1.232E 05 8.287E 04 5.590E 04	3.7796 04 2.5616 04 1.7406 04 1.1846 04 8.0826 03
1.6338E 01 N(N2) /CM3	5.800E 11 1.942E 11 8.893E 10 4.757E 10 2.803E 10	1.770E 10 1.179E 10 8.180E 09 5.865E 09 3.240E 09	1.916E 09 1.186E 09 7.569E 08 4.941E 08 3.277E 08	2.2006 08 1.4906 08 1.0166 08 6.9736 07	3.326E 07 2.509E 07 1.608E 07 1.123E 07	5.523E 06 3.886E 06 2.741E 06 1.937E 06	9.741E 05 6.928E 05 4.938E 05 3.526E 05 2.523E 05
INT GRAD= MEAN MOL WT	27.46 26.98 26.54 26.13 25.75	25.37 25.01 24.66 24.33 23.67	23.04 22.43 21.84 21.28 20.75	20.25 19.78 19.34 18.94	18.23 17.92 17.64 17.38 17.14	16.93 16.73 16.54 16.36	16.02 15.86 15.69 15.52
02E-01. SCALE HT KM	11.4 16.5 21.0 25.2 29.2	33.2 36.4 40.3 43.6	54.3 58.6 62.5 65.9	72.0 74.7 77.3 79.8 82.1	84.3 86.5 88.5 90.4	94.0 95.7 97.4 99.1	102.4 104.1 105.8 107.6
IS(TH)= -8.6602 PRESSURE DYNE/CM2	3.802E-02 1.846E-02 1.081E-02 7.003E-03	3.516E-03 2.642E-03 2.039E-03 1.607E-03	7.105E-04 4.987E-04 3.584E-04 2.625E-04 1.952E-04	1.470E-04 1.119E-04 8.603E-05 6.670E-05 5.210E-05	4.097E-05 3.242E-05 2.579E-05 2.062E-05 1.657E-05	1.337E-05 1.083E-05 8.801E-06 7.180E-06 5.877E-06	4.8276-06 3.9766-06 3.2866-06 2.7256-06
I= 10.000, COS(TH): DENSITY PRE GM/CM3 DYN	3.536E-11 1.188E-11 5.489E-12 2.972E-12 1.776E-12	1.140E-12 7.728E-13 5.467E-13 4.000E-13 2.311E-13	1.436E-13 9.395E-14 6.378E-14 4.453E-14 3.178E-14	2.310E-14 1.704E-14 1.274E-14 9.628E-15 7.350E-15	5.662E-15 4.396E-15 3.438E-15 2.706E-15	1.706E-15 1.365E-15 1.097E-15 8.847E-16 7.164E-16	5.821E-16 4.746E-16 3.880E-16 3.181E-16 2.615E-16
HOURS)= TEMP	355 504 629 741 845	941 1029 1107 4175	1370 1432 1476 1509	1550 1562 1571 1578 1583	1587 1589 1591 1593 1594	1595 1596 1597 1597	1598 1598 1599 1599
TIME (IN ALT KM	120 130 140 150	170 180 190 200 220	240 260 280 300 320	340 360 380 400 420	200 200 200 200 200	540 560 580 600	640 660 700 720

03 03 03	03 03 03 03	03 03 03 03	03 03 03 03	03 03 03 03	03 03 03 03	03 03 03 03
5.961E 5.890E 5.820E 5.751E 5.684E	5.618E 5.554E 5.490E 5.427E 5.366E	5.306E 5.246E 5.188E 5.131E 4.991E	4.858E 4.729E 4.606E 4.487E 4.373E	4.263E 4.158E 4.056E 3.958E 3.864E	3.773E 3.685E 3.400E 3.518E 3.439E	3.363E 3.290E 3.218E 3.150E 3.083E
05 05 05 05	05 05 05 05	00 00 00 00 00 00 00	005	00 00 00 00 00 00 00 00 00 00 00 00 00	5000 5000 5000 5000	###### 00000
.009E .637E .284E .949E	330E 044E 772E 514E	.036E .815E .604E .404E	.539E .179E .860E .577E	2.100E 1.900E 1.720E 1.560E 1.416E	1.288E 1.172E 1.068E 9.741E 8.896E	3.1336 .4446 .8206 .2556
8 0 0	99000	ហំនាំភាំភាំកាំ	พัพิณีณ์ณั	2		8,400,4
п п п п п п п 0 0 0 0 0 0 0 0 0 0 0 0 0	п п п п п п п п п п п п п п п п п п п	E 06 E 05 E 05	E 055	00 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	E 03 E 03 E 03	E 02 E 02 E 02 E 02
7.574E 6.268E 5.192E 4.306E	2.9716 2.4726 2.0586 1.7166	1.196E 1.000E 8.370E 7.013E 4.524E	2.9368 1.9168 1.2588 8.2998 5.5078	3.674 2.464 1.660 1.125 7.657	5.2386 3.6006 2.4866 1.7246	8.4076 5.9096 4.1716 2.9566 2.1046
03 03 03 03	02 02 02 02	02 01 01	000000	025 025 005 005 005	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
5.527E 5.788E 5.601E 1.791E	3.536E .912E .103E .854E	388E 714E 809E 783E 994E	. 409E . 587E . 548E . 753E-	3276 9776 7196 2506 8006	2.718E-03 1.285E-03 6.137E-04 2.957E-04 1.437E-04	7.049E-05 3.487E-05 1.739E-05 8.749E-06 4.437E-06
	8 5 4 6 -	-004-	20 - W B	-22-2	2.6.2.	8 - 3 - 4
\$0 \$0 \$0	7 7 7 7 8 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	E 03	E 02 E 02 E 01	E 000	E-01 E-01 E-02 E-02	E-02 E-02 E-03 E-03
1.809E 1.299E 9.350E 6.741E 4.869E	3.524E 2.554E 1.855E 1.350E 9.838E	7.1836 5.2536 3.8496 2.8246	6. 1646 2.9238 1.4006 6.7728 3.3066	1.629E 8.103E 4.066E 2.058E 1.051E	5.4096 2.8086 1.4706 7.7546	2.2096 1.1936 6.4876 3.5546
0-04	W 2 6	F 25 45 GT	96-96	320-	50-64	2-96-
15.16 14.96 14.75 14.53	14.04 13.77 13.48 13.17 12.84	12.50 12.14 11.77 11.39	9.42 8.48 7.62 6.88	5.73 5.32 5.00 4.74 4.55	4.19 4.19 4.12	4.02 3.99 3.96 3.93
40800	W2 + 9 B	5-5-4-4-00 	00 mm0	9 4 7 5 0	8-299	75553
113	125 126 130 134 138	142 147 153 159 176	198. 222. 221. 251. 382.	347 379 409 436 436	502 502 519 534 548	561 573 584 595 605
E-06 E-06 E-06 E-06	E-07 E-07 E-07 E-07	E-07 E-07 E-07 E-07	E-07 E-07 E-08 E-08	1 0 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	00 00 00 00 00 00 00 00 00 00 00 00 00	7E-08 5E-08 7E-08
1.8918 1.5838 1.3298 1.1208 9.4788	8.0486 6.8606 5.8726 5.0486 4.3596	3.7816 3.2956 2.8856 2.5386	1.4426 1.1366 9.1976 7.6236 6.4466	5.542E- 4.830E- 4.255E- 3.780E- 3.382E-	3.042E-(2.748E-(2.492E-(2.266E-(1.889E 1.729E 1.586E 1.457E
	~~~~			88888		00000
2.155E-16 1.781E-16 1.475E-16 1.224E-16	8.495E-1 7.101E-1 5.950E-1 4.998E-1	3.5536-17 3.008E-17 2.553E-17 2.174E-17 1.474E-17	1.021E-17 7.242E-18 5.270E-18 3.940E-18 3.027E-18	2.388E-1 1.932E-1 1.598E-1 1.348E-1	1.006E-18 8.847E-19 7.854E-19 7.024E-19 6.319E-19	5.713E-19 5.185E-19 4.721E-19 4.310E-19 3.944E-19
2-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	8	3.5	3.52	2.3	8.8 7.8 6.3	5.7 7.3 7.9
1599 1599 1599 1599 1600	1600 1600 1600 1600	1600 1600 1600 1600	1600 1600 1600 1600	1600 1600 1600 1600	1600 1600 1600 1600	1600 1600 1600 1600 1600
740 760 780 800 820	840 860 980 920	940 960 980 1000	1100 1150 1200 1250 1300	1350 1400 1450 1500	1600 1650 1700 1750	000 000 200
£ £ £ 8 8	ထ်ထိထိတ်ပြ	******	11222	N 4 4 2 C	51 71 81	. 1850 1900 1950 2000 2050

40							
N(H) /CM3	4.356E 04 2.984E 04 2.328E 04 1.924E 04 3.650E 04	1.456E 04 1.313E 04 1.206E 04 1.124E 04 1.408E 04	9.312E 03 8.780E 03 8.392E 03 8.096E 03 7.862E 03	7.670E 03 7.508E 03 7.367E 03 7.241E 03 7.126E 03	7.019E 03 6.019E 03 6.623E 03 6.732E 03 6.645E 03	6.560E 03 6.477E 03 6.397E 03 6.319E 03 6.242E 03	6.167E 03 6.094E 03 6.022E 03 5.952E 03 5.882E 03
N(HE) /CM3	2.500E 07 1.581E 07 1.161E 07 9.140E 06 7.516E 06	6.390E 06 5.576E 06 4.969E 06 4.501E 06 3.831E 06	3.375E 06 3.041E 06 2.783E 06 2.575E 06 2.400E 06	2.250E 06 2.117E 06 1.997E 06 1.889E 06	1.697E 06 1.611E 06 1.531E 06 1.455E 06 1.384E 06	1.318E 06 1.255E 06 1.195E 06 1.139E 06 1.086E 06	1.035E 06 9.878E 05 9.425E 05 8.996E 05
N(0) /CM3	7.600E 10 3.495E 10 2.021E 10 1.309E 10 9.113E 09	6.693E 09 5.120E 09 4.043E 09 3.273E 09 2.265E 09	1.649E 09 1.241E 09 9.562E 08 7.487E 08	4.758E 08 5.810E 08 3.079E 08 2.497E 08 2.032E 08	1.658E 08 1.355E 08 1.110E 08 9.112E 07 7.489E 07	6.164E 07 5.081E 07 4.193E 07 3.465E 07 2.867E 07	2.375E 07 1.969E 07 1.635E 07 1.359E 07
N(02) /CMs	1.200E 11 3.613E 10 1.520E 10 7.592E 09 4.236E 09	2.561E 09 1.644E 09 1.106E 09 7.707E 08	2.287E 08 1.355E 08 8.303E 07 5.207E 07	2.146E 07 1.400E 07 9.205E 06 6.089E 06	2.703E 06 1.811E 06 1.218E 06 8.219E 05 5.561E 05	3.773E 05 2.566E 05 1.750E 05 1.196E 05 8.196E 04	5.629E 04 3.875E 04 2.673E 04 1.848E 04
1.6269E 01 N(N2) /CM3	5.800E 11 1.940E 11 8.838E 10 4.709E 10 2.776E 10	1.762E 10 1.182E 10 8.271E 09 5.983E 09 3.366E 09	2.025E 09 1.274E 09 8.264E 08 5.478E 08 3.688E 08	2.512E 08 1.727E 08 1.195E 08 8.315E 07 5.814E 07	4.080E 07 2.874E 07 2.030E 07 1.438E 07	7.2706 06 5.187E 06 3.709E 06 2.658E 06 1.909E 06	1.374E 06 9.905E 05 7.155E 05 5.179E 05 3.756E 05
INT GRAD= MEAN MOL WT	27.46 26.98 26.94 26.14 25.76	25.40 25.06 24.72 24.40 23.77	23.17 22.58 22.02 21.48 20.96	20.47 20.01 19.57 19.17 18.80	18.45 18.14 17.85 17.58	17.12 16.92 16.72 16.54	16.21 16.05 15.89 15.73
93E-01, SCALE HT KM	11.4 16.5 21.2 25.6 30.0	34.2 38.1 41.8 45.1	56.1 60.5 64.4 67.9	74.1 76.9 79.5 82.0	86.7 88.9 91.0 93.0	96.8 98.6 100.4 102.1	105.4 107.1 108.8 110.6
S(TH)= -9.65 PRESSURE DYNE/CM2	3.802E-02 1.846E-02 1.083E-02 7.056E-03 4.922E-03	3.604E-03 2.732E-03 2.127E-03 1.690E-03	7.679E-04 5.451E-04 3.958E-04 2.925E-04 2.194E-04	1.666E-04 1.278E-04 9.894E-05 7.724E-05	4.809E-05 3.830E-05 3.066E-05 2.467E-05 1.994E-05	1.619E-05 1.319E-05 1.079E-05 8.855E-06 7.291E-06	6.022E-06 4.989E-06 4.145E-06 3.454E-06 2.887E-06
= 11.000, COS(TH) DENSITY PRE GM/CM3 DYN	3.536E-11 1.187E-11 5.455E-12 2.941E-12 1.758E-12	1.133E-12 7.730E-13 5.509E-13 4.062E-13 2.383E-13	1.502E-13 9.948E-14 6.829E-14 4.817E-14 3.471E-14	2.544E-14 1.892E-14 1.425E-14 1.085E-14 8.336E-15	6.462E-15 5.049E-15 3.973E-15 3.146E-15 2.506E-15	2.0076-15 1.615E-15 1.305E-15 1.059E-15 8.629E-16	7.054E-16 5.785E-16 4.758E-16 3.925E-16 3.246E-16
HOURS)= TEMP	355 505 634 754 868	972 1065 1148 1221 1338	1425 1488 1535 1569	1612 1625 1635 1642 1647	1652 1655 1657 1659 1660	1661 1662 1663 1664 1664	1665 1665 1665 1665
TIME (IN ALT KM	120 130 140 150	170 180 190 200 220	240 260 280 300 320	340 340 380 400 420	## ##0 \$20 \$20	540 580 600 620	640 660 680 700 720

5.815E 03 5.748E 03 5.683E 03 5.619E 03			. 777E . 656E . 540E . 27E . 319E . 115E . 925E	111 1 111 11	3.357E 03 3.287E 03 3.218E 03 3.152E 03 5.088E 03
8.203E 05 7.837E 05 7.488E 05 7.158E 05	44E 60E 90E 33E	25.5E 03.3E 82.2E 62.0E	746E 380E 762E 762E 502E 270E 974E 706E		9.1336 04 8.3886 04 7.7136 04 7.0996 04 6.5406 04
9.416E 06 7.852E 06 6.554E 06 5.476E 06	3.835E 06 3.214E 06 2.696E 06 2.264E 06 1.903E 06		159E 761E 843E 237E 346E 659E 641E 641E		1.508E 03 1.075E 03 7.693E 02 5.529E 02 3.989E 02
8.890E 03 6.186E 03 4.313E 03 3.014E 03 2.110E 03	1.480E 03 1.040E 03 7.328E 02 5.171E 02	00000	1.756E 01 7.753E 00 3.460E 00 1.561E 00 7.114E-01 1.523E-01 7.154E-02 3.392E-02	7.845E-03 3.824E-03 1.881E-03 9.331E-04 4.670E-04	2.35/E=04 1.199E=04 6.152E=05 3.181E=05 1.658E=05
2.729E 05 1.986E 05 1.448E 05 1.058E 05 7.743E 04	5.677E 04 4.169E 04 3.067E 04 2.260E 04 1.668E 04	1.234E 04 9.137E 03 6.778E 05 5.037E 03	1.169E 03 5.711E 02 2.818E 02 1.403E 02 7.052E 01 3.576E 01 1.829E 01 9.435E 00 4.908E 00	1.362E 00 7.257E-01 3.899E-01 2.110E-01 1.151E-01	3.500E-02 3.500E-02 1.951E-02 1.095E-02 6.189E-03
15.41 15.23 15.05 14.86	14.44 14.21 13.96 13.70	13.12 12.81 12.48 12.14	10.31 9.38 8.48 7.67 6.95 6.34 5.84 5.84 5.84	4.63 4.47 4.34 4.25 4.17	4.02 3.99 3.99
114.2 116.2 118.3 120.5	125.4 128.2 131.1 134.4	141.9 146.1 150.7 155.8	188.5 210.1 235.2 263.7 294.7 327.3 360.3 423.4 451.9	477.9 501.2 522.2 540.9 557.7	587.0 600.0 612.2 623.8
2.420E-06 2.034E-06 1.715E-06 1.450E-06	1.047E-06 8.943E-07 7.665E-07 6.593E-07 5.692E-07	4.934E-07 4.294E-07 3.752E-07 3.293E-07 2.422E-07	1.832E-07 1.425E-07 1.138E-07 9.306E-08 7.778E-08 6.621E-08 5.724E-08 5.012E-08 4.434E-08 3.955E-08	3.552E-08 3.207E-08 2.909E-08 2.418E-08 2.417E-08	2.030E-08 1.866E-08 1.718E-08
2.237E-16 2.237E-16 1.863E-16 1.555E-16 1.301E-16	1.091E-16 9.168E-17 7.720E-17 6.515E-17 5.510E-17	4.670E-17 3.968E-17 3.379E-17 2.885E-17 1.965E-17	1.363E-17 9.638E-18 6.964E-18 5.150E-18 3.030E-18 2.411E-18 1.962E-18 1.630E-18	1.187E-18 1.034E-18 9.117E-19 8.111E-19 7.271E-19	5.9446-19 5.4116-19 4.9426-19 4.5266-19
1666 1666 1666 1666	1667 1667 1667 1667	1667 1667 1667 1667 1667	1667 1667 1667 1667 1667 1667 1667	1667 1667 1667 1667 1667	1667 1667 1667
740 760 780 800 820	840 860 880 900	940 960 980 1000 1050	1100 1150 1200 1250 1350 1350 1400 1450 1500	1600 1650 1700 1750 1800	1900 1950 2000 2050

N(H) /CM3	4.356E 04 2.978E 04 2.305E 04 1.890E 04	1.418E 04 1.278E 04 1.173E 04 1.093E 04 9.810E 03	9.073E 03 8.560E 03 8.185E 03 7.900E 03	7.488E 03 7.51E 05 7.194E 03 7.072E 03 6.961E 03	6.858E 03 6.762E 03 6.670E 03 6.583E 03 6.498E 03	6.417E 03 6.558E 05 6.262E 03 6.187E 05	6.042E 03 5.972E 03 5.904E 03 5.837E 03 5.771E 03
N(HE) /CM3	2.500E 07 1.578E 07 1.150E 07 8.988E 06 7.358E 06	6.243E 06 5.447E 06 4.856E 06 4.402E 06 3.755E 06	3.315E 06 2.993E 06 2.744E 06 2.543E 06 2.374E 06	2.228E 06 2.099E 06 1.983E 06 1.878E 06 1.781E 06	1.691E 06 1.608E 06 1.530E 06 1.456E 06 1.387E 06	1.322E 06 1.261E 06 1.203E 06 1.148E 06	1.046E 06 9.994E 05 9.549E 05 9.127E 05 8.727E 05
N(0) /CM3	7.600E 10 3.488E 10 2.005E 10 1.292E 10 8.990E 09	6.614E 09 5.077E 09 4.025E 09 3.271E 09 2.282E 09	1.674E 09 1.269E 09 9.842E 08 7.755E 08 6.180E 08	4.967E 08 4.017E 08 3.264E 08 2.663E 08 2.180E 08	1.788E 08 1.470E 08 1.212E 08 9.999E 07 8.265E 07	6.842E 07 5.672E 07 4.707E 07 3.912E 07 3.255E 07	2.711E 07 2.261E 07 1.888E 07 1.578E 07
N(02) /CM3	1.200E 11 3.607E 10 1.511E 10 7.538E 09 4.221E 09	2.569E 09 1.663E 09 1.128E 09 7.928E 08	2.426E 08 1.458E 08 9.050E 07 5.747E 07 3.711E 07	2.427E 07 1.602E 07 1.065E 07 7.129E 06 4.794E 06	3.238E 06 2.196E 06 1.494E 06 1.020L 06 6.978E 05	4.7896 05 3.295E 05 2.273E 05 1.571E 05 1.089E 05	7.564E 04 5.266E 04 3.673E 04 2.568E 04 1.799E 04
1.6239E 01 N(N2) /CM3	5.800E 11 1.937E 11 8.781E 10 4.669E 10 2.760E 10	1.761E 10 1.189E 10 8.386E 09 6.111E 09	2.126E 09 1.354E 09 8.881E 08 5.951E 08	2.787E 08 1.935E 08 1.353E 08 9.512E 07 6.718E 07	4.763E 07 3.388E 07 2.418E 07 1.730E 07	8.925E 06 6.432E 06 4.646E 06 3.363E 06 2.439E 06	1.291E 06 1.291E 06 9.417E 05 6.883E 05 5.040E 05
INT GRAD= MEAN MOL WT	27.46 26.98 26.55 26.15 25.78	25.43 25.10 24.77 24.46 23.86	23.27 22.71 22.16 21.63	20.64 20.18 19.75 19.35	18.63 18.31 18.02 17.75	17.27 17.06 16.87 16.69	16.35 16.20 16.04 15.89
00E-01. SCALE HT KM	11.4 16.5 21.4 26.1 30.7	35.1 39.2 42.9 46.3 52.4	57.5 61.9 65.8 69.4 72.6	75.6 78.4 81.1 83.7 86.2	88.5 90.8 92.9 95.0	98.9 100.8 102.6 104.3	107.8 109.5 111.2 112.9
S(TH)=-10.0000E-01. PRESSURE SCALE DYNE/CM2 HT KM	3.802E-02 1.847E-02 1.087E-02 7.120E-03 5.004E-03	3.691E-03 2.819E-03 2.209E-03 1.766E-03	. 186 . 284 . 187	836 416 102 645	5.433E-05 4.347E-05 3.496E-05 2.826E-05 2.294E-05	1.871E-05 1.531E-05 1.258E-05 1.037E-05 8.572E-06	7.110E-06 5.914E-06 4.933E-06 4.127E-06 3.462E-06
= 12.000, COS(TH DENSITY PR GM/CM3 DY	3.536E-11 1.185E-11 5.419E-42 2.915E-12 1.747E-12	1, 131E-12 7,764E-13 5,569E-13 4,133E-13 2,454E-13	1.563E-13 1.045E-13 7.230E-14 5.137E-14	2.748E-14 2.055E-14 1.555E-14 1.190E-14 9.188E-15	7.155E-15 5.614E-15 4.437E-15 3.528E-15 2.822E-15	2.269E-15 1.834E-15 1.488E-15 1.213E-15 9.924E-16	8.147E-16 6.710E-16 5.543E-16 4.592E-16 3.814E-16
HOURS)= TEMP K	355 506 640 768 888	998 1096 1182 1257	1466 1532 1579 1614	1659 1673 1683 1691	1701 1705 1708 1710	1713 1714 1715 1715 1715	1716 1717 1717 1718 1718
TIME (IN ALT KM	120 130 140 150	170 180 190 200	240 260 280 300	340 340 380 400 420	440 460 480 500 520	540 560 580 600	640 660 680 700 720

5.706E 03 5.643E 03 5.580E 03 5.19E 03		5.066E 03 5.014E 03 4.962E 03 4.837E 03 4.716E 03 4.600E 03			3.350E 03 3.281E 03 3.215E 03 3.151E 03
8.346E 05 7.984E 05 7.639E 05 7.312E 05 7.000E 05	00000	5.197E 05 4.985E 05 4.785E 05 4.317E 05 3.902E 05 3.542E 05 3.201E 05	037E 401E 187E 994E 821E 664E	523E 395E 280E 175E	9.932E 04 9.147E 04 8.432E 04 7.780E 04
1.106E 07 9.270E 06 7.780E 06 6.537E 06 5.497E 06	27E 29E 39E 46E 34E	1.680E 06 1.424E 06 1.207E 06 8.030E 05 5.370E 05 3.610E 05 2.440E 05 1.657E 05	01.9911.01.01	.267E .959E .333E .506E	2.310E 03 1.664E 03 1.203E 03 8.752E 02 6.363E 02
1.263E 04 8.887E 03 6.265E 03 4.425E 03		2.939E 02 2.112E 02 1.520E 02 6.733E 01 3.016E 01 1.365E 01 6.244E 00 2.885E 00	.350E-0 .023E-0 .453E-0 .045E-0	1.703E-02 8.487E-03 4.266E-03 2.162E-03 1.105E-03	5.694E-04 2.958E-04 1.549E-04 8.170E-05 4.344E-05
3.697E 05 2.717E 05 2.001E 05 1.476E 05	.0686 .9816 .4416 .3036 .4616	1.3736 04 1.028E 04 7.706E 03 3.777E 03 1.869E 03 9.337E 02 4.707E 02	.229E .360E .320E .748E .274E	2.675E 00 1.453E 00 7.957E-01 4.388E-01 2.438E-01	1.364E-01 7.687E-02 4.362E-02 2.492E-02 1.433E-02
15.58 15.42 15.25 14.90	14.70 14.50 14.28 14.04 13.80	13.26 12.96 12.96 11.84 10.96 10.96 9.17	7.56 6.88 6.31 5.43 5.11	######################################	0000 0000 0000 0000 0000 0000
116.5 118.4 120.3 122.4 124.6	127.0 129.5 132.2 135.2 138.4	145.6 149.7 154.2 167.1 182.9 202.0 224.6 250.6	311.0 343.9 377.1 409.6	469.6 496.1 520.1 541.8 561.3	579.0 595.1 609.8 623.5 656.4
2.912E-06 2.456E-06 2.077E-06 1.761E-06	278E- 093E- 382E- 078E- 979E-	2.216E-07 1.30E-07 2.950E-07 2.216E-07 1.30E-07 1.093E-07	52E- 40E- 57E- 07E- 26E- 68E-	4.003E-08 3.609E-08 3.271E-08 2.977E-08 2.719E-08	2.491E-08 2.288E-08 2.105E-08 1.94.1E-08
3.176E-16 2.650E-16 2.217E-16 1.859E-16 1.561E-16	1.314E-16 1.109E-16 9.372E-17 7.938E-17 6.736E-17	4.8826-17 4.1696-17 3.5696-17 2.4436-17 1.6996-17 1.2016-17 8.6576-18	4.786E-18 3.679E-18 2.893E-18 2.326E-18 1.910E-18	1.361E-18 1.176E-18 1.029E-18 9.105E-19 8.126E-19	7.305E-19 6.607E-19 6.006E-19 5.482E-19 5.021E-19
1718 1718 1719 1719	1719 1719 1719 1719 1719	9171	17 19 17 19 17 19 17 19 17 19	1719 1719 1719 1719	1719 1719 1719 1719 1719
740 760 780 800 820	840 880 940 940 950	9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	1300 1350 1400 1450 1500	1600 1650 1700 1750 1800	1850 1900 1950 2000 2050

	<b>ಕ</b> ಕಕಕಕ		03	200 000 000 000 000 000 000 000 000 000	
N(H)	4.556E 2.969E 2.283E 1.862E	1.391E 1.253E 1.151E 1.073E 9.644F	929 #31 066 787 565	7.382E 7.227E 7.092E 6.972E 6.862E 6.666E	
N(HE) /CM3	0E 07 3E 07 0E 07 2E 06 9E 06	_		7E 06 06 06 06 06 06 06 06 06 06 06 06 06	
NCH CM	2.5006 1.5736 1.1406 8.8626 7.2396	6. 1406 5. 3596 4. 7826 4. 34 16	3.282E 2.968E 2.725E 2.527E 2.361E	2.217E 2.090E 1.976E 1.873E 1.777E 1.689E	1.4576 1.3896 1.2656 1.2076 1.1026 1.0076 9.6276
	22228	88888	60 60 80	888888888	008 007 007 007 007 007
N(0) /CM3	7.600E 3.480E 1.990E 1.280E 8.906E	6.567E 5.057E 4.022E 3.280E 2.302E	698 293 007 962 368	5.1356 4.1676 3.3986 2.7818 2.2838 1.8806 1.5516	7.3176 6.0866 5.0866 5.0706 4.5286 3.5306 2.9516 2.9516 2.0696 1.5756
_		60000 80000	08 07 07	000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000	
N(02)	1.200E 3.599E 1.503E 7.505E	2.584E 1.684E 1.149E 8.129E 4.388E	2.540E 1.540E 9.633E 6.163E 4.008E	2.639E 1.754E 1.174E 7.913E 5.359E 3.645E 2.489E	3.8686 3.8686 2.6876 1.3066 6.4056 4.5006 3.1686
0	=== <u>0</u>	00000	66888	008 008 008 07 07	
1.6255E N(N2) /CM3	5.800E 1.933E 8.731E 4.642E 2.753E	1.765E 1.199E 8.504E 6.231E 3.591E	2.208E 1.417E 9.360E 6.313E	2.9936 2.9936 1.4706 1.0406 7.3886 5.2706 3.7726	950 950 384 384 909 909 953 1228
INT GRAD= MEAN MOL WT	27.46 26.98 26.55 26.16 25.80	25.46 25.13 24.82 24.51 23.92	23.35 22.80 22.26 21.74 21.24	20.76 20.30 19.88 19.47 19.10 18.75 18.43	80 8-0-0 48-08
593E-01, SCALE HT KM	11.4 16.6 21.6 26.5 31.3	35.8 39.9 43.7 47.2 53.2	58.4 62.8 66.7 70.2 73.5	76.5 79.4 82.1 84.7 87.2 89.6 91.9	
S(TH)= -9.6 PRESSURE DYNE/CM2	3.802E-02 1.848E-02 1.091E-02 7.185E-03 5.079E-03	3.768E-03 2.892E-03 2.277E-03 1.827E-03	8.576E-04 6.165E-04 4.527E-04 3.381E-04 2.559E-04	1.960E-04 1.516E-04 1.184E-04 9.313E-05 7.379E-05 5.885E-05 3.808E-05	.0346- .5136- .0546- .3896- .3896- .5146- .5146- .5186- .5186- .5186- .5186-
= 13.000, CO: DENSITY GM/CM3	3.536E-11 1.182E-11 5.387E-12 2.898E-12 1.741E-12	1.133E-12 7.815E-13 5.635E-13 4.202E-13 2.515E-13	1.613E-13 1.085E-13 7.544E-14 5.382E-14 3.918E-14	2.8996-14 2.1756-14 1.6516-14 1.2676-14 9.8066-15 7.6566-15 6.0236-15	3.803E-15 3.050E-15 2.458E-15 1.991E-15 1.620E-15 1.324E-15 1.086E-15 1.086E-16 6.114E-16 6.114E-16
HOURS) TEMP K	355 507 647 780 905	10 18 11 19 12 06 12 82 14 03	1493 1558 1607 1642 1669	1688 1703 1714 1722 1728 1733 1737	1745 1746 1746 1749 1750 1751 1751 1752 1752
TIME (IN Alt Km	120 130 140 150 160	170 180 190 200 220	240 260 280 300 320	780 780 780 780 780 780 780 780 780	500 520 580 620 640 700 720

03 03 03 03 03 03	00 00 00 00 00 00 00 00 00 00 00 00 00	00000	03 03 03 03
5.636E 5.578E 5.514E 5.458E 5.397E 5.283E 5.2285 5.120E	5.067E 1.964E 1.964E 1.793E 1.562E 1.562E 1.562E 1.562E	4.151E 4.057E 3.966E 3.879E 3.794E 3.713E 3.634E 3.558E 3.484E	3.2776 3.2126 3.1496 3.0896
0000 0000 00000 00000	005 005 005 005 005	000 000 000 000 000 000 000 000 000 00	5 4 4 4 4 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
.4356 .7356 .4096 .1006 .8046 .5236 .2556	.5236 .3026 .0906 .8886 .4216 .0046 .5316 .2976	. 4876 . 0746 . 8976 . 7576 . 5926 . 4616 . 3426 . 1366	. 0476 . 6606 . 9196 . 2436 . 6256
88rrr 9999N	የመመቀት ችሥመሪያ	222	-0884
00 00 00 00 00 00 00 00 00 00 00 00 00	E 066 E 066 E 066 E 056	1003 1003 1003 1003 1003 1003 1003 1003	E 03 E 03 E 02
1.225E 8.677E 7.315E 6.173E 5.214E 4.408E 3.731E 3.160E	2.274E 1.931E 1.642E 1.397E 9.368E 6.315E 4.279E 2.915E	9.4896 6.5918 4.5998 3.2248 2.2708 1.6068 1.1418 8.1378 5.8298	3.0286 2.1951 1.5981 1.1671 8.5586
003 003 003 003 003 003 003 003 003 003	002 002 002 001 001 000	-01 -01 -01 -02 -03	### # # # # # # # # # # # # # # # # #
1	876 616 656 466 466 866 866	715 725 786 786 986 105	973E- 249E- 783E- 487E- 008E-
1.58 7.94 7.94 7.94 7.94 7.05 7.05 7.05 7.05	36 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	9.9 2.2 1.4 8.0
500 S S S S S S S S S S S S S S S S S S	005 005 005 005 005 005 005 005 005 005	000000000000000000000000000000000000000	00000
876 186 236 096 096 256 056	3666 7786 33396 0106 0216 2276 5206 3626 7486	69E 49E 85E 89E 26E 26E 52E 86E- 27E-	23E- 67E- 71E- 00E- 42E-
# 100 00 00 00 00 00 00 00 00 00 00 00 00	4	W6-24 7-249	55555
15.69 15.38 15.38 15.04 14.86 14.47 14.25	3.78 3.52 3.52 2.97 2.20 2.20 1.36 0.49 7.98	7.27 6.65 6.13 5.69 5.33 5.04 4.81 4.62 4.47	7 - 2 - 3 - 3 - 3 - 3 - 3 - 3 - 3 - 3 - 3
	- 6 4 5 4 5 5 5 6 6 6 7 6 6 6 6 6 6 6 6 6 6 6 6 6	8 t c 2 c - 2 - 2 - 2 - 2	мэрью
118.0 119.9 123.8 125.9 125.9 128.2 130.6 133.2 135.9	142.1 145.4 149.4 153.5 165.4 197.6 218.5 272.6	3300.5 332.7 335.9 3365.9 3369.1 462.0 462.0 561.6 561.8	588- 598- 615- 643-
77000 00000	~~~~~ ~~~~		8888
26-0 26-0 26-0 36-0 36-0 36-0	36 - 0 36 - 0 36 - 0 36 - 0 36 - 0 36 - 0 36 - 0		716-0 716-0 766-0 006-0
3.28 2.34 2.34 1.70 1.70 1.45 1.07 7.97	6.91 6.01 6.01 7.25 7.36 7.36 7.36 7.36 7.36 7.36 7.36 7.36	8-422 6-2318 5-4678 4-3338 4-3338 3-5331 2-9351	2.69 2.47 2.27 2.27 1.94
	717777777777777777777777777777777777777	88888 88866	6666
36- 26- 36- 36- 36- 36- 36- 36- 36-	5316-1 7726-1 0926-1 8126-1 9606-1 3886-1 9946-1		857E-1
3.53 2.95 2.05 2.08 1.75 1.25 7.66	6.5316 5.5778 4.0928 2.8128 1.9608 1.9608 7.3338	4. 1978 3.2798 2.6176 2.1328 1.7718 1.4978 1.2868 1.2868 1.2868 1.8198	7.88 6.4.0 5.86 5.33
# # # # # # # # # # # # # # # # # # #	ವನನನನ ಹನನನನ	1754 1754 1754 1754 1754 1754 1754 1754	1754 1754 1754 1754 1754
71 71 71 71 71 71 71 71 71 71 71 71 71 7		71 71 71 71 71 71 71 71 71 71 71 71 71 7	77.77
740 740 760 800 820 820 840 880 900	940 940 940 940 940 950 950 350 350	350 400 500 550 600 650 1750	1850 1900 1950 2000 2050
<b>~~~∞∞ ∞∞∞∘∘</b>	2225	P2222 2222	~~~~~

	Œ.	/CM3	-356E	-960E	.265E	_	1.566E 04			1.141E 04			-836E	. 397E	.037E	-760E	7.539E 03		37E	<u>=</u>	55.	H +	6.833E 03	316	35E	6.545E 03	39E	76E	97E	20E	6.145E 03	7.3E		933E	.865F	799F	.735E	5.671E 03
į	N(HE)	/CM3				8.777E 06	7.168E 06	085E 06	318E 06	4.751E 06	318E 06	700E 06	27.7E	967E	725E	528E	2.363E 06		219E	09.2E	3E	874E	7		608E 06	531E 06	459E 06	1E 06	90	267E 06	210E 06	156E 06	90	056E	010E	659E	24.3E	8.848E 05
	(O)N	/CM3	.600E	-4.70E	-979E	1.272E 10	.866€	.554E	-059E	4.054E 09	.297E	•323E	.718E	.311E	.022E	•093E	6.479E 08		-228E	.246E	.465E	.838E	2.355E 08	.922E	.587E	1.314E 08	•089E	•043E	.521E	.264E	223E	.362E	949.	52E	58E	39t	32E	1.5156 07
	N ( 02 )	/CM3	200€	591E	498E	7.495E 09	23 1E	-602E	.703E	2	.285E	366ħ•	.616E	.591E	977E	.397E	4.168E 07		.749E	.830E	•	.289E	9479	.833E	.623E	1.801E 06	.24 JE	.572E	.939E	. 126E	2.873£ 05	-006E	* #0#E	.845E	-920E	.875E	- t t 1 E	2.434E 04
1.6315E 01	NINZI	/Cw3	.800E	.928E 1	.695E 1	4.630E 10	.755E 1			8.610E 09		-	2.263E 09				-			111	1.528E 08	111		₹00¢	-947E	2.839E 07	.048E	*481E	111	111	5.686E 06			.225E	.634E	.202E	.862E	6.545E 05
INT GRAD=	MEAN	MOL WT	-‡	26.98	5	_	25.81	5	Š	24.84	*	δ.	23.39	22.84	22.31	21.79	21.29		20.81	~	19.93	. ^	_	18.80	18.47	18.18	17.90	17.65		N	17.00	16.82	•	16.48	16.33	16.17	16.03	15.88
03E-01,	SCALE	H KA	11.4	16.6	21.7	26.8	31.6			- † <del>†</del>			58.6	63.0	6.99	70.4	73.6			•	82.3			•	- 6	94.5	•	٠		•	104.5			-	-		115.1	116.8
S(TH)= -8.66			802E-0	-849E-0	.095E-0	•	.138E-0	-824E-0	.943E-0	2.322E-03	.867E-0	.257E-0	8.799E-04	.334E-	•655	-478E-	.635E-		-019E-	•563E-0	1.2216-04	.613E-0	.623E-0	.084E-0	.885E-0	3.943E-05	.198E-0	•606E-0	.133E-0	.752E-0	1.444E-05	.195E-0	.917E-0	~	.891E-0	-	4.842E-06	.075E-0
= 14.000, CO			3.536E-11	-180E-1	-365E-1	.889E-1	.742E-1	.137E-1	.876E-1	5.697E-13	.261E-1	.562E-1	1.648E-13	. 1 1 IE-1	.736E-1	.525E-1	.025E-1		2.980E-14	2.237E-14	1.699E-14	1.304E-14	1.010E-14	.887E-1	.208E-1	4.920E-15	.925E-1	. 149E-1	2.540E-15	2.059E-15	1.677E-15	1.372E-15	1.126E-15	.276E-1	-667E-1	.357E-1	5.285E-16	.406E-1
N HOURS)	T E	¥	355	509	652	789	916	1030	1130	12.18	1293	1413	1502	1567	1615	1650	1677		9691	1711	1723	1732	1739	1744	1748	1752	1755	1757	1759	1760	1761	1763	1763	1764	1765	1765	1766	1766
TIME (IN	_	¥	120	130	0 1 1	150	160	170	180	190	200	220	240	260	280	300	320	i	340	360	380	004	420	044	1460	1480	200	520	540	260	580	909	<b>9</b> 50	049	099	980	700	720

5.609E 03 5.548E 03 5.489E 03 5.430E 03	5.315E 03 5.260E 03 5.205E 03 5.151E 03 5.098E 03	5.046E 03 4.995E 03 4.945E 03 4.895E 03 4.775E 03	4.59E 03 4.548E 03 4.440E 03 4.337E 03 4.237E 03 4.047E 03 3.958E 03		3,341E 03 3,275E 03 3,210E 03 3,148E 03 3,088E 03
8.471E 05 8.113E 05 7.772E 05 7.448E 05	6.844E 05 6.564E 05 6.296E 05 6.041E 05 5.777E 05	5.565E 05 5.343E 05 5.131E 05 4.929E 05 4.462E 05	4.044E 05 3.670E 05 3.335E 05 3.035E 05 2.765E 05 2.522E 05 2.303E 05 2.106E 05		1.069E 05 9.867E 04 9.116E 04 8.430E 04 7.803E 04
1.275E 07 1.074E 07 9.057E 06 7.645E 06	5.464E 06 4.625E 06 3.920E 06 3.325E 06 2.822E 06	2.398E 06 2.040E 06 1.736E 06 1.479E 06 9.951E 05	6.728E 05 4.573E 05 3.124E 05 2.145E 05 1.480E 05 1.026E 05 7.149E 04 5.003E 04		3.365E 03 2.446E 03 1.784E 03 1.307E 03 9.607E 02
1.726E 04 1.226E 04 8.723E 03 6.221E 03 4.445E 03	3.182E 03 2.282E 03 1.640E 03 1.180E 03 8.514E 02	6.151E 02 4.452E 02 3.228E 02 2.345E 02 1.062E 02	4.865E 01 2.251E 01 1.052E 01 4.967E 00 2.368E 00 1.140E 00 5.538E-01 2.716E-01	3446 7106 7106 7176 7936 5426 3656	1.241E-03 6.564E-04 3.499E-04 1.879E-04
4.842E 05 3.588E 05 2.664E 05 1.981E 05 1.476E 05	1.101E 05 8.233E 04 6.164E 04 4.622E 04 3.472E 04	2.612E 04 1.968E 04 1.485E 04 1.123E 04 5.612E 03	2.832E 03 1.442E 03 7.407E 02 3.839E 02 2.007E 02 1.058E 02 5.622E 01 3.012E 01	- 1 1	2.689E-01 1.540E-01 8.874E-02 5.149E-02 3.006E-02
15.73 15.58 15.43 15.26	14.92 14.74 14.54 14.33	13.87 13.62 13.36 13.08	11.52 10.66 9.79 8.94 8.15 7.43 6.25	5.80 5.42 5.42 5.42 6.44 6.53 8.39	# # 129 # # 15 # 09
118.6 120.5 122.4 124.4 126.5	128.7 131.0 133.6 136.3 136.3	142.3 145.7 189.4 153.4	179.0 196.0 216.3 239.9 266.8 296.5 328.3 361.4	394.7 427.4 458.6 487.8 514.7 539.3	581.7 600.0 616.8 632.2 646.5
3.438E-06 2.908E-06 2.467E-06 2.097E-06 1.788E-06	1.529E-06 1.311E-06 1.127E-06 9.714E-07 8.401E-07	7.288E-07 6.342E-07 5.538E-07 4.853E-07 3.542E-07	2.647E-07 2.026E-07 1.589E-07 1.276E-07 1.047E-07 7.464E-08		2.772E-08 2.547E-08 2.346E-08 2.166E-08 2.003E-08
3.682E-16 3.084E-16 2.590E-16 2.179E-16 1.837E-16	1.552E-16 1.314E-16 1.114E-16 9.469E-17 8.062E-17	6.877E-17 5.877E-17 5.033E-17 4.319E-17 2.972E-17	2.074E-17 1.469E-17 1.058E-17 7.759E-18 5.801E-18 4.426E-18 3.449E-18	.230E-1 .847E-1 .557E-1 .334E-1 .158E-1 .018E-1	8.092E-19 7.296E-19 6.618E-19 6.032E-19 5.520E-19
1767 1767 1767 1767	1768 1768 1768 1768	1768 1768 1768 1768	1768 1768 1768 1768 1768	1768 1768 1768 1768 1768 1768	1768 1768 1768 1768
740 760 780 800 820	840 880 900 920	940 960 980 1000	1100 1150 1200 1250 1300 1400	1500 1550 1600 1650 1750	1850 1900 1950 2000 2050

54	****	· នានានានាកា សហហសាកា	וא פארא מארא מארא מארא מ	
~ m	20030 20030			00000 00000
HS/	3561 951 253 833 560	1 MUM - 0 - 0 - 3 - 10 MUM 1	408 408 110 110 110 110 110 110 110 110 110 1	.3246 .2466 .1706 .0966 .0256 .9556 .8206 .7546
	300-F			
	07 07 06 06	99999999999	999999999999999999999999999999999999999	2000 COCC CCC CCC CCC CCC CCC CCC CCC CCC
Ē.				411 (14 14 141 411 (17 121 141 141 141 141
NCHE!	500E 564E 738E	32 32 33 33 72 72 72 74 74 74 74	3669 4888	3298 2108 1046 1046 1046 1046 1046 1046 1046 1046
	. 0	оровы метор	1 00	
	22228	6666666689	0088888 00880 0080 0080 0080 0080	007 007 007 007 007 007
N(0) /CM3	006 616 726 696 706	1736 1846 1876 1876 1876 1876 1876 1876 1876 187	406 496 616 616 316 236 126 776 496	34E 85E 52E 98E 90E 02E 13E 67E 84E
ΣŠ	7.60 3.46 1.97 1.26 8.87	noomm -mo-n	i datam datado	3.59 3.59 3.59 3.50 1.76 1.76
	, , , _			12.0.4.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1
_	<u> </u>	00 00 00 00 00 00 00 00 00 00 00 00 00	000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000 000	00 00 00 00 00 00 00 00 00 00 00 00 00
N(02)	200E 584E 496E 505E 252E	6236 1816 3856 3856 5536 6446 6056 1696	- 0 - M + 6 0 0 - 6	73E 02E 81E 338E 54E 76E 76E 75E 75E
<b>Z</b> \	3.5	200 p		2.32 2.32 2.32 3.29 2.32
-				
0	==222	000000000000000000000000000000000000000		00 00 00 00 00 00 00 00 00 00 00 00 00
64116 NCN2 /CM3	800E 924E 677E 633E	7866 2206 6966 3986 7086 7086 4696 4766	171 172 173 173 173 173 173 174 174 174 174 174 174 174 174 174 174	0486 6056 5306 0306 9436 1536 1606 5796 5796 5796
2	v - 0 = 4			091-2 245
AD=				
2 Z Z	#6 98 56 17	85 97 97 97 31 31	000-t-4 -000	7.40 7.18 6.98 6.98 6.63 6.15 6.15 5.86
INT MG	26. 26. 26.	22223 33455	00000 0000	FF 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6
₩₩	4 F O O F	awoam woac-	2-840 v8-44	מאומר ממסרים
SCALE HT XM	26.1.	450 0 344 60 60 60 60 60 60 60 60 60 60 60 60 60	76.79 81.8 81.8 84.9 94.9 90.1 90.2 90.2 90.2	100- 102- 104- 105- 107- 111- 116-
2	010101000			
PRESSURE DYNE/CM2	3.802E-02 1.851E-02 1.099E-02 7.281E-03 5.174E-03	3.853E-03 2.967E-03 2.340E-03 1.880E-03 1.264E-03 8.832E-04 6.343E-04 3.465E-04 2.623E-04	2.006E-04 1.205E-04 1.205E-04 0.507E-05 6.002E-05 4.813E-05 3.881E-05 3.146E-05 2.561E-05	2.094E-05 1.719E-05 1.416E-05 1.170E-05 9.706E-06 8.073E-06 6.735E-06 5.634E-06 4.726E-06 3.975E-06
H H	802 851 099 281	3.853E-0 2.3407E-0 2.3400E-0 1.264E-0 8.832E-0 6.3452E-0 2.623E-0	00061 20091 52091 52091 6021 88181 5618	2.094E-(1.719E-(1.416E-(1.170E-(9.706E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E-(9.735E
COS(TH) PRE DYN	₩×	W 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	2 de 10 de 1	219 B 20-4W
>-	==222	* <u>555565 55444</u>	<u> </u>	85888 55555
15.000, C DENSITY GM/CM3	19 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	40 - 40 - 40 - 40 - 40 - 40 - 40 - 40 -	06- 26- 36- 36- 76- 76- 86- 86- 86- 86-	25 F F F F F F F F F F F F F F F F F F F
.5 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0 .0	3.536E-11 1.177E-11 5.354E-12 2.891E-12 1.748E-12	1.1446-12 5.7546-13 5.7546-13 4.3046-13 2.5896-13 1.6656-14 7.7866-14 5.5496-14	2.980E-14 1.6.92E-14 1.296E-14 1.296E-14 1.003E-14 7.820E-15 6.147E-15 4.866E-15 3.877E-15	2.505E-15 2.029E-15 1.651E-15 1.349E-15 1.106E-15 9.107E-16 6.231E-16 5.177E-16
S)=				
HOURS)=	355 510 655 793 919	1032 1131 1216 1216 1407 1493 1603 1604	1684 1699 1711 1720 1728 1738 1742 1745	1749 1751 1753 1754 1754 1755 1757 1757 1758
		orer effet		
ME (IN ALT KM	250 200 60 60	170 180 220 220 240 240 260 3300 320	3840 3860 3860 3860 5860 5860 5860	5540 6580 6580 6580 700 700
TIME ALT KM		กิน กินกัพพ	mmកានា នានុនិលីហី	2000 000 000 000 000 000 000 000 000 00

5.627E 05 5.566E 03 5.506E 03 5.446E 05	5.231E 03 5.275E 03 5.220E 03 5.166E 03	5.060E 03 5.008E 03 4.958E 03 4.787E 03	4.670E 03 4.557E 03 4.449E 03 4.345E 03	4.147E 03 4.054E 03 3.964E 03 5.877E 05	3.711E 05 3.632E 03 3.556E 03 3.483E 03 3.412E 03	3.343E 03 3.276E 03 3.212E 03 3.149E 03 3.089E 03
8.457E 05 8.098E 05 7.756E 05 7.431E 05	6.826E 05 6.544E 05 6.276E 05 6.020E 05 5.777E 05	5.544E 05 5.322E 05 5.110E 05 4.907E 05	4,023E 05 3,649E 05 3,315E 05 3,015E 05 2,745E 05	2.503E 05 2.285E 05 2.088E 05 1.910E 05	1.604E 05 1.473E 05 1.353E 05 1.245E 05 1.146E 05	1.057E 05 9.749E 04 9.003E 04 8.323E 04 7.701E 04
1.248E 07 1.051E 07 8.853E 06 7.467E 06	5.328E 06 4.507E 06 3.816E 06 3.234E 06 2.745E 06	2,329E 06 1,979E 06 1,684E 06 1,435E 06 9,623E 05	6.495E 05 4.407E 05 3.005E 05 2.060E 05	9.817E 04 6.827E 04 4.769E 04 3.547E 04 2.360E 04	1.671E 04 1.188E 04 8.484E 03 6.084E 03	3.166E 03 2.298E 03 1.674E 03 1.224E 03 8.986E 02
1.647E 04 1.168E 04 8.296E 03 5.906E 03	3.011E 03 2.156E 03 1.547E 03 1.112E 03 8.006E 02	5.775E 02 4.174E 02 3.022E 02 2.191E 02 9.891E 01	4.512E 01 2.080E 01 9.687E 00 4.557E 00 2.165E 00	1.038E 00 5.027E-01 2.457E-01 1.212E-01 6.030E-02	3.027E-02 1.533E-02 7.825E-03 4.029E-03 2.091E-03	1.0946-03 5.7696-04 3.0666-04 1.64 16-04 8.8546-05
4.650E 05 3.44TE 05 2.55TE 05 1.894E 05	1.050E 05 7.83BE 04 5.860E 04 4.389E 04 3.292E 04	2.473E 04 1.861E 04 1.402E 04 1.059E 04 5.274E 03	2.653E 03 1.346E 03 6.895E 02 3.562E 02 1.856E 02	9.754E 01 5.169E 01 2.761E 01 1.487E 01 8.069E 00	4.413E 00 2.431E 00 1.350E 00 7.546E-01	2.410E-01 1.376E-01 7.909E-02 4.577E-02 2.666E-02
15.71 15.56 15.40 15.24 15.07	14.89 14.70 14.50 14.29	13.82 13.57 13.30 13.02	11.43 10.57 9.69 8.84 8.05	7.34 6.71 6.18 5.73 5.37	5.07 4.83 4.64 4.94 4.37	4.27 4.20 4.13 4.08
118.2 120.1 122.0 124.0	128.3 130.7 133.3 136.0 139.0	142.2 145.6 149.3 153.4	179.5 196.8 217.4 241.5	298.7 330.8 363.9 397.2 429.6	460.5 489.3 515.8 539.8 561.6	581.4 599.3 615.7 630.8 644.8
3.352E-06 2.834E-06 2.402E-06 2.042E-06 1.746E-06	1.487E-06 1.274E-06 1.095E-06 9.437E-07 8.159E-07	7.077E-07 6.158E-07 5.377E-07 4.711E-07 3.440E-07	2.572E-07 1.971E-07 1.547E-07 1.244E-07	8.566E-08 7.306E-08 6.326E-08 5.547E-08	4.392E-08 3.953E-08 3.579E-08 3.256E-08 2.973E-08	2.1246-08 2.5036-08 2.3056-08 2.1276-08 1.9676-08
3.602E-16 3.015E-16 2.530E-16 2.127E-16 1.792E-16	1.513E-16 1.280E-16 1.085E-16 9.215E-17 7.84 IE-17	6.685E-17 5.711E-17 4.888E-17 4.192E-17 2.882E-17	2.010E-17 1.423E-17 1.025E-17 7.516E-18 5.623E-18	4.2956-18 3.3516-18 2.6716-18 2.1746-18 1.8036-18	1.523E-18 1.306E-18 1.136E-18 9.992E-19 8.880E-19	7.9566-19 7.1786-19 6.5136-19 5.9386-19 5.4356-19
1758 1758 1759 1759	1759 1759 1760 1760	1760 1760 1760 1760 1760	1760 1760 1760 1760 1760	1760 1760 1760 1760 1760	1760 1760 1760 1760	1760 1760 1760 1760
740 760 780 800	840 880 900 920	940 960 980 1000 1050	1100 1150 1200 1250	1350 1400 1450 1500 1550	1600 1650 1700 1750	1850 1900 1950 2000 2050

N(H) /CM3	4.356E 04 2.943E 04 2.246E 04 1.833E 04	1.383E 04 1.253E 04 1.156E 04 1.082E 04	9.079E 03 8.588E 05 8.224E 03 7.940E 03	7.521E 03 7.358E 03 7.214E 05 7.085E 03	6.860E 03 6.758E 03 6.663E 03 6.572E 03	6.401E 03 6.320E 03 6.242E 03 6.166E 03	6.020E U3 5.950E 03 5.881E 03 5.814E 03
N(HE) /CM3	2.500E 07 1.560E 07 1.123E 07 8.740E 06 7.176E 06	6.1226 06 5.372E 06 4.815E 06 4.387E 06 3.769E 06	3.343E 06 3.027E 06 2.778E 06 2.575E 06 2.403E 06	2.254E 06 2.122E 06 2.003E 06 1.895E 06	1.704E 06 1.619E 06 1.539E 06 1.465E 06	1.329E 06 1.268E 06 1.209E 06 1.154E 06	1.052E 06 1.005E 06 9.604E 05 9.182E 05 8.780E 05
NCO) / CM3	7.600E 10 5.454E 10 1.969E 10 1.272E 10 8.915E 09	6.622E 09 5.129E 09 4.097E 09 3.352E 09 2.360E 09	1.740E 09 1.323E 09 1.027E 09 8.092E 08 6.444E 08	5.174e 08 4.180E 08 3.394e 08 2.766E 08	1.855E 08 1.525E 08 1.257E 08 1.037E 08	7.103E 07 5.892E 07 4.894E 07 4.070E 07	2.826E 07 2.360E 07 1.972E 07 1.650E 07
N(02) /CM3	1.200E 11 3.578E 10 1.496E 10 7.533E 09 4.281E 09	2.644E 09 1.734E 09 1.189E 09 8.429E 08 4.553E 08	2.627E 08 1.583E 08 9.833E 07 6.241E 07 4.025E 07	2.628E 07 1.732E 07 1.151E 07 7.693E 06 5.171E 06	3.493E 06 2.369E 06 1.613E 06 1.102E 06 7.548E 05	5.187E 05 3.575E 05 2.470E 05 1.711E 05	8.272E 04 5.772E 04 4.036E 04 2.828E 04 1.986E 04
1.6533E 01 N(N2) /CM3	5.800E 11 1.921E 11 8.675E 10 4.648E 10 2.783E 10	1.800E 10 1.230E 10 8.763E 09 6.438E 09 3.714E 09	2.278E 09 1.455E 09 9.552E 08 6.398E 08 4.349E 08	2.989E 08 2.073E 08 1.448E 08 1.017E 08 7.177E 07	5.088E 07 3.620E 07 2.584E 07 1.850E 07	9.566E 06 6.904E 06 4.994E 06 3.621E 06 2.631E 06	1.916E 06 1.398E 06 1.022E 06 7.483E 05 5.491E 05
INT GRAD= MEAN MOL WT	27.46 26.98 26.56 26.18 25.82	25.48 25.16 24.85 24.54 23.95	23.37 22.81 22.26 21.73	20.73 20.27 19.83 19.43	18.70 18.37 18.08 17.80	17.32 17.11 16.91 16.73	16.40 16.24 16.08 15.93
00006-01, SCALE HT KM	11.4 16.7 21.9 26.9 31.6	36.0 39.9 43.5 46.8	57.4 61.6 65.4 68.9 72.1	75.1 78.0 80.8 83.4	88.4 90.7 93.0 95.1	99.2 101.1 102.9 104.7	108.2 109.9 111.7 115.2
COS(TH)= -5.00 PRESSURE DYNE/CM2	3.802E-02 1.855E-02 1.101E-02 7.305E-03 5.188E-03	3.858E-03 2.964E-03 2.332E-03 1.869E-03	8.686E-04 6.207E-04 4.531E-04 3.364E-04 2.533E-04	1.930E-04 1.487E-04 1.156E-04 9.057E-05	5.686E-05 4.548E-05 3.658E-05 2.957E-05	1.959E-05 1.604E-05 1.318E-05 1.087E-05 8.998E-06	7.468E-06 6.217E-06 5.190E-06 4.345E-06 3.647E-06
16.000. DENSITY GM/CM3	3.536E-11 1.175E-11 5.352E-12 2.900E-12 1.759E-12	1.154E-12 8.007E-13 5.797E-13 4.333E-13 2.597E-13	1.662E-13 1.113E-13 7.698E-14 5.461E-14 3.952E-14	2.907E-14 2.169E-14 1.638E-14 1.251E-14 9.641E-15	7.498E-15 5.877E-15 4.640E-15 3.688E-15 2.949E-15	2.371E-15 1.916E-15 1.555E-15 1.268E-15 1.038E-15	8.523E-16 7.024E-16 5.807E-16 4.814E-16
N HOURS)= TEMP K	355 512 657 793 916	10.25 11.20 12.03 12.73	1469 1530 1576 1610 1636	1656 1671 1683 1692	1705 1710 1717 17171 9171	1722 1723 1723 1726 1726	1728 1729 1729 1730
TIME (IN ALT KM	120 130 140 150	170 180 190 200 220	240 260 280 300	340 340 380 420	2000 2000 2000 2000	540 580 600 620	640 660 680 700 720

5.684E 03 5.621E 03 5.559E 03 5.498E 03 5.439E 03	5.380E 03 5.323E 03 5.266E 03 5.210E 03 5.156E 03	5.102E 03 5.049E 03 4.998E 03 4.946E 03	4.703E 03 4.588E 03 4.477E 03 4.371E 03	4.169E 03 4.074E 03 3.982E 03 3.893E 03	3.724E 03 3.644E 03 3.564E 03 3.492E 03	3.349E 03 3.281E 03 3.216E 03 3.152E 05
8.399E 05 8.037E 05 7.692E 05 7.365E 05 7.053E 05	6.756E 05 6.473E 05 6.204E 05 5.947E 05 5.702E 05	5.469E 05 5.247E 05 5.035E 05 4.832E 05	3.949E 05 3.577E 05 3.244E 05 2.946E 05	2.438E 05 2.223E 05 2.028E 05 1.853E 05 1.695E 05	1.552E 05 1.423E 05 1.306E 05 1.200E 05	1.015E 05 9.358E 04 8.631E 04 7.969E 04 7.365E 04
1.159E 07 9.730E 06 8.176E 06 6.877E 06 5.791E 06	4.881E 06 4.118E 06 3.478E 06 2.940E 06 2.947E 06	2.106E 06 1.785E 06 1.515E 06 1.286E 06 8.582E 05	5.756E 05 3.882E 05 2.631E 05 1.793E 05	8.446E 04 5.840E 04 4.057E 04 2.831E 04 1.985E 04	1.398E 04 9.886E 03 7.022E 03 5.009E 03 3.588E 03	2.581E 03 1.863E 03 1.351E 03 9.829E 02 7.180E 02
1.398E 04 9.860E 03 6.968E 03 4.934E 03 3.501E 03	2.489E 03 1.773E 03 1.265E 03 9.047E 02 6.481E 02	4.651E 02 3.344E 02 2.409E 02 1.738E 02	3.491E 01 1.590E 01 7.315E 00 3.400E 00 1.597E 00	7.570E-01 3.624E-01 1.751E-01 8.541E-02 4.203E-02	2.087E-02 1.046L-02 5.282E-03 2.691E-03 1.383E-03	7.160E-04 3.738E-04 1.967E-04 1.043E-04 5.569E-05
4.037E 05 2.973E 05 2.194E 05 1.622E 05 1.201E 05	8.906E 04 6.617E 04 4.925E 04 3.671E 04 2.741E 04	2.050E 04 1.536E 04 1.152E 04 8.658E 03 4.267E 03		7.411E 01 5.888E 01 2.056E 01 1.097E 01 5.894E 00	3.193E 00 1.743E 00 9.585E-01 5.311E-01 2.964E-01	1.666E-01 9.427E-02 5.372E-02 3.082E-02 1.780E-02
15.63 15.47 15.31 15.14	14.77 14.57 14.36 16.14	13.64 13.37 13.09 12.79	11.13 10.24 9.35 8.51 7.73	7.04 6.45 5.95 5.20	4.93 4.55 4.11 4.30	4.22 4.15 4.10 4.05
117.0 118.8 120.8 122.9	127.3 129.8 132.5 135.3	141.8 145.4 149.4 153.7	181.5 199.9 221.8 247.1 275.5	306.4 339.1 372.3 405.2 436.7	466.4 493.7 518.6 541.1	579.8 596.4 611.7 625.9 639.1
3.070E-06 2.591E-06 2.193E-06 1.861E-06 1.583E-06	1.351E-06 1.157E-06 9.929E-07 8.551E-07 7.389E-07	6.406E-07 5.573E-07 4.866E-07 4.264E-07	2.337E-07 1.797E-07 1.4 17E-07 1.144E-07 9.444E-08	7.951E-08 6.809E-08 5.915E-08 5.201E-08 4.618E-08	4.134E-08 3.725E-08 3.375E-08 3.071E-08 2.805E-08	2.570E-08 2.360E-08 2.173E-08 2.004E-08 1.852E-08
3.334E-16 2.785E-16 2.332E-16 1.957E-16	1.386E-16 1.170E-16 9.901E-17 8.394E-17 7.129E-17	6.067E-17 5.174E-17 4.422E-17 3.787E-17 2.595E-17	1.806E-17 1.277E-17 9.199E-18 6.756E-18 5.068E-18	3.8866-18 3.0476-18 2.4426-18 1.9986-18 1.6676-18	1.415E-18 1.220E-18 1.065E-18 9.404E-19	7.526E-19 6.801E-19 6.179E-19 5.637E-19 5.162E-19
1731 1731 1731 1732	1732 1732 1732 1732 1732	1732 1733 1733 1733 1733	1733 1733 1733 1733 1733	1733 1733 1733 1733	1733 1733 1733 1733 1733	1733 1733 1733 1733 1733
740 760 780 800	840 860 880 900	940 960 980 1000 1050	1100 1150 1200 1250	1350 1400 1450 1500	1600 1650 1700 1750 1800	1850 1900 1950 2000 2050

58		a + + a a	80 M M M M	003 003 003 003 003 003 003	00000 B88888
N(H) /CM3	4.356E 04 2.936E 04 2.244E 04 1.838E 04 1.579E 04	1.401E 04 1.274E 04 1.179E 04 1.106E 04	9.307E 03 8.805E 03 8.425E 03 8.130E 03 7.891E 03	7.691E 0 7.569E 0 7.569E 0 7.234E 0 7.111E 0 6.892E 0 6.697E 0	6,518E 0 6,183E 0 6,183E 0 6,27E 0 6,197E 0 6,048E 0 5,977E 0 5,907E 0
N(HE) /CM3	2.500E 07 1.556E 07 1.122E 07 8.767E 06 7.234E 06	6.198E 06 5.458E 06 4.904E 06 4.474E 06 3.849E 06	3.412E 06 3.085E 06 2.827E 06 2.616E 06 2.437E 06	2.282E 06 2.145E 06 2.022E 06 1.910E 06 1.808E 06 1.713E 06 1.625E 06 1.544E 06 1.467E 06	1.328E 06 1.265E 06 1.205E 06 1.149E 06 1.095E 06 9.971E 05 9.518E 05 9.689E 05
N(0) /CM3	7.600C 10 3.448E 10 1.969E 10 1.277E 10 8.987E 09	6.695E 09 5.193E 09 4.150E 09 3.392E 09 2.379E 09	1.745E 09 1.319E 09 1.018E 09 7.969E 08 6.309E 08	5.037E 08 4.047E 08 3.268E 08 2.650E 08 2.156E 08 1.439E 08 1.180E 08 9.694E 07	6.576E 07 6.429E 07 4.489E 07 3.717E 07 3.081E 07 2.126E 07 1.769E 07 1.473E 07
Nf02) /CM3	1.200E 11 3.574E 10 1.498E 10 7.571E 09	2.668E 09 1.748E 09 1.195E 09 8.44 IE 08	2.573E 08 1.532E 08 9.401E 07 5.897E 07	2.428E 07 1.583E 07 1.041E 07 6.886E 06 4.583E 06 2.058E 06 1.388E 06 9.390E 05	4.340E 05 2.963E 05 2.029E 05 1.393E 05 9.586E 04 4.573E 04 4.573E 04 2.202E 04 1.533E 04
1.6669E 01 N(N2) /CM3	5.800E 11 1.918E 11 8.683E 10 4.670E 10 2.805E 10	1.242E 10 8.826E 09 6.464E 09 3.698E 09	2.245E 09 1.418E 09 9.214E 08 6.108E 08	2.798E 08 1.922E 08 1.330E 08 9.257E 07 6.477E 07 3.211E 07 2.273E 07 1.614E 07	8.207E 06 5.876E 06 4.216E 06 3.033E 06 2.186E 06 1.579E 06 1.143E 06 8.294E 05 6.028E 05
INT GRAD= MEAN MOL WT	27.46 26.98 26.56 26.18 25.82	25.48 25.15 24.83 24.52 23.91	23.31 22.74 22.17 21.63 21.11	20.61 20.14 19.70 19.29 18.91 18.56 18.24 17.95	17.21 17.00 16.80 16.62 16.45 16.13 15.97 15.97
382E-01, SCALE HT KM	11.4 16.8 21.9 26.8 31.4	35.5 39.3 #2.7 #5.8	56.0 60.2 64.0 67.4	73.7 76.5 76.5 776.5 81.9 86.8 86.8 89.1 991.3	97.4 99.3 101.1 102.9 104.6 106.3 108.0 111.5
COS(TH)= -2.58 PRESSURE DYNE/CM2	3.802E-02 1.855E-02 1.104E-02 7.318E-03 5.188E-03	3.846E-03 2.943E-03 2.306E-03 1.839E-03	8.394E-04 5.951E-04 4.312E-04 3.180E-04 2.380E-04	1.804E-04 1.382E-04 1.069E-04 8.343E-05 6.559E-05 5.193E-05 4.137E-05 3.315E-05 2.670E-05	1.756E-05 1.433E-05 1.173E-05 9.644E-06 7.953E-06 6.579E-06 5.459E-06 4.542E-06 3.791E-06
17.000, DENSITY GM/CM3	3.536-11 1.1736-11 5.3576-12 2.9136-12 1.7736-12	1.165E-12 8.084E-13 5.843E-13 4.356E-13 2.592E-13	1.645E-13 1.092E-13 7.493E-14 5.275E-14 3.791E-14	2.771E-14 2.056E-14 1.544E-14 1.173E-14 9.002E-15 6.970E-15 5.442E-15 4.280E-15 3.389E-15	2.163E-15 1.742E-15 1.409E-15 1.145E-15 9.337E-16 6.277E-16 5.171E-16 4.272E-16
HOURS)= TEMP K	355 513 658 791 909	1012 1101 1179 1245	1431 1490 1535 1568 1568	1614 1629 1641 1650 1658 1668 1672 1675 1675	1680 1683 1684 1685 1685 1688 1688 1688
TIME (IN ALT KM	120 130 140 150	170 180 190 200 220	240 260 280 300 320	340 340 340 340 340 360 360 360 360	540 560 620 620 640 720

5.772E 03 5.706E 03 5.64 IE 03 5.578E 03	5.455E 03 5.396E 03 5.337E 03 5.279E 03	5.167E 03 5.112E 03 5.058E 03 5.005E 03	h.753E 03 h.634E 03 h.520E 03 h.409E 03	4.2016 03 4.102E 03 4.007E 03 3.916E 03	3.742E 03 3.659E 03 3.580E 03 3.504E 03	3.356E 03 3.287E 03 3.220E 03 3.154E 03
8.296E 05 7.930E 05 7.582E 05 7.25 IE 05 6.936E 05	6.637E 05 6.353E 05 6.082E 05 5.824E 05	5.345E 05 5.123E 05 4.910E 05 4.708E 05 4.242E 05	3.828E 05 3.459E 05 3.130E 05 2.835E 05 2.572E 05	2.336E 05 2.124E 05 1.934E 05 1.763E 05	1.470E 05 1.345E 05 1.232E 05 1.129E 05	9.520E 04 8.754E 04 8.059E 04 7.426E 04 6.849E 04
1.026E 07 8.575E 06 7.175E 06 6.009E 06 5.039E 06	4.229E 06 3.553E 06 2.988E 06 2.515E 06 2.119E 06	1.787E 06 1.509E 06 1.275E 06 1.078E 06 7.123E 05	4.730E 05 3.159E 05 2.121E 05 1.431E 05 9.708E 04	6.618E 04 4.534E 04 3.122E 04 2.159E 04 1.501E 04	1.048E 04 7.346E 03 5.174E 03 3.660E 03 2.600E 03	1.855E 03 1.329E 03 9.554E 02 6.898E 02 5.000E 02
1.070E 04 7.478E 03 5.239E 03 3.679E 03 2.588E 03	1.825E 03 1.289E 03 9.121E 02 6.468E 02 4.595E 02	3.271E 02 2.335E 02 1.667E 02 1.193E 02 5.212E 01	2.303E 01 1.028E 01 4.642E 00 2.117E 00 9.755E-01	4.541E-01 2.134E-01 1.013E-01 4.854E-02 2.347E-02	1.1466-02 5.641E-03 2.802E-03 1.404E-03 7.094E-04	3.615E-04 1.857E-04 9.615E-05 5.018E-05 2.639E-05
3.203E 05 2.341E 05 1.714E 05 1.258E 05 9.244E 04	6.806E 04 5.020E 04 3.709E 04 2.745E 04 2.035E 04	1.511E 04 1.124E 04 8.370E 03 6.246E 03	1.479£ 03 7.301£ 02 3.638£ 02 1.829£ 02 9.282£ 01	4.751E 01 2.453E 01 1.277E 01 6.706E 00	1.894E 00 1.018E 00 5.518E-01 3.013E-01	9.182E-02 5.124E-02 2.879E-02 1.629E-02 9.282E-03
15.50 15.33 15.16 14.98	14.58 14.36 14.12 13.88	13.33 13.04 12.73 12.41	10.64 9.71 8.82 7.99 7.24	6.60 6.06 5.61 5.25 4.96	4.55 4.55 4.30 4.21	4.15 4.09 4.05 4.01 3.98
115.1 117.0 119.1 121.2	125.9 128.6 131.4 134.5	141.6 145.6 149.9 154.7	185.3 205.7 229.6 256.8 286.9	319.0 352.1 385.0 416.7	473.9 498.8 521.2 541.3 559.4	575.8 590.7 604.5 617.3
2.663E-06 2.241E-06 1.892E-06 1.602E-06	1.159E-06 9.902E-07 8.490E-07 7.304E-07 6.306E-07	5.465E-07 4.754E-07 4.152E-07 3.641E-07 2.670E-07	2.011E-07 1.557E-07 1.236E-07 1.006E-07 8.369E-08	7.094E-08 6.111E-08 5.335E-08 4.709E-08	3.762E-08 3.395E-08 3.078E-08 2.802E-08	2.343E-08 2.150E-08 1.978E-08 1.822E-08
2.939E-16 2.447E-16 2.042E-16 1.707E-16	1.202E-16 1.012E-16 8.532E-17 7.211E-17 6.108E-17	5.1846-17 4.4106-17 3.7606-17 3.2146-17 2.1936-17	1.522E-17 1.076E-17 7.756E-18 5.717E-18	3.330E-18 2.633E-18 2.130E-18 1.759E-18	1.2676-18 1.1006-18 9.6646-19 8.5756-19 7.671E-19	6.909E-19 6.256E-19 5.691E-19 5.197E-19 4.760E-19
1689 1689 1690 1690 1690	1690 1690 1690 1690	1691 1691 1691 1691	1691 1691 1691 1691	1691 1691 1691 1691	1691 1691 1699 1699	1691 1691 1691 1691
740 760 780 800 820	840 860 880 920	940 960 980 1000 1050	1100 1150 1200 1250 1300	1350 1400 1450 1500	1600 1650 1700 1750	1850 1950 2000 2050

60							
N(H) /CM3	4.356E 04 2.930E 04 2.244E 04 1.847E 04	1.422E 04 1.299E 04 1.207E 04 1.136E 04	9.664E 03 9.167E 03 8.789E 03 8.490E 03 8.245E 03	8.038E 03 7.859E 03 7.700E 03 7.557E 03 7.426E 05	7.304E 03 7.190E 03 7.082E 03 6.979E 03	6.785E 03 6.693E 03 6.604E 03 6.518E 03	6.352E 03 6.272E 03 6.194E 03 6.117E 03
N(HE) /CM3	2.500E,07 1.553E 07 1.122E 07 8.809E 06 7.303E 06	6.287E 06 5.559E 06 5.013E 06 4.587E 06 3.963E 06	3.521E 06 3.187E 06 2.920E 06 2.700E 06	2.347E 06 2.202E 06 2.071E 06 1.952E 06	1.742E 06 1.649E 06 1.562E 06 1.481E 06 1.405E 06	1.334E 06 1.267E 06 1.204E 06 1.145E 06 1.089E 06	1.036E 06 9.863E 05 9.392E 05 8.947E 05
N(0) /CM3	7.600E 10 3.443E 10 1.971E 10 1.284E 10	6.773E 09 5.265E 09 4.210E 09 3.441E 09 2.408E 09	1.758E 09 1.320E 09 1.010E 09 7.84.1E 08 6.149E 08	4.861E 08 3.866E 08 3.091E 08 2.481E 08	1.6136 08 1.306E 08 1.060E 08 8.619E 07 7.021E 07	5.729E 07 4.682E 07 3.832E 07 3.141E 07 2.578E 07	2.119E 07 1.744E 07 1.437E 07 1.185E 07 9.790E 06
N(02) /CM3	1.200E 11 3.570E 10 1.501E 10 7.612E 09 4.348E 09	2.690E 09 1.761E 09 1.201E 09 8.446E 08	2.510E 08 1.469E 08 8.853E 07 5.446E 07	2.153E 07 1.375E 07 8.853E 06 5.737E 06 3.740E 06	2.449E 06 1.611E 06 1.064E 06 7.053E 05	3.129E 05 2.094E 05 1.405E 05 9.453E 04	4.313E 04 2.924E 04 1.988E 04 1.354E 04
1.6811E 01 N(N2) /CM3	5.800E 11 1.916E 11 8.698E 10 4.695E 10 2.827E 10	1.833E 10 1.252E 10 8.888E 09 6.490E 09 3.680E 09	2.207E 09 1.375E 09 8.791E 08 5.730E 08	2.534E 08 1.709E 08 1.161E 08 7.939E 07 5.455E 07	3.764E 07 2.608E 07 1.813E 07 1.264E 07 8.843E 06	6.203E 06 4.362E 06 3.076E 06 2.174E 06 1.540E 06	1.093E 06 7.779E 05 5.547E 05 3.964E 05 2.838E 05
INT GRAD= MEAN MOL WT	27.46 26.98 26.56 26.18 25.82	25.47 25.14 24.81 24.49 23.86	23.24 22.63 22.04 21.48 20.93	20.42 19.94 19.49 19.07	18.34 18.02 17.73 17.46	17.00 16.79 16.60 16.42	16.08 15.91 15.75 15.58
2703E-06, SCALE HT KM	11.4 16.8 21.9 26.7 31.1	35.0 38.5 41.7 44.6	54.0 57.9 61.5 64.8	70.8 73.5 76.2 78.8 81.2	83.5 85.7 87.8 89.8 91.8	93.6 95.4 97.1 98.8	102.2 103.9 105.6 107.4
soure Soure E/CM2	3.802E-02 1.856E-02 1.105E-02 7.322E-03 5.178E-03	3.825E-03 2.913E-03 2.270E-03 1.800E-03	8.009E-04 5.603E-04 4.008E-04 2.920E-04 2.159E-04	1.618E-04 1.226E-04 9.388E-05 7.253E-05 5.648E-05	4.430E-05 3.497E-05 2.77E-05 2.217E-05 1.779E-05	1.434E-05 1.160E-05 9.425E-06 7.685E-06	5.162E-06 4.251E-06 3.513E-06 2.911E-06 2.421E-06
* 18.000, COS(TH) DENSITY PRE GM/CM3 DYN	3.536E-11 1.172E-11 5.366E-12 2.929E-12 1.787E-12	1.176E-12 8.159E-13 5.890E-13 4.382E-13 2.589E-13	1.628E-13 1.069E-13 7.247E-14 5.041E-14 3.580E-14	2.587E-14 1.898E-14 1.411E-14 1.061E-14	6.1846-15 4.7846-15 3.7306-15 2.9286-15 2.3136-15	1.838E-15 1.468E-15 1.178E-15 9.493E-16 7.681E-16	6.237E-16 5.082E-16 4.153E-16 3.404E-16 2.798E-16
HOURS) =	355 5 14 658 787 900	997 1080 1150 1210 1305	1375 1427 1466 1496 1518	1536 1549 1560 1568 1575	1580 1584 1588 1590	1595 1596 1598 1599 1600	1601 1601 1602 1603
TIME (IN ALT KM	120 130 140 150	170 180 190 200 220	240 260 280 300 320	340 380 380 400	##0 ##0 #80 \$20	540 560 580 600	640 660 700 720

5.969E 03 5.898E 03 5.828E 03 5.759E 03	.625E .560E .496E .434E	5.312E 03 5.253E 03 5.195E 03 5.137E 03 4.998E 03	4.865E 03 4.737E 05 4.614E 03 4.495E 03	4.272E 03 4.166E 03 4.065E 03 3.967E 03 3.873E 03	3.782E 03 3.694E 03 3.609E 03 3.528E 03 3.449E 03	3.373E 03 3.299E 03 3.228E 03 3.159E 03
8.126E 05 7.749E 05 7.391E 05 7.051E 05	01101002400	5.115E 05 4.890E 05 4.677E 05 4.475E 05	3.599E 05 3.234E 05 2.911E 05 2.623E 05 2.367E 05	2.139E 05 1.936E 05 1.754E 05 1.591E 05	1.314E 05 1.196E 05 1.090E 05 9.949E 04 9.089E 04	8.313E 04 7.611E 04 6.975E 04 6.399E 04 5.877E 04
8.095E 06 6.702E 06 5.555E 06 4.609E 06 3.828E 06	3.183E 06 2.650E 06 2.208E 06 1.842E 06	1.285E 06 1.075E 06 9.006E 05 7.550E 05	3.1706 05 2.072E 05 1.362E 05 9.002E 04 5.982E 04	3.996E 04 2.684E 04 1.811E 04 1.229E 04 8.376E 03	5.737E 03 3.948E 03 2.730E 03 1.896E 03	9.267E 02 6.522E 02 4.609E 02 5.271E 02 2.330E 02
6.330E 03 4.342C 03 2.985E 03 2.057E 03	9.8296 02 6.8166 02 4.7366 02 3.2986 02 2.3016 02	1.609E 02 1.127E 02 7.908E 01 5.561E 01 2.325E 01	9.838E 00 4.210E 00 1.822E 00 7.970E-01 3.525E-01	1.576E-01 7.116E-02 3.246E-02 1.496E-02 6.961E-03	3.2716-03 1.5516-03 7.4256-04 3.5866-04 1.7486-04	8.593E-05 4.261E-05 2.131E-05 1.074E-05 5.462E-06
2.036E 05 1.464E 05 1.054E 05 7.609E 04 5.501E 04	3.985E 04 2.892E 04 2.103E 04 1.531E 04 1.117E 04	8.167E 03 5.979E 03 4.385E 03 3.222E 03 1.501E 03	7.069E 02 3.361E 02 1.614E 02 7.827E 01 3.831E 01	1.893E 01 9.435E 00 4.746E 00 2.408E 00 1.232E 00	6.359E-01 3.309E-01 1.736E-01 9.178E-02 4.891E-02	2.626E-02 1.421E-02 7.745E-03 4.252E-03 2.351E-03
15.23 15.04 14.83 14.62	14.14 13.88 13.60 13.30	12.65 12.30 11.93 11.56	9.60 8.66 7.78 7.02 6.37	5.83 5.40 5.06 4.80	4.43 4.31 4.21 4.08	4.04 4.00 3.97 3.94 3.92
111.2 113.3 115.5 117.9	123.3 126.3 129.7 133.3	141.7 146.6 151.8 157.6	194.9 219.2 246.9 277.5 309.9	342.7 374.8 405.1 433.1 458.3	480.8 500.7 518.4 534.3 548.6	561.7 573.9 585.3 596.3 606.8
2.019E-06 1.690E-06 1.419E-06 1.195E-06	8.576E-07 7.306E-07 6.249E-07 5.367E-07 4.630E-07	4.011E-07 3.491E-07 3.053E-07 2.683E-07 1.984E-07	1.512E-07 1.187E-07 9.573E-08 7.908E-08 6.669E-08	5.720E-08 4.976E-08 4.377E-08 3.885E-08	3.1226-08 2.8206-08 2.5566-08 2.3256-08 2.1206-08	1.937E-08 1.774E-08 1.627E-08 1.495E-08
2.306E-16 1.905E-16 1.578E-16 1.31CE-16	9.088E-17 7.597E-17 6.366E-17 5.347E-17 4.502E-17	3.800E-17 3.216E-17 2.730E-17 2.323E-17 1.573E-17	1.088E-17 7.696E-18 5.583E-18 4.158E-18 3.182E-18	2.500E-18 2.014E-18 1.660E-18 1.396E-18	1.037E-18 9.103E-19 8.070E-19 7.209E-19 6.481E-19	5.856E-19 5.312E-19 4.836E-19 4.415E-19
1604 1604 1604 1605 1605	1605 1605 1605 1605	1606 1606 1606 1606	1606 1606 1606 1606	1606 1606 1606 1606	1606 1606 1606 1606	1606 1606 1606 1606
740 760 780 800 820	840 860 880 900	940 960 980 1000 1050	1100 1150 1200 1250	1350 1400 1450 1500 1550	1600 1650 1700 1750 1800	1850 1900 1950 2000 2050

N(H)		2.926E 04				10 3444-1					1.0066 04		9.228E 03				8.507E 03	•330E	. 170E	.024⊡	3888	.760E	.638E	-522E	7.410E 05	.302E	7.197E 03				11	6.715E US				
NCHE) /CM3	2.500E u7	1.5516 07				6.380E 66					90 49	303€	3.032E 06	80 SE	610E		2.438E 06					79 1E	3069	596E	1.508E 06	42.6E	1.349E 06	277E	209E	145E	085E	1.029E 06	760E	259E	78 7E	342E
N(0) /CM3		3.440E 10				ထ	.331E	4.267E 09	.487E	•435E			1.004E 09				4.685E 08					-454E	.160E	.277E	7.431E 07	.962E	.792	.857E	0.4E	300€	.028E	1.642E 07			-11	14.8
N(02)		3.569E 10				.708E 0	.769E 0	1.203E 09	.427E 0	.406E 0	30 th	10年	8.293E 07	99 1E	045E		37.8E	168E 0	314E U	507E 0	0	.854E 0	.183E 0	.581E 0	4.873E 05	. 143E 0	2.033E 05	.319E		.598E	.662E	2.402E 04		1.041E 04		
1.6947E 01 N(N2) /CM3	800E	1.915E 11	. 717E	. 720E	-848€	848E	261E	8.930E 09	500E	652E	.165E	.329E	8.357E 08	.346E	3494		.266E	3464.	3606.	.607E	4.425E 07				9.230E 06		.292	.938E	113	.387E	.564E	0	0	3.179E 05	0	О
INT GRAD# MEAN MOL WT	27.46	26.98	26.56	26.18	25.82	₹.		24.79		æ			21.90				.2	~	~	ω,	18.42	18.07	17.75	17.46	17.20	16.96	16.74	16.54	16.34	16.16	15.98			15.43		
SCALE HT KM	4-11	16.8	21.9	26.6	30.7			40.7		•	52.0	5.5	58.7	61.7	64.5	)	67.2	2.69	72.2	74.5	76.8	4			84.7				91.5		-	4.96	98.1	60.66	101.8	103.8
COS(TH) = 2.58 PRESSURE CYNE/CM2	-02	1.858E-02	06E-0	19E-0	0	.797E-0	878F-0		.758E-0	35E-0	-611E-	247F-	97E	-452E-	-932F-	;	.426E-	-064E-	-3050	-3411	4.6946-05		826F	214F-	1.7446-05	-380E-	1.098E-05	.769E-0	7.033E-06	.663E-0	.576E-0	•	.022E-0	2.469E-06	.025E-0	.667E-0
19.000, C DENSITY	3-534E-11				1.800E-12	1856-1	222F-1	927E-1	.398E-1	2.5805-13	1-607E-13	1.0466-14	6.998F-14	4.8061-14	3- 568F-14		2.401E-14	1.737E-14	1.274E-14	9.449F-15	7.084E-15	3635-1	1-3400	1516-1	2-442E-15	1.9046-15	74E-1	78E-1	9.333E-16	26E-1	32E-1	.756E-1	.826E-1	3.087E-16	1-366 h.	24\028E-16
HOURS)		5. S.	657	783	890	981	1058	1122	1176	1259	1319	1341	1301	41 41	14.30	2	1442	1451	1458	1464	1468	14.71	1473	1475	1477	1478	1480	1481	1481	1482	1483	1483	1483	1841	1484	1841
TIME (IN ALT KM	06.	130	071	150	160	170	0 6 1	000	200	220	240	240	280	300	300	3	340	360	380	001	420	č	0 4 4	200	005	520	240	260	580	900	620	049	660	980	700	720

6.285E 03 6.204E 03 6.125E 03 6.047E 03 5.971E 03	5.896E 03 5.823E 03 5.751E 03 5.681E 03 5.611E 03	5.543E 03 5.477E 03 5.411E 03 5.347E 03 5.191E 03	5.041E 03 4.898E 03 4.760E 03 4.628E 03 4.502E 03	4.380E 03 4.263E 03 4.151E 03 4.043E 03 3.940E 03	3.840E 03 3.744E 03 5.651E 03 5.562E 03 3.476E 03	5.593E 03 5.313E 03 3.236E 03 3.162E 03 3.090E 03
7.923E 05 7.526E 05 7.152E 05 6.798E 05 6.464E 05	6.148E 05 5.849E 05 5.567E 05 5.299E 05 5.046E 05	4.806E 05 4.579E 05 4.364E 05 4.160E 05 3.695E 05	3.287E 05 2.929E 05 2.614E 05 2.336E 05 2.091E 05	1.874E 05 1.682E 05 1.512E 05 1.361E 05 1.226E 05	1.107E 05 9.999E 04 9.046E 04 8.194E 04 7.431E 04	6.747E 04 6.134E 04 5.582E 04 5.086E 04
5.814E 06 4.741E 06 3.871E 06 3.164E 06 2.589E 06	2.122E 06 1.740E 06 1.429E 06 1.175E 06	7.964E 05 6.568E 05 5.423E 05 4.482E 05 2.795E 05	1.755E 05 1.108E 05 7.043E 04 4.502E 04 2.895E 04	1.872E 04 1.217E 04 7.960E 03 5.233E 03 3.459E 03	2.298E 03 1.535E 03 1.030E 03 6.945E 02 4.707E 02	3.205E 02 2.192E 02 1.507E 02 1.040E 02 7.210E 01
3.027E 03 2.015E 03 1.344E 03 8.990E 02 6.026E 02	4.048E 02 2.726E 02 1.839E 02 1.244E 02 8.432E 01	5.727E 01 3.898E 01 2.659E 01 1.818E 01 7.084E 00	2.796E 00 1.117E 00 4.520E-01 1.850E-01 7.662E-02	3.209E-02 1.359E-02 5.822E-03 2.520E-03 1.103E-03	4.874E-04 2.177E-04 9.819E-05 4.473E-05	9.551E-06 4.476E-06 2.116E-06 1.010E-06 4.861E-07
1.077E 05 7.544E 04 5.293E 04 3.721E 04 2.621E 04	1.850E 04 1.309E 04 9.274E 03 6.584E 03	3.338E 03 2.383E 03 1.705E 03 1.222E 03 5.354E 02	2.372E 02 1.062E 02 4.809E 01 2.199E 01	4.743E 00 2.236E 00 1.064E 00 5.111E-01 2.478E-01	1.212E-01 5.985E-02 2.980E-02 1.497E-02 7.583E-03	3.873E-03 1.994E-03 1.035E-03 5.4 14E-04 2.854E-04
14.80 14.56 14.30 14.02 13.72	13.40 13.06 12.70 12.32	11.51 11.08 10.65 10.22 9.14	8.14 7.25 6.50 5.88 5.40	5.03 4.75 4.53 4.37	900 7 7 00 3 7 7 8	3.93 3.91 3.89 3.87 3.85
106.0 108.3 110.9 113.8	120.4 124.2 128.5 133.2	144.2 150.5 157.4 165.0	212.8 242.2 273.8 306.3	367.9 394.9 418.8 439.7 457.9	473.9 487.9 500.6 512.2 522.9	533.1 542.9 552.4 561.8 571.1
1.377E-06 1.143E-06 9.522E-07 7.969E-07 6.700E-07	5.660E-07 4.806E-07 4.102E-07 3.520E-07 3.038E-07	2.637E-07 2.302E-07 2.021E-07 1.785E-07 1.343E-07	1.045E-07 8.381E-08 6.902E-08 5.808E-08 4.973E-08	4.316E-08 3.786E-08 3.348E-08 2.980E-08 2.666E-08	2.395E-08 2.158E-08 1.951E-08 1.767E-08	1.460E-08 1.330E-08 1.214E-08 1.110E-08
1.651E-16 1.348E-16 1.103E-16 9.050E-17 7.446E-17	6.143E-17 5.083E-17 4.218E-17 3.511E-17 2.932E-17	2.456E-17 2.065E-17 1.743E-17 1.477E-17 9.938E-18	6.883E-18 4.918E-18 3.630E-18 2.767E-18 2.175E-18	1.757E-18 1.455E-18 1.229E-18 1.055E-18 9.178E-19	8.068E-19 7.150E-19 6.378E-19 5.718E-19 5.147E-19	4.649E-19 4.211E-19 3.823E-19 3.478E-19 3.170E-19
1485 1485 1485 1485 1485	1485 1486 1486 1486	1486 1486 1486 1486 1486	1486 1486 1486 1486	1486 1486 1486 1486 1486	14 86 14 86 14 86 14 86	14.86 14.86 14.86 14.86
740 760 780 800 820	840 860 900 920	940 960 980 1000 1050	1100 1150 1200 1250 1300	1350 1400 1450 1500 1550	1600 1650 1700 1750 1800	1850 1900 1950 2000 2050

3	2 11 2 2	5 2 2	4.356E 04	.924E	.252E	.870E	• 6 30E	4 6 8 E	.352E	1.267E 04	201E	.107E	3440 <b>-</b>	3044.	9.642E 05	.362E	. 127E		8.924E 03	.742E	.577E	.423E	•279E	.142E	.011E	.885E	7.763E 03	.645E	7.530E 05	1 × 1	-310E	.204E	. 101E	7.000E 03	300.	3408	.709E	.617E
2	71111	C R J .	2.500E 07	3	0	Ç	0	.478E	₹770E	5.236E 06	.818E	. 199E			3.132E 06				2.510E 06					.821E	.714E	.613E	1.520E 06	• 433E	1.35 1E 06	.275E	.203E	. 136E	•073E	1.014E 06	286E	065E	576E	115E
6		C E 3 /	7.600E 10					.925E	395E	4.319E 09	.528E	•456E	.776E	-316E	9.912E 08	.551E	-800E	,	.482	.480E	113	.121E	.663E	37E	362	22E	6.420E 07	33E	4.031E 07	32E	# <b>7</b> E	29E	19E	1.293E 07	.035E	289E	3649°	-340E
10071	1 70 IN	CM)	1.200E 11	.56.BE	.508E		3404°	722E	775E	1.202E 09	382E	328E	360E	333E	7.715E 07	54 JE	707F	) }	659	883€	033E	702E	2.283E 06	. 413E	. 785E	.480E	3.430E 05	.154E	1.357E 05	.571E	431E	451E	199E	.405E 0	.002E 0	5.782E 03	.724E 0	. 405E 0
1.7067E 01	7211	/CM3	BOOE	9.15E	740E	4.745E 10	867E	-860E	.268F	10	.493E	•612E	. 113E	277F	7.891E 08	953E	1456	,	015E	300E	430E	495E	3.597E 07	363E	558E	031E	6.837E 06	38 †S	3.034E 06	.029E	ш	• 148E	.165E	4.164E 05	.820E		.302E	.875E
INT GRAD=	Z Z		≠.	٥.	S	26.18	25.81	25.45	25.11	24.76	24.42	23.74	23.06	22.40	21.75	21.13	20.54		٥.		19.00	9	18.18	•			16.97	•	16.52	16.32	16.12	15.93	15.73	15.54	15.33	15.11	14.88	14.63
1000E-01,			<b>7.</b> -	16.9	21.9	26.4	30.4	9.55	37.0	30.7	42.2	46.5	50.1	4.8.8	56.4	50.1	4	•	64.3	66.8	69.1	71.3	73.4	75.4	77.3	79.1	80.9	82.5	- 3	9	87.3	ဆ	0	92.3	7.40	0.96	98.1	100.3
S(TH)= 5.	SSURE	E/CM2	02E-	-36S	07E-	7.308E-03	5.136E-03	76.45	A A B E - O	1875	713E-0	0	-217E-	-9005	3-407F-04	-30UT	7315-		-260E-	-290E-	920E-	204F-	3.947E-05	-917E-	322E-0	798E-0	1.400E-05	0-3960.	.624E-	-815E-	•	-311E-	450E-	.772E-0	.236E-0	1.812E-06	.474E-0	.205E-0
= 20.000,	DENSITY	GM/CM3	3.536E-11	1.171E-11	5.391E-12	2.960E-12	1.813E-12	1. 1όμΕ-12	8 272E-13	5.9516-13	4.4036-13	2.563E-13	1.580F-13	1 015E-13	6.718F-14	11 -5555-11	7 15 15 - 15	3.1316-14	2.217E-14	7			6.231E-15	4-663F-15	3.521F-15	2.679E-15	2.054E-15	1.585E-15	_	Ξ	-	=	4.677E-16	.709E-1	.952E-1	358E	.888E-1	.517E-1
	LEMP	*	355	515	656	777	880	945	10.26	200	1143	1216	1267	1202	1327	1388	1257	1001	1366	1373	1378	1382	1385	1387	1389	1391	1392	1393	1394	1361	1395	1395	1396	1396	1397	1397	1397	1397
TIME (IN	ALT	¥	120	130	071	150	160	170	9 0	001	200	220	240	046	000	200	000	076	340	360	380	004	#50 #50	OTH	1	0.04	200	520	940	260	580	900	620	049	999	989	200	720

6.526E 03 6.437E 03 6.350E 03 6.264E 03 6.181E 03	6.099E 03 6.018E 03 5.939E 03 5.862E 03 5.786E 03	5.712E 03 5.639E 03 5.567E 03 5.497E 03 5.326E 03	5.163E 03 5.008E 03 4.858E 03 4.716E 03	4.447E 03 4.322E 03 4.201E 03 4.085E 03	3.867E 03 3.764E 03 3.665E 03 3.570E 03	3.591E 03 3.306E 03 3.224E 05 3.145E 03
7.682E 05 7.275E 05 6.891E 05 6.530E 05 6.190E 05	5.869E 05 5.566E 05 5.281E 05 5.012E 05 4.758E 05	4.518E 05 4.292E 05 4.078E 05 3.875E 05 3.417E 05	3.018E 05 2.670E 05 2.365E 05 2.099E 05 1.866E 05	1.661E 05 1.481E 05 1.322E 05 1.182E 05 1.059E 05	9.492E 04 8.522E 04 7.662E 04 6.898E 04	5.612E 04 5.071E 04 4.588E 04 4.156E 04 3.769E 04
4.294E 06 3.458E 06 2.788E 06 2.250E 06 1.819E 06	1.472E 06 1.192E 06 9.672E 05 7.854E 05 6.386E 05	5.198E 05 4.235E 05 3.455E 05 2.822E 05 1.709E 05	1.042E 05 6.396E 04 3.951E 04 2.456E 04 1.536E 04	9.668E 03 6.121E 03 3.898E 03 2.496E 03 1.608E 03	1.041E 03 6.780E 02 4.438E 02 2.921E 02 1.932E 02	1.284E 02 8.579E 01 5.759E 01 3.885E 01 2.632E 01
1.557E 03 1.010E 03 6.573E 02 4.287E 02 2.803E 02	1.837E 02 1.207E 02 7.946E 01 5.244E 01	2.300E 01 1.529E 01 1.018E 01 6.796E 00 2.497E 00	9.302E-01 3.511E-01 1.342E-01 5.196E-02 2.036E-02	8.079E-03 3.244E-03 1.318E-03 5.414E-04 2.249E-04	9.450E-05 4.013E-05 1.723E-05 7.471E-06 3.274E-06	1.449E-06 6.476E-07 2.923E-07 1.332E-07 6.124E-08
6.065E 04 4.153E 04 2.850E 04 1.960E 04 1.351E 04	9.332E 03 6.459E 03 4.480E 03 3.113E 03 2.168E 03	1.513E 03 1.058E 03 7.410E 02 5.201E 02 2.165E 02	9.116E 01 3.883E 01 1.673E 01 7.288E 00 5.209E 00	1.428E 00 6.423E-01 2.918E-01 1.339E-01 6.206E-02	2.904E-02 1.372E-02 6.541E-03 3.147E-03	7.483E-04 3.697E-04 1.842E-04 9.253E-05 4.687E-05
14.36 14.06 13.74 13.40 13.03	12.64 12.23 11.79 11.35	10.42 9.95 9.49 9.03 7.96	7.03 6.27 5.66 5.20 4.85	4.59 4.41 4.27 4.17	# 03 3 99 3 95 8 95 8 90 9 90	3.88 3.86 3.84 3.82
102.8 105.6 108.6 112.0	120.1 124.9 130.2 136.1	149.9 157.8 166.4 175.8 202.1	231.8 263.7 295.8 326.4 354.4	379.1 400.4 418.7 434.5	460.3 471.2 481.3 490.9 500.1	509.0 517.9 526.7 535.5 544.4
9.896E-07 8.167E-07 6.776E-07 5.652E-07	4.002E-07 3.399E-07 2.906E-07 2.500E-07 2.166E-07	1.889E-07 1.659E-07 1.466E-07 1.304E-07	7.937E-08 6.484E-08 5.422E-08 4.617E-08 3.986E-08	3.4786-08 3.0606-08 2.7086-08 2.4096-08	1.927E-08 1.731E-08 1.558E-08 1.406E-08	1.151E-08 1.044E-08 9.488E-09 8.636E-09 7.872E-09
1.223E-16 9.884E-17 8.013E-17 6.517E-17	4.352E-17 3.575E-17 2.948E-17 2.440E-17	1.692E-17 1.419E-17 1.196E-17 1.013E-17 6.848E-18	4.801E-18 3.495E-18 2.640E-18 2.064E-18 1.663E-18	1,374E-18 1,159E-18 9,939E-19 8,630E-19 7,565E-19	6.682E-19 5.936E-19 5.298E-19 4.745E-19	3.839E-19 3.465E-19 3.134E-19 2.839E-19 2.576E-19
1398 1398 1398 1398	1398 1398 1398 1398	1399 1399 1399 1399	1599 1399 1399 1399	1399 1399 1399 1399	1399 1399 1399 1399	1399 1399 1399 1399 1399
740 760 780 800 820	8 & CO 8 & CO 9 & CO 9 & CO	940 960 980 1000 1050	1100 1150 1250 1350	1350 1400 1450 1500 1550	1600 1650 1700 1750	1850 1960 1950 2000 2050

66

N 6	3 6	03	03	,	03	2 0	0 0	מי מ	3	0.3	03	03	03	03	20	2 5	3 6	3 6	3 8	C.	03	50	200	0.5	0.5	03	03	03	03	03	03	S	03	03	03
 6.723E		0 1 1	.350		6.261E		200	000	. 72.	448.	.766	5.689E	.613	• 430	25.4	007.	200	4.738E	7 22	200	4.492E	.359	.251	901	066	.878	- 769	3.665E	.565	69ħ.	.577	.288	3.203E	. 121	-042
39E 05	2 4 4 5 5	71E 0	28E 0		05E 05	ייני מיני	יי מינו	ם מיני מיני	ם מ	7E 0	3E 0	822E 05	3E 0	3E 0	C U	יי מע	יי מיי	133E 03	ם היי	ii N	486E 05	o :	O (	о : ::::	o ui	ĐĘ	<b>9</b> 6	586E 04	7	3	9 E	7E	840E 04	핃	3E
- N	•				2.60	•		•					•			•	•	- 0	•		7.		•	•		•		6.5	•	•	_	~	3.8	₹.	Ξ.
90	2 6	3 8	90		90	5 5	5	<u>0</u> 6	S	9	90	05	9	90	ä	3 3	Šē	į	5 6	S	03	03	03	03	05	05	02	05	02	10		_	5		
3.2516	, 14 C	2 4 4	317		1.054E	150	080.	707	00.	.528	.845	2.297E	.856	•095		200	20.40	1 1211	177.	· 0.	.340	3.302E	450	-285	.093	.125	.264	2-090E	.346	-71¢	672	711	2-440E	.613	.071
05	2 0	200	02		0	0 5	- :	5 5	5	0	0	00	0	9	¢	?	? ?	700	ף כ	7	-03	٩	9	9	၀	٩	9	90-	9	9	ç	ç	-08	9	Ŷ
8.496E	27.5	180	004		8.977E	02.	82.	704.	.000	•		4.284E	•	•		4585	71.47	4.0100	100	7717	361	.997E	• 488E	.369E	• 434E	. 18	86	3.643E	.51	•35	4	7	5.005E	Ξ.	9.672E
<del>1</del> 0	<b>1</b> 6	† †	03		03	0.3	03	03	ŝ	05	05	05	02	5				2 6			9	-01	9	9	9	- 1	ı	- 1		10-	70	-05	-05	-05	E-06
591E	714	200	101		017E	107	319	, a	- 0	402	080	376T	<b>#</b> 08	577	i.	22	7 0	485E	2 2	7	872E	102E	169E	042E	800E	960	680	688E	822	658	7.27	224	. 952E	916	370
พี่เ	•				Š.	٠,	7	<b>.</b> ,	-	_	'n	3.	5	•	,	'n.	<b>:</b> ,	• (	• •	<u>:</u>	#	8	o.	<b>.</b>	÷	8	*	· -	7	3.	_	α	M	_	ò
13.90	, .	0.0	2.3		11.87	M (	Φ.	10.0			٥.	8.47	0	٥.		6.22	70.0	5.12	- (	4.52	×	4.21	Ξ.	਼		٥,	•		Θ.	3.86	α	0	, α	~	3.76
101.0	* * * * * * * * * * * * * * * * * * *	•	9		121.7	~	~	- (	•	57.	,	77.	88	217.5	(	• •	· .	311.0	ģ:	-	381.2	398.0	•			5	75	63	72	480.7			506.2		523.8
107E-07	745-0	10 E E E E	٩		984E-07	4 1E-0	80E-0	0	42E-0	4 JE-0	74E-0	134E-07	16E-0	35E-0		0	)   	4 76E-08	? (		907E-0	557E	261E-0	006E-0	786E-0	94F-0	27F-0	80E	50E-0	035E-08			639F-09	0	291E-09
7	•	•					٠	•						~		•	•	# 1	•	•	•	~	•	•	٠		•			-					•
7.318E-17		_			5.204E-17	-9619°	.151E-	-775E-	.472E-					5.047E-18		.602E-1	.681E-1	. 073E-18	-05/E-1	.361E-1	. 142E-1	-749E-19	.427E-1	.353E-1	.463E-1	712F-1	770E-1	146-1	34F-1	3.613E-19	21,25-1	0156-1	625F-	368F-1	140E-1
٠.	_	~ -	,	1	,,,	•	••									י ניאו			_ '	_		•	æ	_	•										
1329	1329	1329	1329		1329	1329	1330	1330	1330	1330	1330	1330	1330	1330		1330	1330	1350	1330	1330	1330	1330	1330	1330	1330	1330	1220	02.51	1330	1330	7 2	2 2	יי ב	2 2	1330
740	<b>•</b>	$\infty$ $<$	$\sim$		940	ø	Ø	006	2	- 2	٠.	σ		1050		1100	1150	1200	1250	30	1350	1400	1450	1500	1550	1400	2014	1400	1750	1800			1050	2000	2050

H	/CM3		-356E	-924€	.268E	1.901E 04	.671E	L.	, ,	•	11.	-264E	• 175E	.114E	.070E	1.035E 04	.007E	1 11	3170-	605E	408F	227E	1440	8.894E 03	8.759E 03	-589E	-445E	.305E	.170E	.037E	3606°	33E	3199.	1541	4246	3105	1986	מאמו.	6.982E 03
N HE	/CM3				_	9.057E 06	7.658E 06	_		3. YO E UO				-949E	-589E	3.290E 06	035F	1100 1100		.612E	4.4.32F	267E	1175	1.978E 06	1.850E U6	-732E	• 622E	. 520E	. 425E	.337E	.255E		.106E	1.039E 06	Щ	u.	Į U	щ	7.658E US
(5)N	,(CM3					1.315E 10	9.589E 09	0.42F		40 DC0C*C	170 T	287E	475E	58E	30E	9.552E 08	4 3 F	1 0 0	200					1.388E 08	1.067E 08	225E	350E	911E	805E	2.953E 07	366	B78	193E □	388C	•511E	-666F	223F	107E	3.231E 06
10078	/CM3					7.762E 09	60 ∃ካከከ•ክ	738F	1000	1011104	- 1 h	•217E	. 131E			6.629E 07				.237t	3061 -	203E	109H	1.457E 06	8.634E 05	• 136E	.067E	-837E	• 104E			2.446E 04		9.089E 03	566E 0	118F 0	105F 0	O HOOK	8.055E 02
1.7229E 01	/CM3		300E	916E	792E	4.793E 10	ш			01 3417*1				mr	641	6.977E 08	i.	171	ı	€00E	31 TO	209E	8065	2.455E 07	1.552E 07	-848⊡	-268E	•002E	.563E	9949-	3090•	6.843E 05	.431E	-876E	.872E	.221F	990F	200E	3.445E 04
INT GRAD=			27.46	26.98	26.56	26.17	25.80	ď	,	00.62	÷.	;	ň	22.88	22,17	21.47	20.81	a. 00	20.10	19.61	19.08	18.60	18.17	17.79	17.45	17.14	16.87	16.62	16.39	16.17				15.29	0	7	=		13.83
.6602E-01,	H K		<b>†</b>	16.9	21.7	26.0	29.6	32.8		0.00	28.0	40.2	43.9	~	0	52.8	LC	۱ ۱	-	60.2	62.5	7-49	7.49	68.7	70.5	72.2	73.9	75.5	77.0	78.6	_	81.7			87.0	89.1	7-10	0 10	6.96
S(TH) = 8,			)2E-	50E-	-39C	7.265E-03	5.070E-03	AOF.	1 1	Z* I 4 I E - U.S	9.5E-	20E-0	07E-0	2	3E-	2.917E-04	7	7 L	- 20	0	32F-	7E-	1 6	2.918E-05	2.189E-05	54E-	8	25E-	04E-	5.726E-06	-450E-	₹.	-727E-	-151E-	.705	-358E-	-088E-	760F-	7.111E-07
: 22.000, CC	GM/CM3		3.536E-11	1.172E-11	5.4245-12	2.991E-12	1.8346-12	1.2065-12	1000	0.3306-13	5.759E-15	4.377E-13	2.503E-13	1.512E-13	9.492E-14	6.139E-14	4.068F-14	2 75.25-11	#1-37C) *7	1.895E-14	1.326E-14	9-4145-15	6.770F-15	4.925E-15	3.619E-15	2.685E-15	2.008E-15	1.512E-15	1.1476-15	8.745E-16	6.704E-16	5.164E-16	3.995E-16	3.103E-16	2.419E-16	1.893E-16	1.487E-16	1 1725-16	9.271E-17
N HOURS)		:	355	515	651	765	858	933	100	***	5401	1083	1143	1182	1209	1227	1240	1210	4471	1255	1260	1263	1266	1268	1269	1270	1271	1272	1273	1273	1274	1274	12.74	1275	1275	1275	1275	1276	1276
TIME (II	. Y	,	120	130	071	150	160	170			0.5	200	220	240	260	280	300	200	920	340	360	380	004	# 50	011	094	180	200	520	240	260	580	900	620	049	660	089	700	720

6.877E 03 6.775E 03 6.674E 03 6.576E 03 6.480E 03	6.386E 03 6.294E 03 6.204E 03 6.116E 03 6.029E 03	5.944E 03 5.861E 03 5.779E 03 5.699E 03	5.322E 03 5.146E 03 4.979E 03 4.818E 03 4.666E 03	4.519E 03 4.579E 03 4.246E 03 4.117E 05	3.87FE 03 3.764E 03 3.656E 03 3.553E 03 3.453E 03	3.357E 03 3.266E 03 5.177E 03 3.092E 03
7.211E 05 6.794E 05 6.403E 05 6.036E 05	5.370E 05 5.068E 05 4.784E 05 4.518E 05 4.268E 05	4.055E U5 3.812E 05 3.604E 05 3.409E 05 2.970E U5	2.592E 05 2.266E 05 1.985E 05 1.742E 05 1.531E 05	1.348E 05 1.188E 05 1.050E 05 9.286E 04 8.227E 04	7.301E 04 6.488E 04 5.774E 04 5.146E 04 4.593E 04	4.105E 04 3.674E 04 3.293E 04 2.955E 04 2.655E 04
2.545E 06 2.007E 06 1.546E 06 1.254E 06 9.935E 05	7.877E 05 6.255E 05 4.973E 05 3.959E 05 3.156E 05	2.519E 05 2.013E 05 1.611E 05 1.290E 05 7.450E 04	4.333E 04 2.539E 04 1.498E 04 8.898E 03 5.322E 03	3.205E 03 1.942E 03 1.185E 03 7.273E 02 4.492E 02	2.791E 02 1.745E 02 1.097E 02 6.935E 01 4.410E 01	2.820E 01 1.815E 01 1.171E 01 7.610E 00
5.003E 02 5.116E 02 1.946E 02 1.219E 02 7.651E 01	3.040E 01 3.040E 01 1.924E 01 1.220E 01 7.761E 00	4.948E 00 2.162E 00 2.026E 00 1.301E 00 4.347E-01	1.474E-01 5.068E-02 1.768E-02 6.252E-03 2.24 IE-03	8.141E-04 2.996E-04 1.117E-04 4.216E-05	6.232E-06 2.439E-06 9.657E-07 3.868E-07	6.415E-08 2.655E-08 1.111E-08 4.696E-09 2.005E-09
2.270E 04 1.499E 04 9.929E 03 6.590E 03	2,923E 03 1,953E 03 1,508E 03 8,783E 02 5,909E 02	3.984E 02 2.692E 02 1.823E 02 1.237E 02 4.736E 01	1.837E 01 7.212E 00 2.868E 00 1.154E 00	1.936E-01 8.068E-02 3.400E-02 1.449E-02 6.238E-03	2.715E-03 1.194E-03 5.306E-04 2.481E-04 1.079E-04	4.947E-05 2.280E-05 1.063E-05 5.002E-06 2.374E-06
13.45 13.05 12.61 12.14 11.66	11.15 10.63 9.59	8.58 8.11 7.66 7.25 6.36	5.66 5.15 4.78 4.52	4.20 4.04 3.999 3.95	3.92 3.83 3.83 3.83 8.85	3.78 3.78 3.76 3.74
100.2 103.4 108.1 112.9	124.4 131.1 138.7 147.1	176.1 176.7 188.0 199.9 231.1	262.9 293.0 319.9 343.0 362.5	378.7 392.3 404.1 414.5	432.7 441.1 449.3 457.5	473.8 482.2 490.8 499.5 508.5
5.804E-07 4.771E-07 3.950E-07 3.296E-07	2.350E-07 2.009E-07 1.732E-07 1.506E-07	1.166E-07 1.037E-07 9.293E-08 8.382E-08 6.643E-08	5.4246-08 4.5316-08 3.8496-08 3.3166-08	2.5116-08 2.2056-08 1.9456-08 1.7226-08	1.3606-08 1.2136-08 1.0846-08 9.7066-09 8.7106-09	7.830E-09 7.053E-09 6.364E-09 5.752E-09
7.361E-17 5.866E-17 4.694E-17 3.772E-17 3.044E-17	2.469E-17 2.013E-17 1.650E-17 1.360E-17 1.128E-17	9.4236-18 7.9236-18 6.7106-18 5.7246-18 3.9776-18	2.8946-18 2.1986-18 1.7336-18 1.4086-18		5.016E-19 4.443E-19 3.947E-19 3.516E-19 3.138E-19	2.8066-19 2.5146-19 2.2566-19 2.0276-19 1.8256-19
	1277 1277 1277 1277 1277	1277 1277 1277 1277 1277	12.77 12.77 12.77 12.77	1277 1277 1277 1277	1277 1277 1277 1277 1271	1277 1277 1277 1277
740 760 780 800 820	840 840 880 900	940 960 980 1000 1050	1100 1150 1200 1250	1350 1400 1450 1500	1600 1650 1700 1750	1850 1900 1950 2000 2050

N(H) /CM3	4.356E 04				40 31 45 -			-242E 04	1. 1	7.7.1	10 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	1000	11	100 pt 0t	,					9.117E 03			7 1 L	1985	.355E 03		0817	3646	820E	.694€ 03	7.1E	1 11 12	I II	18E	.106E 03
N(HE)	. ~ ~	20	90	30	715 06 1	3E 06	1 90 36t	5.129E 06 1	J <del>t</del> E	0.046	45 PE 00	31.45 04	00 00 000	8':0F 06 1		643E 06	456E 06	285E 06	7€ U.6	90	70 E 10 4	7325 06 3	618F 06 B	514E 06 8	416E 06 8	8 90	0.6	2 90	06	90	7 50	50	50	05	
N(0)	10 2	2 2	2 (	ŝ	60	60	60	60.5E .09 5.	60 ⊒	7.55 00	2725 00	248C 08	0.450	181F 08 2.1	•	91E 08	35E 08 2	21E 08 2	.686E 08 2.	282E 08 1	705 07	73F 07	.722E 07 1.	896 07 1	72E 07	07	0.7	07	07	_	90	582E 06	344E 06	.385E 06 7.	642E 06
/N(.02.) /GM3.	11 7	5216 10 2	791E 09 1	40/12/04	739E 09 1	768E 09	182E 09 4	8.106E 08 5	123E 08 2	55.08	80 45	56 07 0	0 to	1-929E 07 5		095E 07 3	255E 06 2	595E 06 2	077E 06 1	205E 06 1	0.50	20	2.412E 05 5	0.5	\$ 40	986E 04 2	968E 04 2	772E 04	061E 04 1	376E 03 9	842E 03 7	322E 03 5	408E 03 4	560E 02 3	219E 02 2
.7265E 01 N(N2) /CM3	5.800E 11 1	01	2 2	2	01	10	60	6.365E 09 8	60	.926E 09	1145 09	.571F 0A	-928F 08	.371E 08		• 443E 08	*833E 07	*437E 07	.362E	.087E 07	300F 07	131E 06	5.100E 06 2	209E 06	026E 06	90	50	.182E 05 1.	50 :	50	359E 05	742E 04	640E 04	** 40 3849	365E 04
INT GRAD= 1 MEAN MOL WT	27.46 5 26.98 1	.0.				<b>70</b>	.67	24.30	55	. 80	. 06	35 6	67	20.04		19.45	92	<b>*</b> * *	02	<del>1</del> 9	30	00	16.73 5	64	25	.03	.81	58	.35	01.	.83	•53	.21	13.85 3.	94.
93E-01, SCALE HT. KM	1.1.4	21.6	9,0	1	32.3	34.9	37.2	39.3	42.4	46.0	6.84	51.6	54.1	56.5		58.9	61.1	63.2	65.2	67.1	689	70.5	72.1	73.7	75.2	7.6.7		•			85.5	87.7	90.3	93.1	ħ•96
0S(TH)= 9.65 PRESSURE DYNE/CM2	3.802E-02 1.860E-02	04E-0	30E-0	) 	6.35E-	- 700E-	-046E-		•040E-	181E-	-3950.	.724E-	-865E-	.2		185E-0	-580E-0	• 769E-0	493E-	.581E-0	-923E-0	.443E-0	1.091E-05	.290E-0	.337E-0	0	. 162E-0	-922E-	.281E-0	.790E-0	1-412E-06	-121E-0	.954E-0	-199E-	. 828E-0
= 23.000, C DENSITY GM/CM3	3.536E-11	5.44.1E-12	3-004E-12		1.210E-12	8.535E-13	5.945E-13	4.549E-15	2.403E-13	1.4748-13	9.166E-14	5.872E-14	3.855E-14	2.585E-14		1.766E-14		- 1	0. LC1E-15	-	3.256E-15	2.399E15	1.783E-15	1.334E-15	1.005E-15	7.616E-16	2.800E-16	4-439E-16	5.4 LZE-16	2.633E-16	2.040E-16	1.587E-16	1.239E-16	7. / 10E-1/	(-039E-1/
IN HOURS)	355 515	648	847		918	9,6	7701	1059	2	1150	11.74	1191	1203	1211		1217	1221	#221	0 2 2 2	977	1229	1230	1231	12.52	1232	1233	1233	1254	12.54	<del>1</del> 5.71	1235	12.55	1235	5251	1233
TIME (IN ALT KM	120	0 1 1	160		170	0 0	0 6 6	220	7.50	240	260	280	300	320	i	340	000	000	2 2	7	044	100	180	200	220	540	000	085	9 6	020	049	000	080	130	071

NASA TN D-1443  National Aeronautics and Space Administration.  TIME-DEPENDENT STRUCTURE OF THE UPPER ATMOSPHERE. Isadore Harris and Wolfgang Priester. July 1962. 71p. OTS price, \$2.00.  (NASA TECHNICAL NOTE D-1443)  The physical properties of the upper atmosphere are determined principally by heat conduction, heat sources, and the barometric law. An analysis of the integro-differential equation describing these physical processes has been carried out. It is found that heating of the thermosphere due to absorption of the solar extreme ultraviolet (EUV) radiation alone cannot explain the observed diurnal variation of density and temperature, since it would yield a maximum of the soperies at about 17h local time, instead of 14h where it is observed. Secondly, if the EUV flux is adjusted to give the observed average temperature, then the amplitude of the diurnal density variation would be much too large compared to the observed amplitude. Thirdly, it would require an extremely high efficiency for the conversion of EUV radiation	I. Harris, Isadore II. Priester, Wolfgang III. NASA TN D-1443 (Initial NASA distribution: 6, Astronomy; 16, Cosmochemistry; 21, Geophysics and geodesy; 30, Physics, atomic and molecular; 31, Physics, nuclear and particle.)	NASA TN D-1443  National Aeronautics and Space Administration.  TIME-DEPENDENT STRUCTURE OF THE UPPER ATMOSPHERE. Isadore Harris and Wolfgang Priester. July 1962. 71p. OTS price, \$2.00.  (NASA TECHNICAL NOTE D-1443)  The physical properties of the upper atmosphere are determined principally by heat conduction, heat sources, and the barometric law. An analysis of the integro-differential equation describing these physical processes has been carried out. It is found that heating of the thermosphere due to absorption of the solar extreme ultraviolet (EUV) radiation alone cannot explain the observed diurnal variation of density and temperature, since it would yield a maximum of these properties at about 17h local time, instead of 14h where it is observed. Secondly, if the EUV flux is adjusted to give the observed average temperature, then the amplitude of the diurnal density variation would be much too large compared to the observed amplitude. Thirdly, it would require an extremely high efficiency for the conversion of EUV radiation	I. Harris, Isadore II. Priester, Wolfgang III. NASA TN D-1443 (Initial NASA distribution: 6, Astronomy; 16, Cosmochemistry; 21, Geophysics and geodesy; 30, Physics, atomic and molecular; 31, Physics, nuclear and particle.)
NASA TN D-1443  National Aeronautics and Space Administration.  TIME-DEPENDENT STRUCTURE OF THE UPPER ATMOSPHERE. Isadore Harris and Wolfgang Priester. July 1962. 71p. OTS price, \$2.00.  (NASA TECHNICAL NOTE D-1443)  The physical properties of the upper atmosphere are determined principally by heat conduction, heat sources, and the barometric law. An analysis of the integro-differential equation describing these physical processes has been carried out. It is found that heating of the thermosphere due to absorption of the solar extreme ultraviolet (EUV) radiation alone cannot explain the observed diurnal variation of density and temperature, since it would yield a maximum of these properties at about 17h local time, instead of 14h where it is observed. Secondly, if the EUV flux is adjusted to give the observed average temperature, then the amplitude of the diurnal density variation would be much too large compared to the observed amplitude. Thirdly, it would require an extremely high efficiency for the conversion of EUV radiation	I. Harris, Isadore II. Priester, Wolfgang III. NASA TN D-1443 (Initial NASA distribution: 6, Astronomy; 16, Cosmochemistry; 21, Geophysics and geodesy; 30, Physics, atomic and molecular; 31, Physics, nuclear and particle.)	NASA TN D-1443  National Aeronautics and Space Administration.  TIME-DEPENDENT STRUCTURE OF THE UPPER ATMOSPHERE. Isadore Harris and Wolfgang Priester. July 1962. 71p. OTS price, \$2.00.  (NASA TECHNICAL NOTE D-1443)  The physical properties of the upper atmosphere are determined principally by heat conduction, heat sources, and the barometric law. An analysis of the integro-differential equation describing these physical processes has been carried out. It is found that heating of the thermosphere dury and analysis of the solar extreme ultraviolet (EUV) radiation alone cannot explain the observed durmal variation of density and temperature, since it would yield a maximum of these properties at about 17h local time, instead of 14h where it is observed. Secondly, if the EUV flux is adjusted to give the observed average temperature, then the amplitude of the diurnal density variation would be much too large compared to the observed amplitude. Thirdly, it would require an extremely high efficiency for the conversion of EUV radiation	I. Harris, Isadore II. Priester, Wolfgang III. NASA TN D-1443 (Initial NASA distribution: 6, Astronomy; 16, Cosmochemistry; 21, Geophysics and geodesy; 30, Physics, atomic and molecular; 31, Physics, nuclear and particle.)

## NASA TN D-1443

sity, pressure, scale height, mean molecular weight, and the number densities of N2, O2, O, He and H) are given as a function of local time and for the altidensities. There is evidence that this additional heat source derives its energy ultimately from the solar corpuscular radiation. The results of calculations are presented for a model in the equatorial and temaverage solar activity corresponds to a solar radiation flux of 200  $\times$  10-22 W/m2-cps at 10.7 cm wave-The physical properties (temperature, den-Thus, it is necessary to have another heat source in obtained that is in good agreement with the observed addition to the absorption of EUV radiation. If an additional heat source is used, with a maximum at about 9h local time and a flux of 1 erg/cm²-sec, a perate zones of the earth for those times when the time-dependent model of the upper atmosphere is nto heat (i.e., comparing the required flux with Hinteregger's measurements of the EUV flux). udes between 120 and 2050 km. length.

## **NASA TN D-1443**

densities. There is evidence that this additional heat sity, pressure, scale height, mean molecular weight, are presented for a model in the equatorial and temperate zones of the earth for those times when the average solar activity corresponds to a solar radiation flux of 200  $\times$  10-22 W/m²-cps at 10.7 cm wavelength. The physical properties (temperature, denand the number densities of N2, O2, O, He and H) are given as a function of local time and for the alti-Thus, it is necessary to have another heat source in obtained that is in good agreement with the observed source derives its energy ultimately from the solar corpuscular radiation. The results of calculations addition to the absorption of EUV radiation. If an about 9h local time and a flux of 1 erg/cm²-sec, a additional heat source is used, with a maximum at time-dependent model of the upper atmosphere is into heat (i.e., comparing the required flux with Hinteregger's measurements of the EUV flux). udes between 120 and 2050 km.

## NASA TN D-1443

sity, pressure, scale height, mean molecular weight, and the number densities of N₂, O₂, O, He and H) are given as a function of local time and for the altidensities. There is evidence that this additional heat are presented for a model in the equatorial and temlength. The physical properties (temperature, denobtained that is in good agreement with the observed average solar activity corresponds to a solar radiation flux of 200  $\times$  10-22 W/m²-cps at 10.7 cm wave-Thus, it is necessary to have another heat source in source derives its energy ultimately from the solar corpuscular radiation. The results of calculations addition to the absorption of EUV radiation. If an additional heat source is used, with a maximum at about 9h local time and a flux of 1 erg/cm²-sec, a perate zones of the earth for those times when the time-dependent model of the upper atmosphere is into heat (i.e., comparing the required flux with Hinteregger's measurements of the EUV flux). udes between 120 and 2050 km.

## NASA TN D-1443

sity, pressure, scale height, mean molecular weight, and the number densities of N₂, O₂, O, He and H) are given as a function of local time and for the altidensities. There is evidence that this additional heat The physical properties (temperature, denare presented for a model in the equatorial and temaverage solar activity corresponds to a solar radiation flux of  $200 \times 10^{-22} \text{ W/m}^2$ -cps at 10.7 cm wave-Thus, it is necessary to have another heat source in obtained that is in good agreement with the observed source derives its energy ultimately from the solar The results of calculations addition to the absorption of EUV radiation. If an additional heat source is used, with a maximum at about 9h local time and a flux of 1 erg/cm²-sec, a perate zones of the earth for those times when the time-dependent model of the upper atmosphere is into heat (i.e., comparing the required flux with Hinteregger's measurements of the EUV flux). tudes between 120 and 2050 km. corpuscular radiation. length.

NASA

ASAM

ASAM